



Floor Stand Series

G2460FS - 24U

P2460FS - 24U



GV INDUSTRIES SDN. BHD

| G-Series | P-Series |
|----------------------------------|-----------------------------|
| | |
| FRONT TEMPERED GLASS DOOR | FULL PERFORATED DOOR |

Features & Specifications

- Lockable PERFORATED / TEMPERED GLASS front swing door
- Lockable PERFORATED rear swing door
- Lockable detachable quick release side panels
- 1.5mm thickness panel mounting members
- 19" server compatible panel mounting members
- 40 sets of M6 caged nuts and screws
- Roof mount fan for suitable ventilation system
- 2 pcs equipment trays
- 2 pcs ventilation fans
- 1 set of castor wheels c/w front braking system
- Side vertical cable management panel
- 13A power point channel complete socket
- Finished high quality epoxy powder coating (Black)



Wheel Stopper



Equipment Tray




19" 5 Gang Power Distribution



Ventilation Fan



Earthing cable



Side Panel Latch

| Model | Capacity (U) | Height (mm) | Width (mm) | Depth (mm) | Packing Dimension (H*W*D) | Weight (kg) |
|---------|--------------|-------------|------------|------------|---------------------------|-------------|
| P2460FS | 24 | 1200 | 600 | 600 | 1210 x 610 x 610 | 48 |
| G2460FS | 24 | 1200 | 600 | 600 | 1210 x 610 x 610 | 49 |

Black
 Grey
 Beige

* **P = perforated door, G = Tempered glass door**

* **Customized sizes available upon request**

* **Product shown is for illustration purpose only**



GV INDUSTRIES SDN. BHD
 NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,
 Taman Indah Subang Uep, 47150 Subang Jaya,
 Selangor Darul Ehsan.
 +603 - 8081 2216 sales@gvisb.com.my

Penang Branch
 737-6-9, Sri Nibong Complex,
 Jalan Sultan Azlan Shah,
 11900 Penang
 +604 - 642 8753

Johor Branch
 No.49 & 49A, Jalan Pulai 23,
 Taman Pulai Utama, 81300
 Skudai, Johor, Malaysia
 +607 - 520 5236