



Floor Stand Series

G2860FS - 28U

P2860FS - 28U



GV INDUSTRIES SDN. BHD

G-Series	P-Series
FRONT TEMPERED GLASS DOOR	FULL PERFORATED DOOR

Features & Specifications

- Lockable PERFORATED / TEMPERED GLASS front swing door
- Lockable PERFORATED rear swing door
- Lockable detachable quick release side panels
- 1.5mm thickness panel mounting members
- 19" server compatible panel mounting members
- 40 sets of M6 caged nuts and screws
- Roof mount fan for suitable ventilation system
- 2 pcs equipment trays
- 2 pcs ventilation fans
- 1 set of castor wheels c/w front braking system
- Side vertical cable management panel
- 13A power point channel complete socket
- Finished high quality epoxy powder coating (Black)



Wheel Stopper



Equipment Tray



19" 5 Gang Power Distribution



Ventilation Fan



Earthing cable



Side Panel Latch

Model	Capacity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Weight (kg)
P2860FS	28	1370	600	600	1380 x 610 x 610	53
G2860FS	28	1370	600	600	1380 x 610 x 610	54

Black
 Grey
 Beige

* P = perforated door, G = Tempered glass door

* Customized sizes available upon request

* Product shown is for illustration purpose only



GV INDUSTRIES SDN. BHD

NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang, Taman Indah Subang Uep, 47150 Subang Jaya, Selangor Darul Ehsan.

+603 - 8081 2216 sales@gvisb.com.my

Penang Branch

737-6-9, Sri Nibong Complex, Jalan Sultan Azlan Shah, 11900 Penang

+604 - 642 8753

Johor Branch

No.49 & 49A, Jalan Pulai 23, Taman Pulai Utama, 81300 Skudai, Johor, Malaysia

+607 - 520 5236