

Floor Stand Series




Features & Specifications

- Internal system base with vented roof
- 2.0mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
- Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 2.0mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 2 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- 13A power point channel complete socket
- Finished high quality epoxy powder coating (Black)



Top Cover
Vented Design



Equipment
Tray



19" 5 Gang
Power Distribution



Earthing
cable



Side Panel
Latch



19" Panel
Mounting

Model	Capacity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Weight (kg)
QP1560FS	15	812	600	600	822 x 610 x 610	61
QP1860FS	18	945	600	600	955 x 610 x 610	65.5
QP2460FS	24	1212	600	600	1222 x 610 x 610	73.5
QP2860FS	28	1390	600	600	1400 x 610 x 610	79.5
QP3360FS	33	1612	600	600	1622 x 610 x 610	88
QP3760FS	37	1790	600	600	1800 x 610 x 610	93
QP4260FS	42	2012	600	600	2022 x 610 x 610	101.5
QP42100FS	42	2012	600	1000	2022 x 610 x 1010	113

Black
 Grey
 Beige

* Customized sizes available upon request

GV INDUSTRIES SDN. BHD

NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,
Taman Indah Subang Uep, 47150 Subang Jaya,
Selangor Darul Ehsan.

+603 - 8081 2216 sales@gvisb.com.my

Penang Branch

737-6-9, Sri Nibong Complex,
Jalan Sultan Azlan Shah,
11900 Penang

+604 - 642 8753

Johor Branch

No.49 & 49A, Jalan Pulai 23,
Taman Pulai Utama, 81300
Skudai, Johor, Malaysia

+607 - 520 5236