









Floor Stand

QP3360FS - 33U



Features & Specifications

- Internal system base with vented roof
- 1.5mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
- Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 1.5mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 2 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- 13A power point channel complete socket
- Finished high quality epoxy powder coating (Black)



Vented Design

Top Cover



Equipment Tray



19" 5 Gang Power Distribution



Earthing cable



Side Panel Latch



19" Panel Mounting

Model	Capasity (U)	Height (mm)	Width (mm)	The state of the s	Packing Dimension (H*W*D)	Weight (kg)
QP3360FS	33	1612	600	600	1635 x 612 x 612	88





Beige

Product shown is for illustration purpose only



GV INDUSTRIES SDN. BHD

NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang, Taman Indah Subang Uep, 47150 Subang Jaya, Selangor Darul Ehsan.

sales@gvisb.com.my

Penang Branch 737-6-9, Sri Nibong Complex, Jalan Sultan Azlan Shah, 11900 Penang

Johor Branch No.49 & 49A, Jalan Pulai 23, Taman Pulai Utama, 81300 Skudai, Johor, Malaysia +607 - 520 5236

^{*} Customized sizes available upon request