

Floor Stand

Series

QP3760FS - 37U



Features & Specifications

- Internal system base with vented roof
- 1.5mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
- Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 1.5mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 2 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- 13A power point channel complete socket
- Finished high quality epoxy powder coating (Black)



*Top Cover
Vented Design*



*Equipment
Tray*



*19" 5 Gang
Power Distribution*



*Earthing
cable*



*Side Panel
Latch*



*19" Panel
Mounting*

Model	Capacity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Weight (kg)
QP3760FS	37	1790	600	600	1815 x 612 x 612	93

Black
 Grey
 Beige

* Customized sizes available upon request
 * Product shown is for illustration purpose only



GV INDUSTRIES SDN. BHD
 NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,
 Taman Indah Subang Uep, 47150 Subang Jaya,
 Selangor Darul Ehsan.
 +603 - 8081 2216 sales@gvisb.com.my

Penang Branch
 737-6-9, Sri Nibong Complex,
 Jalan Sultan Azlan Shah,
 11900 Penang
 +604 - 642 8753

Johor Branch
 No.49 & 49A, Jalan Pulai 23,
 Taman Pulai Utama, 81300
 Skudai, Johor, Malaysia
 +607 - 520 5236