

# Floor Stand

# Series

**QP1870FS - 18U**



## Features & Specifications

- Internal system base with vented roof
- 1.5mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
- Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 1.5mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 2 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- 13A power point channel complete socket
- Finished high quality epoxy powder coating (Black)



*Top Cover  
Vented Design*



*Equipment  
Tray*



*19" 5 Gang  
Power Distribution*



*Earthing  
cable*



*Side Panel  
Latch*



*19" Panel  
Mounting*

Model	Capacity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Weight (kg)
QP1870FS	18	945	600	700	970 x 612 x 712	66.5

Black
  Grey
  Beige

\* Customized sizes available upon request  
 \* Product shown is for illustration purpose only

**GV INDUSTRIES SDN. BHD**

NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,  
 Taman Indah Subang Uep, 47150 Subang Jaya,  
 Selangor Darul Ehsan.  
 +603 - 8081 2216    sales@gvisb.com.my

**Penang Branch**

737-6-9, Sri Nibong Complex,  
 Jalan Sultan Azlan Shah,  
 11900 Penang  
 +604 - 642 8753

**Johor Branch**

No.49 & 49A, Jalan Pulai 23,  
 Taman Pulai Utama, 81300  
 Skudai, Johor, Malaysia  
 +607 - 520 5236

