







oor Stand






Features & Specifications


- Internal system base with vented roof
- 2.0mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
 Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 2.0mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 4 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- Power Distribution Unit(PDU) (PS8001/BAM3205)
- Finished high quality epoxy powder coating (Black)
- Support weight up to 1500kg













Top Cover Vented Design

Equipment Tray

19" 5 Gang Power Distribution

Earthing cable

Side Panel Latch

19" Panel Mounting

Model	Capasity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Weight (kg)	PDU (nos)
X1560FS	15	850	600	600	862 x 610 x 610	91	5
X1860FS	18	980	600	600	992 x 610 x 610	95.5	5
X2460FS	24	1250	600	600	1262 x 610 x 610	102.5	5
X2860FS	28	1420	600	600	1432 x 610 x 610	109.5	5
X3360FS	33	1650	600	600	1662x 610 x 610	118	12
X3760FS	37	1830	600	600	1842 x 610 x 610	123	12
X4260FS	42	2050	600	600	2062 x 610 x 610	131.5	12
X42100FS	42	2050	600	1000	2062 x 610 x 1010	143	12

Black

Grey

Beige

^{*} Customized sizes available upon request



GV INDUSTRIES SDN. BHD

NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang, Taman Indah Subang Uep, 47150 Subang Jaya, Selangor Darul Ehsan.

Penang Branch 737-6-9, Sri Nibong Complex, Jalan Sultan Azlan Shah, 11900 Penang

Johor Branch No.49 & 49A, Jalan Pulai 23, Taman Pulai Utama, <u>81300</u>