

Floor Stand

X SERIES



Features & Specifications

- Internal system base with vented roof
- 2.0mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
- Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 2.0mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 4 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- Power Distribution Unit(PDU) (PS8001/BAM3205)
- Finished high quality epoxy powder coating (Black)
- Support weight up to 1500kg



Top Cover
Vented Design



Equipment
Tray



19" 5 Gang
Power Distribution



Earthing
cable



Side Panel
Latch



19" Panel
Mounting

Model	Capacity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Weight (kg)	PDU (nos)
X1570FS	15	850	600	700	862 x 610 x 710	92	5
X1870FS	18	980	600	700	992 x 610 x 710	96.5	5
X2470FS	24	1250	600	700	1262 x 610 x 710	104.5	5
X2870FS	28	1420	600	700	1432 x 610 x 710	110.5	5
X3370FS	33	1650	600	700	1662x 610 x 710	119	12
X3770FS	37	1830	600	700	1842 x 610 x 710	124	12
X4270FS	42	2050	600	700	2062 x 610 x 710	132.5	12
X42100FS	42	2050	600	1000	2062 x 610 x 1010	143	12

Black
 Grey
 Beige

* Customized sizes available upon request

GV INDUSTRIES SDN. BHD

NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,
Taman Indah Subang Uep, 47150 Subang Jaya,
Selangor Darul Ehsan.

+603 - 8081 2216 sales@gvish.com.my

Penang Branch

737-6-9, Sri Nibong Complex,
Jalan Sultan Azlan Shah,
11900 Penang

+604 - 642 8753

Johor Branch

No.49 & 49A, Jalan Pulai 23,
Taman Pulai Utama, 81300
Skudai, Johor, Malaysia

+607 - 520 5236