

Floor Stand

X SERIES

XP3770FS - 37U



Features & Specifications

- Internal system base with vented roof
- 2.0mm thickness metal frame
- Lockable honeycomb perforated front door c/w push lock
- Lockable honeycomb perforated rear swing door
- Lockable detachable side panels with latch
- 19" server compatible mounting elements
- 2.0mm thickness panel mounting members with "U" marking
- 40 sets M6 caged nuts & screws
- Heavy duty castor wheels
- Adjustable feet
- 4 ball bearing fans with fan tray
- 2 equipment trays
- Side vertical metal cable management panel
- Power Distribution Unit(PDU) (PS8001/BAM3205)
- Finished high quality epoxy powder coating (Black)
- Support weight up to 1500kg



Top Cover
Vented Design



Equipment
Tray



Ball Bearing
Fans



Earthing
cable



Side Panel
Latch



19" Panel
Mounting

Model	Capacity (U)	Height (mm)	Width (mm)	Depth (mm)	Packing Dimension (H*W*D)	Weight (kg)	PDU (nos)
XP3770FS	37	980	600	700	992 x 612 x 712	96.5	5

Black
 Grey
 Beige

* Customized sizes available upon request
 * Product shown is for illustration purpose only



GV INDUSTRIES SDN. BHD
 NO. 28 & 30, Jalan TS 6/7, Taman Perindustrian Subang,
 Taman Indah Subang Uep, 47150 Subang Jaya,
 Selangor Darul Ehsan.
 +603 - 8081 2216 sales@gvisb.com.my

Penang Branch
 737-6-9, Sri Nibong Complex,
 Jalan Sultan Azlan Shah,
 11900 Penang
 +604 - 642 8753

Johor Branch
 No.49 & 49A, Jalan Pulai 23,
 Taman Pulai Utama, 81300
 Skudai, Johor, Malaysia
 +607 - 520 5236