













CABLE, POWER & ACCESSORIES PRICE LIST - MARCH 2017








*PRICE / SPECIFICATION / DESIGN SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

PICTURE	ITEM DESCRIPTION	MODEL	PRICE
	Cables		
	All-Link Siamese RG59 Coaxial + VDE Power cable (30/0.15mm); 2-in-1 100m Roll; VDE cable material is Aluminium (LC); 9.3ohm per 100m Suitable for D-I-Y, Weight 6.2kg	CCC003	283.20
	All-Link Siamese RG59 Coaxial + VDE Power cable (30/0.15mm); 2-in-1 250m Roll; VDE cable material is Aluminium (LC); 9.3ohm per 100m Suitable for D-I-Y, Weight 15.5kg	CCC004	528.64
	All-Link RG59 Coaxial cable; CCS Inner Conductor, LC 95% Braiding Signal Distance 300m, Indoor use 305m Drum; 75ohm, PE Insulation, Weight 11.8kg	S112	377.60
	All-Link RG59 Coaxial cable Signal Distance 700m, Indoor use; Foam PE Insulation Bare Copper 0.75mm Inner Conductor, LC 95% Braiding 500m Drum; 75ohm; Weight 19.1kg	A128	887.36
	All-Link RG6 Coaxial cable Signal Distance 900m for 960H camera, 500m for 720P cameras, Indoor use only Bare Copper 1.0mm Inner Conductor, LC Braiding 95% 500m Drum; 75ohm; Weight 22kg	A112	925.12
	All-Link RG59 Outdoor Coaxial cable Signal Distance 700m, Outdoor use; Jelly-Filled PE Insulation Bare Copper 0.65mm Inner Conductor, Bare copper Braiding 95% 500m Drum; 75ohm; Weight 23.6kg	D112PE	1736.96
	All-Link RG6 Outdoor Coaxial cable Signal Distance 900m, Outdoor use; Jelly-Filled PE Insulation Bare Copper 1.0mm Inner Conductor, LC Braiding 95% 500m Drum; 75ohm; Weight 25.5kg	A112PE	1736.96
 	Belden (USA) RG6 Coaxial cable Professional cabling, suitable for distance over 300m Solid Bare Copper Covered Steel; Foam PE insulation; Aluminium Braid Shield 60% 305m Drum; 18AWG, 1.02 sq mm, 75ohm, Weight 14.2kg; PVC jacket (black)	9116S	613.60
 	Belden (USA) RG6 Coaxial cable (3Ghz support) Professional cabling, suitable for distance over 350m; Solid Bare Copper Covered Steel; Foam PE insulation; Aluminium Braid Shield 60% 305m Drum; 18AWG, 1.02 sq mm, 75ohm, Weight 14.2kg; PVC jacket (black)	YJ52818	670.24
 	Lapp Kabel (Germany) 2-pairs Multi-Conductor Low Capacitance Computer Cable Normally used for Data Highway (RS232, RS422, RS485) Unitronic ST 2x2x24AWG (7x0.20mm) Tinned Copper Strands; (Part#: 3800950) Equivalent to Belden 1419A; Grey outer jacket, Weight 15.5kg	LAP-1419A	1132.80





PICTURE	ITEM DESCRIPTION	MODEL	PRICE
	Lapp Kabel (Germany) RG59 Flexible Coaxial cable - for Elevator use; 305m Drum 22 gauge Stranded (7 x 0.254mm) Bare copper center conductor (Part#: 3801420) Outer Shield Material: Bare copper braid 95%, Weight 16.1kg Equivalent to Belden 9259; Black outer jacket	LAP-59FLEX	1982.40
	Lapp Kabel (Germany) Unitronic Cat6 UTP Cable; 250Mhz 305m Box; Full solid copper; 4 x 2 x 23 AWG (Part#: 3801501K) Beige colour jacket, Weight 13.1kg	LAP-CAT6	755.20
	Lapp Kabel (Germany) Unitronic Cat6 Flexible UTP Cable; 250Mhz - for Elevator use 305m Drum; Stranded Bare Copper; 4 x 2 x 24 AWG (Part#: 3801401) Beige colour jacket, Weight 13kg	LAP-C6FLEX	1000.64
	Schneider Electric (France) Digilink Cat5e UTP Cable 305m Box; Full solid copper Light Grey colour, Weight 9.5kg	SCH-CAT5E	641.92
	Schneider Electric (France) Digilink Cat6 UTP Cable 305m Box; Full solid copper Blue colour, Weight 12.4kg	SCH-CAT6	859.04
	Belden (USA) Cat5e UTP Cable 305m Box; Full solid copper 24AWG Blue colour PVC jacket, Weight 10kg	1583A	736.32
	Belden (USA) Cat6 UTP Cable 305m Box; Full solid copper 24AWG Blue colour PVC jacket, Weight 16kg	7814A	981.76
	All-Link Cat5e Jelly-Filled UTP Outdoor Cable 500m Drum; PE Jacket (Black); Full Copper Conductor Black colour, Weight 22.2kg	C5E-PE	1529.28
	All-Link Cat6 Jelly-Filled UTP Outdoor Cable 500m Drum; PE Jacket (Black); Full Copper Conductor Black colour, Weight 28.5kg	C6-PE	1944.64
	All-Link VDE 2-core Power Cable 100m Roll; 30/015mm Aluminium (LC); PE inner jacket Weight 1.9kg; 11.5ohm per 100m; Black PVC outer jacket	VDE100LC	84.96
	FAJAR VDE 2-core Power Cable 100m Roll; 23/0.15mm Bare Copper (BC) Weight 2.7kg; 5.6ohm per 100m; Black PVC outer jacket	VDE100BC	103.84
	FAJAR 4-core Alarm cable 100m Roll; 7/0.20mm; Bare Copper (BC) Weight 2.4kg; 8.8ohm per 100m; White PVC outer jacket	AL100BC	103.84
	FAJAR 4-core Alarm cable 100m Roll; 7/0.20mm; Tinned Pure Copper (TC) Weight 2.4kg; 8.8ohm per 100m; White PVC outer jacket	AL100TC	122.72
	Xpro Telephone cable 4-core (0.50mm) 250m Roll, Copper Clad Aluminium Grey colour jacket	TL250CCA	207.68
	All-Link Telephone cable 4-core (0.50mm) 250m Roll, Full Bare Copper Grey colour jacket; 27.3ohm over 250m	TL250BC	311.52

PICTURE	ITEM DESCRIPTION	MODEL	PRICE
	RGB (VGA) Cable with 2-core (Male-Male) - 3 Analog + 6 Signal		
	Length 1.5m, Shielded, Weight 300g (3 Analog + 4 Signal), Flat type	RGB1MM	22.66
	Length 5m, Shielded, Weight 500g (3 Analog + 4 Signal), Flat type	RGB5MM	47.20
	Length 10m, Shielded, Weight 800g	RGB10MM	66.08
	Length 15m, Shielded, Weight 1.2kg	RGB15MM	92.51
	Length 20m, Shielded, Weight 2.1kg	RGB20MM	122.72
	Length 30m, Shielded, Weight 2.2kg	RGB30MM	183.14
	Length 50m, Shielded, Weight 3.6kg	RGB50MM	368.16
	HDMI(M) to HDMI(M) cable with Nylon Net; Version 1.3; Full copper		
	Length 2m	HDMI2	32.10
	Length 5m	HDMI5	52.86
	Length 10m	HDMI10	83.07
	Length 15m	HDMI15	154.82
	Length 20m	HDMI20	245.44
	Length 25m	HDMI25	509.76
	Length 30m	HDMI30	670.24
	Cat6 Flat Type UTP Patch Cable - Full Copper (Light Blue colour)		
	1m	PC100(Cat6)	13.22
	2m	PC200(Cat6)	15.10
	3m	PC300(Cat6)	18.88
	5m	PC500(Cat6)	22.66
	10m	PC1000(Cat6)	47.20



	Signal Connectors		
	RG59 BNC Connectors (Male) Twist-On Type (Full Copper Inner Conductor), Weight 14g	BNC-TO59	2.83
	RG6 BNC Connectors (Male) Twist-On Type (Full Copper Inner Conductor), Weight 14g	BNC-TO6	
	RG59 BNC Connectors (Male) Crimp Type (Full Copper Inner Conductor), Weight 10g	BNC-CR59	3.21
RG6 BNC Connectors (Male) Crimp Type (Full Copper Inner Conductor), Weight 10g	BNC-CR6		
	BNC Female to Female Connector (Coupler) Weight 10g	BNC001	3.21
	RCA (Female) to BNC (Male) Connector Weight 10g	BNC002	
	BNC (Female) to RCA (Male) Connector Weight 10g	RCA003	
	RG59 F Connector Twist-On type, Weight 10g	RCA001	1.51
	RG6 F Connector Twist-On type, Weight 10g	RCA002	
	RCA (Male) Connector F type base, Weight 10g	RCA004	1.70
	F Connector joint Weight 10g	FC001	3.40
	BNC T-Joint Connector BNC (Male) Split to 2 x BNC (Female), Weight 10g	BNC003	3.78





PICTURE	ITEM DESCRIPTION	MODEL	PRICE
	RCA (Male) to BNC (Male) Connector Weight 10g	RCA005	3.40
	RCA (Male) Screw on Terminal Weight 10g	RCA006	
	BNC (Male) Screw on Terminal Weight 10g	BNC006	
	BNC (Male) Connector F type base, Weight 10g	BNC007	2.83
	BNC Crimper for RG59 and RG6 Coaxial cables Weight 510g	BNC004	84.96
	High Density Mini VGA Gender Changer Male-Male	HD15MM	18.88
	High Density Mini VGA Gender Changer Female-Female	HD15FF	18.88








	Data Connectors Cat5e Modular Jack (Keystone) 8P8C	MJ(Cat5e)	6.61
	Cat6 Modular Jack (Keystone) 8P8C	MJ(Cat6)	8.50
	RJ11 Cat3 (Telephone) Modular Jack (Keystone) 6P4C	MJ(Cat3)	4.72
	Single-gang Modular Jack Faceplate	FP1MJ	4.72
	Double-gang Modular Jack Faceplate	FP2MJ	6.61
	Single-gang RJ11 Jack Faceplate 6P4C	TFP1(RJ11)	4.72
	Double-gang RJ11 Jack Faceplate 6P4C	TFP2(RJ11)	6.61
	RJ11 Plug (6P4C) 6 position 4 contacts; Telephone use Weight 2g	RJ11-6P4C	0.57
	Cat5e RJ45 Modular Plug (8P8C) For use in Telecommunication, Data & Video Transmission Weight 2g	RJ45(Cat5e)	1.04




PICTURE	ITEM DESCRIPTION	MODEL	PRICE
	Cat6 RJ45 Modular Plug (8P8C) For use in Telecommunication, Data & Video Transmission Weight 2g	RJ45(Cat6)	1.60
	RJ45 Inline Coupler 8-pins Female to 8-pins Female Socket	RJ45COUP	3.40
	Coloured Rubber Boots for Cat5e / Cat6 cable	RBC5-CLR	0.60
	Colours available for Cat5e: Clear, Red, Blue & Yellow	RBC5-RED	
		RBC5-BLU	
	Colours available for Cat6: Clear, Green, Grey, Purple	RBC5-YEL	
		RBC6-CLR	
		RBC6-GRN	
	Minimum 10pcs per Order	RBC6-GRY	
	RBC6-PUR		
	Crimper for RJ45 and RJ11 Connectors Suitable for 8P8C, 6P6C, 4P4C	RJC001	95.00







	Datasheen Network Products			
		Cat5e Patch Cable (0.5m, 1m, 3m and 5m) Colours available: Orange, Black, Light Blue (depend on stock availability) Meet the requirement of Fast Ethernet & EIA/TIA applications; 100% Tested 30µ Gold plating RJ45 plug Cat5e Cable; UL certificated/RoHS compliant cable Insert-molded strain relief to enhance life span	PC50(Cat5e) PC100(Cat5e) PC300(Cat5e) PC500(Cat5e)	4.72 5.66 9.44 12.84
		Datasheen Cat5e RJ45 High Quality Modular Plug (8P8C) - 100pcs per box Patent Contact Blade: 3-Prong fits both stranded and solid wire Gold Plating: 50µ; RoHS Compliant; ISO 9001 certified; 100% Tested with X ray machine	RP5U	132.16
		Datasheen Cat6 RJ45 High Quality Modular Plug (8P8C) - 100pcs per box Patent Contact Blade: 3-Prong fits both stranded and solid wire Gold Plating: 50µ; RoHS Compliant; ISO 9001 certified; 100% Tested with X ray machine	RP6U	169.92
		High Quality Cat5e RJ45 Module Patent Contact Blade; High Quality ABS material ISO 9001 certified; 100% Tested with X ray machine	D15K	13.22
	High Quality Cat6 RJ45 Module Patent Contact Blade; High Quality ABS material ISO 9001 certified; 100% Tested with X ray machine	D16K	16.99	
	24-port Patch Panel Frame for 19" Standard Rack Modular Jacks not included (buy separately); only use D16K or D15K Modular Jack Material: Steel + ABS	D24P	113.28	
	Cable Management Panel for 19" Standard Rack Size: 480 x 180 x 40mm Material: Steel + ABS	CM01HC	66.08	
	Sliding Shelf (Tray) for 600-1000mm Depth Racks Material: Vented Steel Item Weight: 4kg	SU00B	151.04	
	19" Standard Rack Power Distribution Unit (PDU) - limited stock 6-port Universal Sockets PVC Case; Neon Switch; c/w 2 meter cable; Complete Earth System	PU06AU	135.94	




PICTURE	ITEM DESCRIPTION	MODEL	PRICE
	Fiber Optic Series Indoor 2-core FTTH Fiber Optic Single Mode cable Price is per meter cut; Full drum is 500m	2C-SM-IN	4.72
	Outdoor 4-core Fiber Optic Single Mode cable; Jelly-Filled with 2-wire Armored jacket Price is per meter cut; Full drum is 1500m	4C-SM-OT	6.61
	Outdoor 4-core Fiber Optic Single Mode cable; Jelly-Filled with 2-wire Armored jacket Price is per meter cut; Full drum is 1500m	8C-SM-OT	9.44
	Simplex Single Mode Fiber Patch Cord 3m length; SC-SC Connector	SSM3-SCSC	33.98
	Simplex Single Mode Fiber Patch Cord 3m length; FC-FC Connector	SSM3-FCFC	33.98
	Single Fiber Single Mode Fiber Patch Cord 3m length; LC-LC Connector	SSM3-LCLC	33.98
	Single Fiber Single Mode Fiber Patch Cord 3m length; FC-SC Connector	SSM3-FCSC	33.98
	Single Fiber Single Mode Fiber Patch Cord 3m length; LC-SC Connector	SSM3-LCSC	33.98
	SC Fast Connector Easy to use, require only simple fiber tools	FAST-SC	28.32
	FC Fast Connector Easy to use, require only simple fiber tools	FAST-FC	28.32
	2-port (Duplex) SC-SC Flange (Coupler)	FL-2SCSC	15.10
	1-port (Simplex) SC-SC Flange (Coupler)	FL-1SCSC	7.55
	1-port (Simplex) FC-FC Flange (Coupler)	FL-1FCFC	7.55
	1-port (Simplex) FC-FC Flange (Coupler)	FL-1SCFC	7.55
	8-port FTTH Terminal Box Wall Mountable Supports 8pcs fiber flange (not included) Includes cabling rack for reliable protection	FTS108	113.28

PICTURE	ITEM DESCRIPTION	MODEL	PRICE
	24-port Fiber Optic Distribution Box 19" Rackmountable; slide out tray Supports 24pcs fiber flange (not included) Includes cabling rack for reliable protection	FDB524	339.84
	16-port Outdoor Fiber Distribution Box Wall Mountable; 2 inlet ports, 2 outlet ports Includes cabling rack for reliable protection Supports 2 units of 1x8 PLC splitter module (not included)	FDB816	339.84
	Single mode 1x8 Planar Light Wave Circuit (PLC) Splitter Module with Connectors 1 input port with 8 multiple ports for dividing optical signals Cassette type	PLC108	188.80
	Fiber FTTH ToolKit in Briefcase (NO Warranty) Includes: Cleaver, Laser, Cutter, Optical Power Meter, Pincer, Plier, Cable Stripper	FB-TOOLKIT	1661.44







	Power Adaptor (1 MONTH warranty for ALL adaptors) 12V DC Switching Power Adaptor 2000mA	PSA004	28.32
	12V DC 5A Power Adaptor For DVR / Cameras use Comes with UK 3-pin power cord	PSA007	75.52
	5V DC Switching Power Adaptor 2000mA	PSA011	37.76
	24V AC Regulated Power Adaptor 3000mA; Weight 1.3kg	PSA012	84.96
	24V DC Switching Power Adaptor 1000mA Comes with UK 3-pin power cord	PSA013	47.20
	24V DC Switching Power Adaptor 2000mA Comes with UK 3-pin power cord	PSA014	66.08
	12VDC Backup Battery for CCTV Cameras Battery capacity: 12V 1800mAh (approx. 3 hours backup for standard cameras) Comes with Power adaptor charger 12.6VDC 350mA	DC-168	103.84



	Centralised Power Supply (1 YEAR Warranty) Centralised 12VDC Switching Power Supply; Brand: Meanwell Taiwan 3A Capacity; supports up to 6 cameras; adjustable 10.2 ~ 13.8V Dimensions: 99(L) x 82(W) x 30(H) mm	LRS-35-12	84.96
	Centralised 12VDC Switching Power Supply; Brand: Meanwell Taiwan 8.5A Capacity; supports up to 16 cameras; adjustable 10.2 ~ 13.8V Dimensions: 129(L) x 97(W) x 30(H) mm	LRS-100-12	122.72
	Centralised 12VDC Switching Power Supply; Brand: Meanwell Taiwan 12.5A Capacity; supports up to 24 cameras; adjustable 10.2 ~ 13.8V Dimensions: 159(L) x 97(W) x 30(H) mm	LRS-150-12	160.48





PICTURE	ITEM DESCRIPTION	MODEL	PRICE
	Centralised 5VDC Switching Power Supply; Brand: Meanwell Taiwan 10A Capacity Dimensions: 99(L) x 98(W) x 36(H) mm	RS-50-5	141.60
	Centralised 15VDC Switching Power Supply; Brand: Meanwell Taiwan 3.3A Capacity Dimensions: 99(L) x 98(W) x 36(H) mm	RS-50-15	141.60
	Centralised 24VDC Switching Power Supply; Brand: Meanwell Taiwan 24VDC 4A Capacity Dimensions: 160(L) x 98(W) x 38(H) mm	SE-100-24	132.16
	Centralised 12V Power Supply 5A Capacity; 4ch Screw Terminal Output DC Output Voltage: 12V +/-5%; Includes Power cord *PWP for package available - ask our crew for more info	PSA12045A	94.40
	Centralised 12V Power Supply in Metal Casing 5A Capacity; 9ch Individual Output with PTC Fuse protection (resettable) DC Output Voltage: 12V +/-5%; Fuse Rating: 1.1A; Includes Power cord Dimensions: 250 x 217 x 59mm, 1.7kg, Grey	PSD12095A	198.24
	Centralised 12V Power Supply in Metal Casing 10A Capacity; 18ch Individual Output with PTC Fuse protection (resettable) DC Output Voltage: 12V +/-5%; Fuse Rating: 1.1A; Includes Power cord Dimensions: 250 x 217 x 59mm, 1.7kg, Grey	PSD121810A	245.44
	Centralised 12V Power Supply in Metal Casing 20A Capacity; 18ch Individual Output with PTC Fuse protection (resettable) DC Output Voltage: 12V +/-5%; Fuse Rating: 1.1A; Includes Power cord Dimensions: 267 x 275 x 87mm, 2.7kg, Grey	PSD121820A	415.36
	Centralised 12V Uninterruptible Power Supply in Metal Casing 3A Capacity; 4ch Individual Output with PTC Fuse Protection (resettable) Excludes battery (PBB001); Includes Power cord; actual voltage output 13.5VDC Dimensions: 264(H) x 206(W) x 86mm(D), 1.9kg, Grey; Fuse Rating: 1.1A	PSB12043A	226.56
	Centralised 12V Uninterruptible Power Supply in Metal Casing 5A Capacity; 9ch Individual Output with PTC Fuse Protection (resettable) Excludes battery (PBB001); Includes Power cord; actual voltage output 13.5VDC Dimensions: 264(H) x 206(W) x 86(D)mm, 2.2kg, Grey; Fuse Rating: 1.1A	PSB12095A	292.64
	Centralised 12V Uninterruptible Power Supply in Metal Casing 10A Capacity; 9ch Individual Output with PTC Fuse Protection (resettable) Excludes battery (PBB001); Includes Power cord; actual voltage output 13.5VDC Dimensions: 264(H) x 206(W) x 86mm(D), 2.4kg, Grey; Fuse Rating: 2A	PSB120910A	339.84
	DC Plug-Male (Screw-on type) Power connector for 12VDC Cameras	DCPM01	2.83
	DC Plug-Female (Screw-on type) Power connector for 12VDC Cameras	DCPF01	2.83
	DC Plug-Male Power connector for 12VDC Cameras Full Copper wires; High quality	DC-PLUG-M	2.83
	DC Plug-Female Power connector for 12VDC Cameras Full Copper wires; High quality	DC-PLUG-F	2.83




PICTURE	ITEM DESCRIPTION	MODEL	PRICE
	800VA Uninterruptible Power Supply (UPS) with 2 x 3-pin UK Output Built-in AVR Overload, discharge and Overcharge Protection Comes with 1 x 12V 7Ah SLA backup battery 2 years warranty	FORMULA80	294.50
	1000VA Uninterruptible Power Supply (UPS) with 4 x Universal Output Built-in AVR; Network Port Protection Short-circuit, Overload and EMI/RFI protection Comes with 2 x 12V 7Ah SLA backup battery (YUASA) 2 years warranty	C-100E	570.00
	2000VA/3000VA Uninterruptible Power Supply (UPS) - Tower (Back-to-back Order) True On Line Pure Sine Wave UPS Power factor correction; Advanced battery management to Prolong Battery Life Smart RS-232 Communication; Overload, Short Circuit, Surge and Spike Protection MX2000W: 6 x 7Ah Batteries; MX3000W: 6 x 9Ah Batteries 2 years warranty	MX2000W	3135.00
		MX3000W	3895.00




	CAL-LAB Lightning Isolators - Professional Series Module for Wall power point (230VAC 5A) Lifetime replacement exchange; burnt unit can be replaced @ RM 40 This unit can be used standalone	MDSC0039(5A)	76.00
	Module for Analog Telephone cable 4-pins RJ11 Lifetime replacement exchange; burnt unit can be replaced @ RM 30 Must be used together with another Cal-Lab device to obtain 99% protection	SP9201-ARD	57.00
	Module for LAN cable (10/100/1000Mbps) 8-pins RJ45 Lifetime replacement exchange; burnt unit can be replaced @ RM 30 Must be used together with another Cal-Lab device to obtain 99% protection	SLAN-8CG	76.00
	Module for POE using UTP cable (10/100Mbps) Lifetime replacement exchange; burnt unit can be replaced @ RM 50 This unit can be used standalone	POE-1236	133.00
	Module for BNC cable, Floating Earth Lifetime replacement exchange; burnt unit can be replaced @ RM 30 Must be used together with another Cal-Lab device to obtain 99% protection	MD-BNC-0E	72.20
	Module for 230V power outlet and phone line (for Alarm panel) Lifetime replacement exchange; burnt unit can be replaced @ RM 40 This unit can be used standalone	MDSF9512-cu(2A)	123.50
	Module for 12V DC jack Lifetime replacement exchange; burnt unit can be replaced @ RM 30 Must be used together with another Cal-Lab device to obtain 99% protection	DCJ-cu(12V1A)	57.00
	Module for 12V DC jack Lifetime replacement exchange; burnt unit can be replaced @ RM 30 Must be used together with another Cal-Lab device to obtain 99% protection	DCJ-cu(12V5A)	66.50
	Module for RS485 (Data/Signal) Lifetime replacement exchange; burnt unit can be replaced @ RM 30 Must be used together with another Cal-Lab device to obtain 99% protection	DCJ-cu(Data-5V)	57.00






PICTURE	ITEM DESCRIPTION	MODEL	PRICE
	Module for 24VAC/DC PTZ Camera with RS485 (Data/Signal) Lifetime replacement exchange; burnt unit can be replaced @ RM 30 Must be used together with another Cal-Lab device to obtain 99% protection	MD-4Ccu(24V2A)	79.80
	Mounting Base for 4*SKPX Non-replaceable Must be used together with another Cal-Lab device to obtain 99% protection	MLPX-BB	66.50
	Enclosure Box for fitting 4*MLPX-BB Non-replaceable	MLPX-BX	47.50
	Analog Plug-in Module for Trunk Line Non-replaceable To be inserted into MLPX-BB	SKPX-ARD	34.20
	Module for 230V power outlet and DSL phone line Lifetime replacement exchange; burnt unit can be replaced @ RM 50 This unit can be used standalone	SF9512-DSL	110.20
	Module for 230V Universal Power Outlet, RJ45 Gigabit LAN and RJ11 DSL Line Lifetime replacement exchange; burnt unit can be replaced @ RM 60 This unit can be used standalone	MD-NIF (8CG-DSL)	171.00

	Power & Video Transmitter over Coax (PVT) 1ch HD-CVI Video and Power over Coax One RX unit + One TX unit; supports up to 2.0MP HD-CVI and 1200TVL Analog Distance <400m (1.0MP) and <200m (2.0MP) using Full Copper RG59 24VDC 2A Power Adaptor included (PSA014)	HDPVT-CVI	228.00
	Analog 960H 8ch Video and Power over Coax - CLEAR STOCK One Receiver unit + 8 Transmitter unit Distance <500m using Full Copper RG59; Does NOT support HD-CVI/TVI/AHD/IPC Built-in Power Supply	P208	969.00

	Video Balun - 4-IN-1 HD SERIES (supports HD-CVI, TVI, AHD and 960H) 1ch HD Passive Transceiver (Balun) - 1 PAIR Unshielded twisted pair - 24AWG UTP Cat5e / Cat6 (screw terminal) Transmit distance: 200m (1080P) / 400m (720P); support PTZ function for HD-CVI Built-in TVS for surge protection; Wave Filter & Anti-Static design	CVB1001	47.50
	4ch HD Passive Transceiver (Video Balun) - 1 unit Unshielded twisted pair - 24AWG UTP Cat5e / Cat6 (RJ45 socket / screw terminal) Transmit distance: 200m (1080P) / 400m (720P); support PTZ function for HD-CVI Desktop/Wall Mount (bracket included)	CVB1004	218.50
	8ch HD Passive Transceiver (Video Balun) - 1 unit Unshielded twisted pair - 24AWG UTP Cat5e / Cat6 (RJ45 socket / screw terminal) Transmit distance: 200m (1080P) / 400m (720P); support PTZ function for HD-CVI Desktop/Wall Mount (bracket included)	CVB1008	370.50
	16ch HD Passive Transceiver (Video Balun) - 1 unit Unshielded twisted pair - 24AWG UTP Cat5e / Cat6 (RJ45 socket / screw terminal) Transmit distance: 200m (1080P) / 400m (720P); support PTZ function for HD-CVI Weight: 2.1kg; Rackmountable, 1U Size	CVB1016	665.00

PICTURE	ITEM DESCRIPTION	MODEL	PRICE
	1ch HD Passive Transmitter (Balun) - 1 PIECE (CAMERA END ONLY) Unshielded twisted pair - 24AWG UTP Cat5e / Cat6 (screw terminal) Transmit distance: 200m (1080P) / 400m (720P); support PTZ function for HD-CVI Built-in TVS for surge protection; Wave Filter & Anti-Static design	CVB1001T	17.10
	1ch HD Passive Transceiver (Balun); Video & Power - 1 PAIR per Set Unshielded twisted pair - 24AWG UTP Cat5e/Cat6 (RJ45 socket) Transmit distance for Video and 12VDC Power: <50m Built-in minor surge protection and interference rejection	CPS1001P	85.50
	1ch Long Range HD Passive Transceiver (Balun); Video & Power - 1 PAIR per Set Unshielded twisted pair - 24AWG UTP Cat5e/Cat6 (RJ45 socket) Transmit distance for Video and 12VDC Power Output: <250m Built-in minor surge protection and interference rejection; input power 24-36VDC	CPC1001P	123.50

	Active Video Balun - CVBS 960H SERIES 1ch Active Receiver Balun - RECEIVER ONLY (can be used with VB1001/VT2001) Unshielded twisted pair - 24AWG UTP Cat5e / Cat6 Transmit distance: <900m (Colour) if used with VB1001	VR2001	133.00
	4ch Active Video Receiver Balun (can be used with VB1001/VT2001) Unshielded twisted pair - 24AWG UTP Cat5e / Cat6 Transmit distance: <700m (Colour) or <1200m (if used with VT2001) Rackmountable; dip switch for distance adjustment	VR2004	418.00
	8ch Active Video Receiver Balun (can be used with VB1001/VT2001) Unshielded twisted pair - 24AWG UTP Cat5e / Cat6 Transmit distance: <900m (Colour) or <1500m (if used with VT2001) Rackmountable; dip switch for distance adjustment; 230V powered	VR2008	817.00

	Video and Power Transmission over UTP - 960H Long Range 1ch Passive Transceiver (Balun); Video & Power - TRANSMITTER ONLY For use on camera end; bundle with VPC1016 Transmit distance for Video and 12VDC Power: <250m (Colour) Built-in minor surge protection and interference rejection	VPS1001T	28.50
	4ch Passive Video Receiver & 12VDC Power Hub (Need to use with VPS1001T) Unshielded twisted pair - 24AWG UTP Cat5e/Cat6 Transmit distance for Video and 12VDC 500mA Power: <50m (Colour) Built-in minor surge protection and interference rejection	VPS1004	722.00
	8ch Passive Video Receiver & 28VDC Power Hub (Need to use with VPS1001T) Unshielded twisted pair - 24AWG UTP Cat5e/Cat6 Transmit distance for Video and 12VDC Power: <250m (Colour) Built-in minor surge protection and interference rejection	VPS1008	931.00
	Video and Power Transmission over UTP - CVBS 960H Long Range 1ch Passive Transceiver (Balun); Video & Power - TRANSMITTER ONLY For use on camera end; bundle with VPC1016 Transmit distance for Video and 12VDC Power: <250m (Colour) Built-in minor surge protection and interference rejection	VCP1001T	47.50
	16ch Passive Video Receiver & 12VDC Power Hub (Need to use with VPS1001T) Unshielded twisted pair - 24AWG UTP Cat5e/Cat6 Transmit distance for Video and 12VDC 500mA Power: <50m (Colour) Built-in minor surge protection and interference rejection	VPS1016	931.00

PICTURE	ITEM DESCRIPTION	MODEL	PRICE
	19" Equipment Rack INCLUDED 3-gang Trailing Socket, detachable side panels with lock 4U Wall Mount Rack (Perspex Front Door with Frame & Lock) 237mm(H)x600mm(W)x500mm(D); Weight 8.8kg 6U Wall Mount Rack (Perspex Front Door with Frame & Lock) 327mm(H)x600mm(W)x500mm(D); Weight 11.5kg	WM4U	285.00
	9U Wall Mount Rack (Perspex Front Door with Frame & Lock) 460mm(H)x600mm(W)x500mm(D); Weight 13kg 12U Wall Mount Rack (Perspex Front Door with Frame & Lock) 594mm(H)x600mm(W)x500mm(D); Weight 16kg 15U Wall Mount Rack (Perspex Front Door with Frame & Lock) 727mm(H)x600mm(W)x500mm(D); Weight 20kg *Perforated Front Door Optional; Top-up RM 50 **600mm Depth Customised Rack; Top-up RM 100	WM6U	313.50
	Standard 19" Floor Standing 800mm Depth Rack - Order time 3-4 working days Stock will send direct from factory after we receive full payment Free Delivery within Klang Valley only (Outstation please enquire delivery cost) Specifications: Vented Top Cover; Front Acrylic Door with Flush lock Rear perforated door with lock; 2 detachable side panels with lock 1 set Castor wheel; 1 set adjustable feet; 40 sets M6 caged nuts 5 x 13A Power Outlets / 10 x Power Outlets for 33U and above Package comes with 2 x Ball-bearing Ventilation fans and 2 x 430mm Equipment trays Height & Weight : 15U - 837mm - 29kg , 18U - 970mm - 33kg , 24U - 1237mm - 41kg 28U - 1415mm - 46kg , 33U - 1637mm - 52kg , 37U - 1815mm - 57kg , 42U - 2037mm - 64kg. All Racks are 600mm Width *Perforated Front Door Optional; Top-up RM 100 **1000mm Depth Customised Rack; Top-up RM 300	WM9U	437.00
		WM12U	608.00
		WM15U	798.00
		ST15U	1349.00
		ST18U	1558.00
		ST24U	1767.00
		ST28U	2280.00
		ST33U	2375.00
		ST37U	2565.00
		ST42U	2888.00
	Equipment Tray 450mm Width, 330mm Depth For use in Wall Mount Racks	RET001	76.00
	Equipment Tray 500mm Width, 430mm Depth For use in Floor Standing Racks	RET002	76.00
	Ventilation Fan 12cm x 12cm size AC 230V powered	RVF001	57.00
	1U Cable Management Panel Comes with cover	RCM001	47.50

WARRANTY PERIODS - Valid beginning 1 August 2013

BELCO CAMERAS & DVR	18 months
CROSSFIRE CAMERAS	18 months
CROSSFIRE DVR	12 months
DAHUA PRODUCTS	18 months
SEAGATE HDD	24 months
KOSS UPS	24 months
NEC PROJECTOR	36 months
ADAPTORS	1 month
TESTER SCREEN	1 month (effective 15 Jan 2013)
ALL OTHERS	12 months

1. PAYMENT TERMS :

1.1. CASH AND CARRY

1.2. CASH DEPOSIT / FUND TRANSFER TO Pro Tech Solution & Services : MAYBANK A/C **5012 7143 7648**

1.3. FOR CHEQUE PAYMENTS, FUNDS HAVE TO CLEAR BEFORE GOODS RELEASE

2. RETURN POLICY :

2.1. GOODS SOLD IS RETURNABLE WITHIN 7 DAYS AT A RESTOCKING FEE OF 20%. GOODS MUST BE RETURNED IN ITS ORIGINAL PACKAGING COMPLETE WITH ACCESSORIES AND IN MINT CONDITION. GOODS RETURNED AFTER 7 DAYS WILL NOT BE ACCEPTED.

3. WARRANTY AND REPAIR :

3.1. MINIMUM 3 WORKING DAYS FOR ITEM SENT IN TO REPAIR.

3.2. HARDWARE PURCHASES COME WITH 1 YEAR WARRANTY (CARRY-IN) EXCEPT FOR POWER ADAPTORS AND UNLESS OTHERWISE STATED.

3.3. ONE TO ONE REPLACEMENT ON FAULTY HARDWARE TO BE GIVEN WITHIN 1 WEEK FROM DATE OF PURCHASE. (SUBJECT TO INSPECTION BY OUR TECHNICIANS FOR DAMAGES)

3.4. PRO TECH RESERVES THE RIGHT TO REPLACE THE PRODUCT OR RELEVANT PART WITH THE SAME OR EQUIVALENT PRODUCT OR PART, RATHER THAN REPAIR IT. WHERE A REPLACEMENT IS PROVIDED, THE PRODUCT OR PART BECOMES PROPERTY OF PRO TECH. PRO TECH MAY REPLACE WITH REFURBISHED PARTS, REPLACEMENT OF THE PRODUCT OR PART DOES NOT EXTEND OR RESTART THE WARRANTY PERIOD.

3.5. WARRANTY COVERS MANUFACTURER DEFECTS ONLY. DOES NOT COVER DAMAGE DUE TO LIGHTNING AND POWER SURGE. THE WARRANTY WILL VOID IF THE FACTORY-APPLIED SERIAL NUMBER HAS BEEN ALTERED/ TORN / REMOVED FROM THE PRODUCT. WARRANTY WILL NOT APPLY IF DAMAGE, MALFUNCTION OR FAILURE RESULTING FROM ALTERATIONS, ACCIDENT, MISUSE, BURNT MARK, FIRE, LIQUID SPILLAGE, MIS-ADJUSTMENT OF CUSTOMER CONTROLS, USE ON AN INCORRECT VOLTAGE, POWER SURGES AND LIGHTNING/THUNDERSTORM ACTIVITIES.

3.6. FOR WARRANTY SERVICE, RETURN PRODUCTS WITH TRANSPORTATION PREPAID TO BELCO MARKETING. BUYER TO BEAR BOTH WAYS TRANSPORTATION CHARGES, IF ANY.

4. LOAN POLICY :

4.1. FOR LOAN ITEM WE REQUIRE FULL DOWNPAYMENT. LOAN PERIOD IS 7 WORKING DAYS. IF NOT RETURNED, WE WILL NOT REFUND THE DOWNPAYMENT AND ITEM IS CONSIDERED SOLD. ITEM MUST BE RETURNED IN PERFECT CONDITION AND PACKAGING AS AT THE TIME OF LOAN.