	_
⋖	
~	7
٠	
ш	ı,
₹	•
4	
4	1
	3
L	,
4	
Ŀ	,
C	•
	1
-	•
⋖	
-	ì
4	
⋖	ľ
	1
-	

Model Number		Dome			Вох					
		Varifocal	Fixed	Indoor	Fixed	Varifocal	Fix	red		
		CV-CFW101L(N)*	CV-CFW103L(N)*	CV-CFN1	03L(N)*	CV-CPW101L(N)* CV-CPW	103L(N)*		
	Image Sensor	1/2.9" 1.0 Mega Pixels CMOS								
Camera	Effective Pixels	1280 (H) x 720 (V)								
	Min Illumination	0.05Lux/F1.4, 0Lux/IR (Varifocal) 0.05Lux/F1.6, 0Lux/IR (Fixed)								
	Video Frame Rate	25fps (PAL) 30fps (NTSC)								
	Day & Night	Auto(ICR) / Color / B/W								
	Max IR Distance	30m	30m	20	20m 30m		20	lm		
	Digital Noise Reduction	2D								
	White Balance, AGC, BLC	Auto 2.7~12 mm 3.6 mm 2.7~12 mm 3.6 mm 3.6 mm 3.6 mm								
Lens	Focal Length	2.7~12 mm	3.6 mm	3.6 mm		2.7~12 mm	3.6	mm		
	Angular Field of View	H: 35°~93° V: 21°~50°	H: 88° V:46°	H: 88° V:46°		V:46° H: 35°~93° V: 21°~50°		V:46°		
General	Weatherproof	IP66	IP66	-		-		IP66	IP	66
Model Number		CJ-HDR104	CJ-HDR	CJ-HDR108 CJ-		-HDR216	6 CJ-HDR416			

Model Number		CJ-HDR104	CJ-HDR108	CJ-HDR216	CJ-HDR416			
Video / Audio Interface	Vid	eo Input	4 CH, BNC	8 CH, BNC	16 CH, BNC	16 CH, BNC		
	Turna	HDCVI	1080P/720P					
	Type	Analog	NTSC/PAL					
	Video Output		1 HDMI, 1 VGA			1 HDMI, 1 VGA, 1 BNC		
	Audio Input		1 CH, RCA			4CH, BNC		
	Audio Output		1 CH, RCA			1CH, BNC		
Display	Multis	creen Mode	1/4	1/4/8/9	1/4/8/9/16	1/4/8/9/16		
Video / Audio Format	Video/Audi	io Compression		H.264/G.711				
	Record Rate	Main Stream	1080P (1~12/15fps), 720P/960H/D1 (1~25/30fps)		1080P (1~12/15fps), 720P/960H/D1/HD1/ 2CIF/CIF (1~25/30fps)			
		Extra Stream	D1 (1~12/15fps), CIF/ QCIF (1~25/30fps)					
Alarm / Event	Alarm Input		-	-	-	16 CH		
	Relay Output		-	-	-	6 CH		
	Trigger Events		Recording, PTZ, Tour, Video push, Email, FTP, Snapshot, Buzzer, Screen tips, Alarm out*					
Playback & Backup	Sync Playback		1/4	1/4/9	1/4/9/16	1/4/9/16		
Network	Mobi	ile Device	iPhone, iPad, Android					
HDD	Unit		1 SATA Port (up to 6 TB)	1 SATA Port (up to 6 TB)	2 SATA Port (up to 12 TB)	4 SATA Port (up to 24 TB)		
External	USB	Interface	face 2 Port, USB2.0					

Optional Accessory (For CJ-HDR416)

Interface

CJ-ES400 eSATA Extension Support 4 SATA HDD, up to 24 TB

Authorised Reseller:

Panasonic System Solutions Asia Pacific

http://security.panasonic.com/ library/C-Series/index.html



Panasonic Business





Clarity Connectivity Convenience

PEACE OF MIND NOW COMES IN Cs



CLARITY

See the details in your video. Powered by improved technology, the C-Series gives you the clarity and sharpness of HD Analog. At a resolution of 720p, HD Analog produces a higher video quality as compared to conventional analog.

CONNECTIVITY

Keep a constant eye anywhere you are. EZ Remote utilizes the mobile EMS software for instant remote monitoring on your mobile devices. The mobile EMS software is available for free on the App Store and the Google Play Store.





CONVENIENCE

Be up and running in no time. The C-Series is engineered to provide a hassle-free installation and operation with its plug and play features. The EMS software installs under 3 minutes and the entire process can be completed in 7 clicks.



Panasonic C-series features a comprehensive range of indoor and outdoor surveillance options for buildings, retail stores, hotel establishments and other applications. The IR cameras provide HD clarity in both day and night operations with unnoticeable video noise, accurate colour rendition and exposure control. Video storage is made easy with our high-capacity recorders storing up to one month's worth of HD quality video footage*. Conventional analog users can upgrade to HD quality without tedious rewiring of cables. You no longer need to compromise on security and image quality.



*based on 3TB hard disk storage with videos from 4 cameras recording at 25/30 fps in HD resolution.