

ESSENTIAL SAE 10W-40

Multigrade engine oil for passenger car Otto and diesel engines.

Description

ESSENTIAL SAE 10W-40 is a multigrade engine oil of SAE grade 10W-40 produced using HC synthetic oils. Its high level of performance is achieved by combining the selected base oils and additives together.

Application

ESSENTIAL SAE 10W-40 is suitable for vehicles equipped with Otto and diesel engines, with or without turbocharging. It is used in vehicles without an extended maintenance interval.

Additionally this product is recommended when the following filling instructions are required

- ACEA A3/B4
- API SL/CF

Benefits

- Suitable for turbocharged engines
- Safer year-round operation
- Low oil consumption
- Miscible and compatible with conventional and synthetic engine oils. However, in order to exploit the full product benefits of ESSENTIAL SAE 10W-40, a complete oil change is recommended.

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,867
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	98,0
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	14,4
Viscosity index	ASTM D-7042	-	154
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	226
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-30
CCS	ASTM D-5293	cP @ °C	6200 @ -25
Total base number	DIN 51639-1	mgKOH/g	10,8

The characteristics shown are typical of current production. This data cannot be constructed as a legally binding warranty or guaranty of certain product properties or of the suitability of the product for a specific application. ROWE products are continually improved. Therefore ROWE reserves the right to change all the technical data in this product information at any time without notice. All sales and deliveries shall be subject to our current General Terms and Conditions of Sale and Terms (www.rowe.com.de).

Are you looking for the correct oil for your vehicle? Scan this code for the ROWE-oilfinder.



20259 | 25.07.2019