



Model: AZC2M4i1-MVDIR

**DESCRIPTION:**

AZC2M4i1-MVDIR is equipped with a 2.8-12mm motorized zoom lens and incorporated with a 6pcs Nanometer LED board. With this innovated design, it is able to be zoom in and zoom out with auto focus functions via CoC features (control over coaxial) through the DVR. It produces a superb night vision for indoor application. And Thanks to the 4 in 1 technology that enables this camera to be used in any coaxial cable with 1080p HD resolution.

FEATURES:

- 1/3" progressive scan CMOS image sensor for excellent image quality
- Supports image resolution up to 1920 x 1080P (30fps)
- Noise Reduction
- Max. Transmission distance: 400m via RG6U / 300m via RG59U coaxial
- Support CoC (control over coaxial)
- Support 4 type analogue format, HDTV I / HDCVI / AHD / CVBS, switchable by the OSD button on the cable
- Switch to CVBS format to use it on any standard Analog equipment
- 6pcs Nanometer LED
- Built-in 2.8-12mm motorized zoom lens

Ordering Information


Model No	AZC2M4i1-MVDIR
Dimension (LxHxW)	Ø140mm x 100mm
Weight	300g
Product Box Size (mm)	185 x 165 x 170 mm
Carton Size; Qty/CTN	510*390*365mm; 12pcs/CTN

Precaution

- Do not install camera in with temperature above 50°C or under -10°C.
- Do not install in a places with high humidity
- Do not face the camera to a strong light
- Do not drop the camera and avoid physical shock.
- Its highly important to use the correct and suitable power supply (DC12V) for the camera.
- Only Professional and qualified technician can install and test the camera

MODEL	AZC2M4i1-MVDIR
CAMERA	
Image Sensor	1/2.9" AR0230 CMOS + FH8536
Effective Pixels	1920(H) × 1080(V), 2MP
Resolutions	2MP (1920 × 1080)
Electronic Shutter Speed	PAL: 1/4s ~ 1/100,000 sec
Signal To Noise Ratio	More than 50dB
Minimum Illumination	0.1Lux/F2.0 (Color); 0.001Lux/F2.0 (IR ON)
IR LED Type	6pcs Nanometer
IR Distance	25M
AGC	Yes
Lens	2.8-12mm Motorized Zoom Lens (2MP)
Video Compression	25/30fps@1080P, 25/30fps@720P
Video Output	Default 1-channel BNC CVI output, switchable to AHD, TVI, CVBS
OSD Languages	English/ Chinese
Day / Night Mode	Color/BW/EXT/Auto
DWDR	Low / Medium / High
Digital Noise Reduction	2D
BLC	Off / Auto
HLC	/
Sense Up	/
Privacy	/
Motion Detection	/
Defog	/
White Balance	ATW / MWB
OPTIONAL	
Audio	-
GENERAL	
Power Source	DC12V ± 25% / 1000mA
Power Consumption	Max. 12W (12V DC)
Net Weight	300g
Dimension (L x W x H) mm	∅140 x 100 mm
IP Rating	IP66
Body Material / Vandalproof Rating	Metal / IK10
Operating Temperature	-10°C ~ +50°C / > 90% RH
Storage Temperature	-40°C ~ +60°C / > 95% RH

Specifications subject to change without notice. © 2017.All rights reserved.

STRUCTURE:**CONNECTOR:**