



Model: AZPINJ-H60W

DESCRIPTION

This single port gigabit 60W high power PoE injector supports LT PoE++ standard and can be backward compatible with IEEE 802.3af /IEEE802.3at PoE standard. The maximum PoE output power is 60W, the total power is 65W. There are 2x RJ45 ports. One is linked the upper switch or other upper network devices. And another network port is used as the port that integrated PoE power output and network data. It's more convenient for installation and use of high power network dome cameras or other high power IP devices. PoE injector can provide a simple and economical solution for high performance Ethernet PoE power supply and data communication. Easy to use and install, superior performance and cost-effective, which is an ideal choice for customer to improve the projects' quality. It's an efficient engineering solution to meet the requirement of the reliability system and simplified installation for remote places without power supply or unable to use Ethernet cable to supply power.

FEATURES:

- Supply power to 5 classes Ethernet network surveillance cameras
- 2x 10/100 Mbps RJ45 ports
- Support network port, lightning-proof power input port (the secondary lightning protection)
- Support LT PoE++ standard, and compatible with IEEE802.3af standard and IEEE802.3at standard
- Single PoE port output power is 60W, the voltage is 50-57V, and the total power is 65W
- No fans, natural cooling, small and exquisite, no noise design, suitable for desktop or wall

Ordering Information


Model No	AZPINJ-H60W
Dimension (LxWxH)	80*76*25mm
Gross Weight	120g
Product Box Size (mm)	250*205*45mm
Carton Size; Qty/CTN	490*440*270mm; 20pcs/ctn

Precaution

- Do not install POE injector in temperature above 50°C or under -10°C.
- Do not install in a places with high humidity
- Do not drop the POE injector and avoid physical shock.
- Its highly important to use the correct and suitable power supply (AC100-240V) for the POE injector.
- Only Professional&qualified technician can install&test the POE injector

MODEL	AZPINJ-H60W
10/100M 60W Single Port PoE Injector	
Connector Type	2x copper cable RJ45 ports
Network Protocol	IEEE 802.3i 10BASET; IEEE 802.3u 100BASET; IEEE 802.3x Flow Control; IEEE 802.1ab 1000BASET; IEEE 802.3af DTE Power via MDI; Support LT PoE++ standard, and downward compatible with IEEE 802.3af/ IEEE 802.3at
Network Medium	10BASE-T: 5 class UTP(≤100m); 100BASE-TX: Cat5 or more UTP(≤100m)
Performance Specifications	Working Speed:10/100Mbps
	Network Port Protection: meet the IEC61000-4-2(ESD)
	MTBF: 100,000 hours
PoE Features	The total power: 65W
	Single PoE Port Output Power: 60W
	Input Voltage: 50-57V
LEDs Indicator	PoE working status
Environment	Operating temperature: 0 to 55° C; Storage temperature: -20 to 75°C; Working Humidity: 10%~90%, non-condensing
Safety	CE Mark ,commercial, FCC Class, RoHS
Warranty	1 year warranty

Dimension



Application:

