



Model: AZMPTZ5M4i1-X550



DESCRIPTION

AZMPTZ5M4i1-X550 is equipped with a 5-50mm motorized zoom lens and incorporated with a 4pcs Array+2pcs Laser LED board. With this innovated design, it is able to be zoom in and zoom out with auto focus functions via CoC features (control over coaxial) through the DVR. It produces a superb night vision for indoor application. And Thanks to the 4 in 1 technology that enables this camera to be used in any coaxial cable with 1080p HD resolution.

FEATURES:

- High performance sensor, resolution up to 2592x1944
- Patent Design for the housing
- Keep original analog system
- Max. Transmission distance: 400m via RG6U / 300m via RG59U coaxial
- Support CoC (control over coaxial)
- Support 4 type analogue format, HDTV / HDCVI / AHD / CVBS, switchable by the OSD button on the cable
- Switch to CVBS format to use it on any standard Analog equipment
- Pan/Tilt/Zoom, A-B scan, tour available
- Built-in 5-50mm motorized zoom lens
- Support coaxial function with XM / Raysharp and so on

Ordering Information

Model No	AZMPTZ5M4i1-X550
Dimension (LxWxH)	306x106x184mm
Gross Weight	1500g
Product Box Size (mm)	390x190x140mm
Carton Size; Qty/CTN	680x410x620mm; 12pcs/ctn

Precaution

- Do not install camera in with temperature above 50°C or under -10°C.
- Do not install in a places with high humidity
- Do not face the camera to a strong light
- Do not drop the camera and avoid physical shock.
- Its highly important to use the correct and suitable power supply (DC12V) for the camera.
- Only Professional & qualified technician can install and test the camera

MODEL		AZMPTZ5M4i1-X550
5MP 4 IN 1 LONG RANGE PATENT PTZ		
Sensor	1/3" CMOS 5MP OV05A10	
Output pixel	2592x1944/30fps; 2592x1944/25fps	
Lens	10X f=5~50MM	
Minimum Illumination	0.01Lux/F2.0 (Color); 0Lux/F2.0 (IR ON)	
AGC	Auto/Manual	
S/N Ratio	>50dB	
Rotation	Pan:0°~200°, Tilt:~45°~50°	
Pan speed	~0°~30°	
Tilt speed	~0°~25°	
Auto Flip	Support	
Ration speed	Support	
IR range	100M	
IR control	PWM	
AB scan	Any point in Pan range: 0°~200°	
AB speed	1-9 grade selectable	
Preset	220	
Tour	3 groups (each group 16 preset, dwell time and speed selectable)	
BW	Auto	
Focus	Auto/Manual	
BLC	Adjust	
Video interface output	AHD/TVI/CVI/CVBS	
Communication mode	RS485 (+/-) / coaxial cable	
Power	DC12V(2A)	
Temperature	-40°C ~ +60°C	
Consumption	≤15W	

