



Model: AZLED32A-4K

FEATURES:

1. HD: 3840*2160, 4 times higher than normal monitor.
2. Turn on the screen to automatically detect the resolution of the input signal in the upper right corner of the screen.
3. Clear: delicate and realistic, conveying true colors, showing the true colors.
4. Bright: The quality is improved, only for better presentation.
5. Adopt industrial screen, high brightness, high contrast.
6. High-precision standard regulated power supply, specially designed for industrial equipment
7. It adopts full metal casing, strong structure, fireproof, moisture proof and shockproof, especially suitable for equipment that is susceptible to electromagnetic interference.
8. Adopt 10bit image chip processing technology, high pixel progressive scan, fine texture.
9. Support intelligent 3D noise reduction, eliminate afterimage function, dynamic brightness, contrast color optimization technology.
10. Apply the world's leading LED driver solution to accurately restore the front-end signal, with a strong sense of reality.
11. LED has small volume, low energy consumption, zero radiation, stable image, no impact on the eyes, natural health.
12. 5ms extremely fast response, avoiding the tailing phenomenon of images in high speed operation.
13. Using nanotechnology, the picture is more three-dimensional, transparent.
14. This machine also comes with a splicing function, no external splicer.

Ordering Information

Model No	AZLED32A-4K
Dimension (LxHxW)	741.3x436.4mm
Weight	6.8KG
Product Box Size (mm)	850x600x190mm
Carton Size; Qty/CTN	850*600*380; 2pcs/carton

Precaution

- Don't put it with temperature above 60°C or under -20°C.
- Avoid the water splash or pouring on the LED screen
- Do not put/store in a places with high humidity
- Do not drop the monitor and avoid physical shock.
- Only Professional&qualified technician can install the monitor

Model No	AZLED32A-4K
Screen size:	32"
Screen type:	LED
Screen ratio:	16:9
Brightness	500nit
Contrast ratio	10000:1
Response time	5ms
Visual area	699.3*396.4
Viewing angle	160°/ 170°
Display color	16.7M
Clearness	3840*2160
Control method	Panel infrared
Input port	HDMI*1, VGA*1, USB*1, DVI*1, RS232*2, CVBS*2
Output port	RS232* 1
Power supply mode	220V / 0. 7A
Power frequency	50Hz
Total power	50W
Case	professional fireproof iron case
Product outer dimensions	741.3*436.4 does not include foot height (foot height 25mm)
Installation method	base, wall mount (with 4 * Hexagonal column screw)
Working environment temperature	most suitable for 20°C
Working environment humidity	10%-90% RH
Storage temperature	- 20°C~ 60°C

Specifications subject to change without notice. © 2019.All rights reserved.

STRUCTURE:

