

RG6 A112 COAXIAL CABLE

APPLICATION


❖ High quality RG Type Coaxial cable,75 Ohm suitable for many applications, particularly broadcast and CATV installations.

PRODUCT FACTS

- ❖ INDOOR USE, Accepts 900m longer
- Suitable for shop-lot, home, factory

PRODUCT CODE

❖ RG6-ALL-A112-500M



TECHNICAL DATA

ITEM		UNIT	SPEC. VALUE
Inner Conductor	Material		Bare Copper
	Dia.(approx)	mm	1.00 ± 0.15
Insulation	Material		Foam Polyethylene
	Nom. Thickness	mm	1.56 ± 0.18
	Dia.(approx)	mm	4.80 ± 0.18
	Colour		Natural
Outer Conductor	Type		Braid
	Material		Aluminum LC
	Coverage	%	95 ± 3
	Dia.(approx)	mm	0.12 x 128
Jacket	Material		PVC
	Nom. Thickness	mm	0.80 ± 0.2
	Colour		Black
	Dia.(approx)	mm	7.00 ± 0.20
CHARACTERISTICS			
DC Conductor Resistance at 20 $^{\circ}\mathrm{C}$			$<26.1\Omega/100m$
Insulation Resistance at 20 $^{\circ}\mathrm{C}$			$> 200~\text{M}\Omega.\text{m}$
Nominal Velocity of Propagation			$66.6 \pm 3\%$
Capacitance			$67 \pm 5 \text{ pF/m}$
Characteristic Impedance at 20 °C,200MHz			$75 \pm 5\Omega$
PACKING			WEIGHT
Wooden drum - 370x370x265(mm)	500m/drum		22.kg