



APPLICATION REPORT

Application Reports are an excellent way to share knowledge throughout the Blagdon sales network. Reports will be available to all unless stated. If any part of this report should remain confidential and not published, please highlight or inform Joanne Shutt



PUMP MODEL

2BSABBTTs (316 Stainless Steel / PTFE)

INDUSTRY

Solvents

DESCRIPTION OF PROCESS/APPLICATION

This 2" Blagdon pump was trolley mounted and used to empty and fill road tankers with solvents.

This type of pump was chosen because the air operated double diaphragm (AODD) pump is considered to be safe in potentially dangerous environments.

It is easy to operate and to maintain with a low cost of ownership in comparison to other AODD pumps.

The pump is of a very robust design and this particular pump has been in service for 11 years.

Blagdon pumps are now standard across this plant (approximately 35 pumps)

PUMP STATISTICS

DUTY Solvents

FLOWRATE N/A

HEAD N/A

AIR PRESSURE Depended on solvents and whether it is a filling or emptying duty.

ANY OTHER INFORMATION

BLAGDON PUMP HOLDINGS LIMITED

Lambert Road, Armstrong, Washington, Tyne & Wear, NE37 1QP. U.K.

Tel: +44 (0) 191 417 7475

Fax: +44 (0) 191 417 5435

Email: sales@blagdonpump.com

Website: www.blagdonpump.com