

drum pumps stainless steel with features for the top position



DRUM PUMPS STAINLESS STEEL

	SD-SS-	A	S	DL-SS-	A	R	S	MP-DL-SS-	A	R	S	Mag-SS-	A	R
important for your application														
large capacity		X			X				X				X	
high pressure			X			X	X			X	X			X
viscosity up to 1.500 mPas (pd500)			X				X				X			
hydraulic tuning			X			X	X			X				
many different liquids				X				X						
mixing function								X				hermetically sealed		
simple disassembly (SD)	X													
easy to clean	X			X				X						
explosion proof	AtEx			AtEx				AtEx				no		
continuous work with induction motor			X				X				X			
tube length	container size	ord.-no.				ord.-no.				ord.-no.			ord.-no.	
700 mm	hobcock 30l	631-0001	631-0006		691-0001	696-0001	691-0006		691-0011	696-0011	691-0016		630-0004	635-0004
1000 mm	drum up to 220 l	631-0002	631-0007		691-0002	696-0002	691-0007		691-0012	696-0012	691-0017		630-0005	635-0005
1200 mm	IBC up to 1000 l	631-0003	631-0008		691-0003	696-0003	691-0008		691-0013	696-0013	691-0018		630-0006	635-0006
> 1200 mm	special container	on demand	on demand		on demand	on demand	on demand		on demand	on demand	on demand		on demand	on demand
electrical motors without explosion proof														
p310 optimised in price	preferred combination	X			X				X				X	X
p400 the ideal drive	improved hydr. performance	X	X		X	X	X		X	X	X		X	X
pd500 silent worker	smooth product treatment		X				X				X			
electrical motors with explosion proof														
EX700 for hazardous locations	safety by power	X	X		X	X	X		X	X	X			
pd500 Ex	smooth product treatment		X				X				X			
compressed air motor for all applications														
d600 for hazardous locations	the power drive	X	X		X	X	X		X	X	X			