

# Specifications

## Indoor Unit



## Outdoor Units



## Wired Remote Controller



Indoor Model	Wired	YCC5J10AAS-SLM	YCC5J15AAS-SLM	YCC5J20AAS-SLM	YCC5J25AAS-SLM	
Outdoor Model		YSM5J10AAS	YSM5J15AAS	YSM5J20AAS	YSM5J25CAS	
Cooling Capacity	Btu/hr	12,500 (2,678~14,388)	13,000 (3,072~15,358)	18,000 (5,460~18,429)	24,000 (5,802~24,231)	
Input Power	W	1,000 (280~1,800)	1,000 (280~1,800)	1,480 (540~2,100)	2,000 (620~2,600)	
Rated Current	A	4.9 (1.2~8)	4.9 (1.2~8)	6.6 (2.3~9.5)	9.1 (2.3~12)	
EER	Btu/hr/W	12.50	13.00	12.50	12.25	
Power Source	Ph/V/Hz	1Ph/220-240V/50Hz				
Refrigerant Type/ Control		R410A / OUTDOOR ELECTRONIC EXPANSION VALVE				
External Static Pressure	Pa	25	25	25	25	
Indoor Air Flow (H/L)	CFM	330/240	330/240	510/360	720/510	
Noise Level (H/L)	dB(A)	37/31	37/31	41/32	46/38	
Dimension (WxDxH)	Indoor	mm	610x483x220	610x483x220	1,090x484x220	1,090x500x220
	Outdoor	mm	780x245x540	780x245x540	810x288x688	860x308x730
Unit Weight	Indoor	kg	14	14	23	24.5
	Outdoor	kg	31.2	31.2	43	49
Refrigerant Piping	Liquid	mm/in	6.35 / 1/4	6.35 / 1/4	6.35 / 1/4	9.52 / 3/8
	Gas	mm/in	9.52 / 3/8	9.52 / 3/8	12.7 / 1/2	15.88 / 5/8

Indoor Model	Wired	YCC5J30AAS-SLM	YCC5J40AAS-SLM	YCC5J50AAS-SLM	
Outdoor Model		YSM5J30CAS	YSM5J40CAS	YSM5J50CAS	
Cooling Capacity	Btu/hr	29,000 (6,484~30,715)	45,000 (19,112~46,414)	48,000 (20,476~49,485)	
Input Power	W	2,720 (500~3,800)	4,100 (2,000~6,000)	4,400 (2,000~6,000)	
Rated Current	A	12 (2.2~18.5)	7 (2.9~10)	7 (2.9~10)	
EER	Btu/hr/W	10.66	10.98	10.91	
Power Source	Ph/V/Hz	1Ph/220-240V/50Hz	3Ph/380-415V/50Hz		
Refrigerant Type/ Control		R410A / OUTDOOR ELECTRONIC EXPANSION VALVE			
External Static Pressure	Pa	50	100	100	
Indoor Air Flow (H/L)	CFM	1,250/1,075	1,550/940	1,550/940	
Noise Level (H/L)	dB(A)	48/42	50/42	50/42	
Dimension (WxDxH)	Indoor	mm	1,135x742x270	1,197x830x360	1,197x830x360
	Outdoor	mm	948x340x840	1,008x410x830	948x340x1,250
Unit Weight	Indoor	kg	45.4	70	70
	Outdoor	kg	64	82	93
Refrigerant Piping	Liquid	mm/in	9.52 / 3/8	9.52 / 3/8	9.52 / 3/8
	Gas	mm/in	15.88 / 5/8	19.05 / 3/4	19.05 / 3/4

Note:

- All designs and specifications are subjected to change without prior notice for product improvement
- Nominal cooling capacity is based on the conditions below  
Power supply, 1Ph/230V/50Hz or 3Ph/380V/50Hz  
Cooling - Indoor: 27°C DB /19°C WB and Outdoor 35°C DB / 24°C WB
- Units are tested and comply with the latest ISO5151

Head Office:

YORK (MALAYSIA) SALES & SERVICE SDN BHD (168496-T)

Bangunan THK, Suite 2.1, 2<sup>nd</sup> Floor,  
No.2A, Jalan 243, Section 51A,  
46100 Petaling Jaya, Selangor Darul Ehsan, Malaysia  
Tel. 03-7628 4100 Fax: 03-7628 4101

Branches:

Penang Branch  
Tel. 04-397 0213 Fax: 04-397 2045

Johor Bahru Branch  
Tel. 07-354 9878 Fax: 07-354 9871

Kota Kinabalu Branch  
Tel. 088-448 350 Fax: 088-448 352

Kuching Branch  
Tel. 082-553 100 Fax: 082-553 200



(Applicable to 2.8 HP and below)

### Authorized Dealer

Customer Care Centre: 1800 - 88 - YORK (9675)

Website: [www.york.com/my](http://www.york.com/my)

YORK-MY-CCI-16-01