

**DANSOON CHEMICALS SDN. BHD. (288272-U)**

No. 142, Jalan Permata 1/5, Arab Malaysian Industrial Park,  
71800 Nilai, Negeri Sembilan Darul Khusus, Malaysia.

Tel: +606-799 8777 Fax: +606-799 2212

Email: donsonchemicals@gmail.com

Website: www.donson.com.my



## **TECHNICAL DATA SHEET**

### **DONSON CA BLACK SEAL ADHESIVE**

#### **PHYSICAL DATA**

Appearance	Black. Non-transparent Liquid
Solid Content	22 ± 2%
Viscosity (30°C)	6000 ± 500cps
Main Solvent	Hydrocarbon Solvent
Specify Gravity	0.89
Drying Time	Minimum 5 minutes depending on ambient conditions

#### **CHARACTERISTICS**

DONSON CA Black Seal Adhesive is a black solvent-based neoprene contact adhesive. It is specially formulated to join seams and butt joints of elastomeric pipe and sheet insulation.

#### **APPLICATION**

1. Ensure the both surface material to be bonded are dry, clean, free from dust, oil or grease.
2. Brush DONSON CA Black Seal Adhesive on surface materials.
3. Press the surfaces. Ensure the materials are in the right position before the adhesive surfaces make initial contact.
4. Close container after use. Allowed the materials to dry.

#### **CAUTIONS**

1. Wipe off excess and wash with soap and water after contact with skin.
2. After contact with eyes, flush immediately with plenty of water or saline eye wash solution and continue rinsing for ten minutes.
3. Highly flammable product. Keep away from sources of ignition. No smoking.
4. Advisable to work in well ventilated areas and avoid inhaling the solvent vapour.

#### **STORAGE**

DONSON CA Black Seal Adhesive is to be stored in a cool and place. Ensure the cans are tightly capped. The storage stability will be at least 6 months from the manufacturing date.

*All information is given in good faith but without warranty. We cannot accept liability for any damage, loss or patent infringement resulting from the use of this information.*