

GENERAL SERVICE PRESSURE GAUGE

Fig. P101

FEATURES & SPECIFICATION

- Economical, designed for general services
- Dual scale pressure units reading
- Bottom socket connection
- Suitable for medium which is non-corrosive to brass
- Applicable for Building Services, Air-Conditioning, Fire-Protection, Cold Water Plumbing, General Industries.

SPECIFICATIONS	
Dial Size	4" (100mm) / 6" (150mm)
Case	Steel, Black
Bezel	Steel
Socket	Brass
Connection	3/8" Bottom Entry
Connection Standard	BSPT
Lens	Glass
Pointer	Aluminium, Black
Scale Unit	Dual Scale in bar & psi
Bourdon Tube	Phosphor Bronze
Movement	Brass
Working Pressure	Maximum 75% of Full Scale Value
Process Temperature	-10°C 65°C
Accuracy	1/- 3-2-3% ANSI/ASME Grade B
Protection	IP 52



		B404	2.03.731	400	0.00	40	-	0.140
		P101	-	100	x	10	*	0/16
Type / Model	Steel Casing with Brass Socket	P101						
Dial	100mm (4")			100				
	150mm (6")			150				
Connection	10mm (¾")					10		
	15mm (¾")					15		
Pressure Range	-760mmHg0; -30inHg0							V/00
	-760mmHg4bar; -30inHg60psi							C/04
	07bar; 0100psi							0/07
	010bar; 0150psi							0/10
	016bar; 0230psi							0/16
	020bar; 0300psi							0/20
	030bar; 0430psi							0/30