

69900-220 MASTERCOOL 220-240 V / 50/60 HZ "MASTERCLEANSE" FLUSH MACHINE



"MASTERCLEANSE" FLUSH MACHINE



Mastercool introduces its new "MASTERCLEANSE" large volume flush machines designed to flush all HVAC/R and automotive systems. "MASTERCLEANSE" will be commonly used for the removal of all solids and residues caused by breakage of compressor or filters. Designed with durable roll-away wheels and handle, this machine can conveniently move as needed.

FEATURES:

- Stainless steel ball valve controls
- 1/4" SAE connection
- Additional external container connection
- External nitrogen bottle connection
- Pump equipped with mechanical seal and PTFE gasket
- Mechanical filter present at suction side

SPECIFICATIONS:

- Pump Flow Rate:
4 g/min (16 l/min)
- Pump Motor: 300 watts
- Pump Horsepower:
110V/60 Hz - 0.4 HP,
220-240V/50/60 Hz - 0.28 HP
- Full Load Amperage: 110V/60 Hz - 2.4 amps, 220-240V/50/60 Hz - 1.7 amps
- Flush Container: 2.6 gal (10 l)
- Hoses: 9 ft (3 m) flexible, clear coiled
- Dimensions: 15" (l) x 16" (w) x 24" (h) /with handle extended 36" (h)
(381 mm (l) x 406 mm (w) x 609 mm (h) /with handle extended 914 mm (h))
- Weight: 42 lbs (19 kg)



A/C FLUSH SOLVENT



91049-32

91049-128

- Effectively removes debris and sludge from A/C components
- Solvent-based
- Evaporates quickly
- Leaves no residue
- O-Ring safe
- Non-Flammable
- Non-Corrosive
- Flush any A/C system

91049-32 32 oz. Flush Solvent

91049-32-6 6 pack - 32 oz. Flush Solvent

91049-128 1 Gallon Flush Solvent

91049-128-4 4 pack - 1 Gallon Flush Solvent