

575C1 Vane and Hotwire Velocity Meter

APPLICATIONS

- Air flow measurements in heating, ventilation and air conditioning systems
- Air duct analysis
- Fume hoods
- Flue Registers
- Exhaust grills
- Hotwire velocity meter enables user to read below 80fpm applications (low flow)



Turn over for technical information and accessory part numbers.

The Value Leader™

Features

- (Vane) Air flow 0.4 to 25 m/s (Also reads km/s, ft/min, knots/h, miles/h)
- (Hotwire) Air flow 0.2 to 20 m/s (Also reads km/s, ft/min, knots/h, miles/h
- Temperature -5° to 175° F (-20° to 80°C)
- Data record function for maximum and minimum temperature and air velocity reading
- Download to a computer using the RS-232 port and optional A500 cable. (The 555 uses Microsoft® Hyper Terminal to download and display air velocity and temperature on your PC.)
- 39" cable length with Lemo connector
- Data Hold
- Auto Power Off
- Protective boot and soft carrying case included



SPECIFICATION ACCESSORIE

Digital

Multimeters •

Clamp Meters • Hand-held

Oscilloscopes •

Refrigerant &

Combustible Gas

Leak Detectors • **Temperature**

Testers • BNC

Coax Cable •

Connectors •

Test Leads •

Accessories

Test Products International, Inc.

Headquarters: 9615 SW Allen Blvd. Beaverton, OR 97005 USA

503-502-9197 Fax: 503-520-1225 email:

info@tpi-thevalueleader.com

Test Products International, Ltd. 342 Bronte St. South

Unit 9 Milton, Ontario L9T 5B7

Canada 905-693-8558 Fax: 905-693-0888 email:

info@tpicanada.com

Test Products International UK Ltd.

Longley House, East Park Crawley, West Sussex RH10 6AP England Tel: +44 (0)1293 561212

Fax: +44 (0)1293813465

contactus@tpieurope.com

575 Vane and Hotwire Velocity Meter

SPECIFICATIONS

Display	Dual digits LCD with function annunciation
Measurement	m/s, km/s, ft/min, knots, mile/h, °C, °F
Measurement Range and Accuracy:	
Air Flow (Vane)	$0.4 \sim 25$ m/s ($\pm 2\%$ of reading ± 3 digits)
(Hotwire) '	$0.2 \sim 20 \text{ m/s } (\pm 5\% \text{ of reading } \pm 3 \text{ digits})$
Temperature	-5°F ~ 175°F (\pm 1% of reading \pm 1.0°F \pm 3 digit
	-20°C ~ 80°C (±1% of reading ±0.5°C ±3 digit
Operating Temperature	0 ~ 50°C (32°F ~ 122°F)
Operating Humidity	Less than 80% R/H
Powering	1.5V AAA x 6EA
Optional Accessories	A500 RS-232 cable
	A901 soft shoulder strap carrying case

Distributed By:



To learn about the entire line of TPI products visit:

www.tpi-thevalueleader.com L 575C1-0105 Copyright @ 2005 Test Products International, Inc.