

elite of technology

BT-1 BT-2 MT-3

BT-1



BT-2



MT-3

Functions:

Dual channel temperature measuring, big LCD display with dual channel temperature, switch between °C/°F, Max./Min. temperature value memory, Max/Min. temperature value recovery function, widely applied to cold storage, office etc.

Specification

Specification: 111×101×21.5(mm)

Technical parameters

- ◆ Power supply: DC1.5V one 7# Alkaline battery (optional)
- ◆ Measuring range:
Indoor temperature -30°C ~ +50°C (-22°F ~ +122°F)
Outdoor temperature -50°C ~ +70°C (-58°F ~ +158°F)
- ◆ Resolution: 0.1
- ◆ Accuracy: ±1°C

Functions:

Dual channel temperature measuring, one channel humidity measuring, big LCD display, switch between °C/°F, Max./Min. temperature value memory, Max/Min. temperature value recovery function, with clock, widely applied to cold storage, office etc.

Specification

Specification: 111×101×21.5(mm)

Technical parameters

- ◆ Power supply: DC1.5V one 7# Alkaline battery (optional)
- ◆ Measuring range:
Indoor temperature -30°C ~ +50°C
Outdoor temperature -50°C ~ +70°C
Relative humidity: 20% ~ 99% RH
- ◆ Resolution: Temperature: 0.1°C Humidity: 1
- ◆ Accuracy: Temperature: ±1°C Humidity: ±5%RH(25°C)

Functions:

Big LCD display with temperature, humidity, clock and calendar, Max./Min. temperature and humidity memory, body comfort degree display, switch between °C/°F, widely used in home and office.

Specification

- ◆ Mounting size: 104×44.5×16.5 (mm)
- ◆ Screen size: 35.5×24.5 (mm)

Technical parameters

- ◆ Power: DC1.5V LR44
- ◆ Indoor temperature measuring range: -30°C ~ +50°C
(-22°F ~ 122°F)
- ◆ Outdoor temperature measuring range: -50°C ~ +70°C
(-58°F ~ 158°F)
- ◆ Indoor humidity measuring range: 20% ~ 99% RH (25)
- ◆ Resolution: Temperature: 0.1 Humidity: 1
- ◆ Accuracy: Temperature: ±1°C Humidity: ±5%RH (25°C)