

ST-1A ST-2 ST-3 DS-1



ST-1A



ST-2



ST-3



DS-1

Functions:

LCD display, one way temperature measuring, small and fashionable appearance, various colors optional. Suitable for home, office and refrigeration repair.

Specification

Specification: 55.5×42.5×16(mm)

Technical parameters

- ◆Power supply: DC1.5V button battery LR44
- ◆Measuring range: -50℃~+70℃
- ◆Resolution: 0.1
- ◆Accuracy: ±1℃

Functions:

In/out door temperature measuring, clock function display, ultra slim shell design.

Specification

- ◆Specification: 57×38.5×13 (mm)
- ◆Product size: 47 (W) ×21.5 (H)

Technical parameters

- ◆1.Power supply: DC1.5V button battery LR44
- ◆2.Measuring range: -50℃~+70℃
- ◆3.Resolution: 0.1 (>-20℃), 1℃ (≤-20℃)
- ◆4.Accuracy: ±1℃

Functions:

Small and fashionable appearance, switch between ℃ and ℉, various colors optional. Specially applied to the aquarium.

Specification

Specification: 58×37×12.5(mm)

Technical parameters

- ◆1.Power supply: DC1.5V button battery LR44
- ◆2.Measuring range: -50℃~+70℃
- ◆3.Resolution: 0.1 (>-20℃), 1℃ (≤-20℃)
- ◆4.Accuracy: ±1℃

Functions:

Two probes measuring two-way temperature, switch between ℃ and ℉, clock function, attractive appearance

Specification

Specification: 118×30×28.5(mm)

Technical parameters

- ◆Power supply: DC1.5V7# alkaline battery
- ◆Measuring range: -50℃~+70℃
- ◆Resolution: 0.1 (>-20℃), 1℃ (≤-20℃)
- ◆Accuracy: ±1℃