

**Carrier**

A United Technologies Company

## **Health and Safety Information**

<b>Product Code:</b> <i>PP33-2</i>	<b>Warning Statement:</b>
<b>Application:</b> <i>Refrigerant compressor lubrication</i>	<i>NO SIGNIFICANT HAZARD</i>

**Description:** *Clear amber liquids containing highly refined mineral oil.*

### **Safe Handling Advice**

#### **Storage**

*No special precautions.*

#### **Handling**

*Avoid skin and eye contact.*

*To avoid the possibility of skin disorders, repeated or prolonged contact with lubricants and industrial oil must be avoided and it is essential that all who come into contact with such products, maintain high standard of personal hygiene. Concentrations of oil mists, fumes and vapours in the working atmosphere must be kept as low as is reasonably practicable.*

### **First Aid Procedures**

**EYES** *Irrigate immediately with copious quantities of water for several minutes.*

**SKIN** *Wash thoroughly with soap and water as soon as possible..  
Infrequent or short term skin contact requires no immediate action.*

**INGESTION** *Send the patient to hospital or obtain medical attention immediately.*

**ASPIRATION** *If aspiration occurs or is suspected, send the patient to hospital or obtain medical attention immediately.*

**INHALATION** *Remove from exposure.*

**Carrier**

A United Technologies Company

## **Health and Safety Information**

<b>Product Code:</b> <i>PP33-2</i>	<b>Warning Statement:</b>
<b>Application:</b> <i>Refrigerant compressor lubrication</i>	<i>NO SIGNIFICANT HAZARD</i>

### **Fire Protection Information**

Flash Point ( test method ) *Above 140°C*

Suitable Extinguishing Media *CO2, Dry powder, Foam or Water fog - Do not used water jet*

---

### **Protection of Environment**

Behaviour in water *Immiscible, floats.  
Not readily biodegradable*

Spillage *Prevent entry into drains, sewers and water coursea.  
Soak up with inert absorbent or contain and remove by best available  
means*

Waste disposal *Dispose of through an authorised contractor to a licence site.  
May be incinerated.  
Used product may be sent for reclamation.*

Typical Data	Density @ 15°C	0.884
	Vicosity @ St 10°C	35.3
	Vicosity @ St 100°C	4.70
	Flesh Point ( PMMC ) °C	165
	Floc Point °C	-39
	Pour Point °C	-36

**THIS DATA DOES NOT CONSTITUTE A CONTRACT IN TERM OF PROPERTIES**