



71270-00001.C



t -10 ... +120 °C

ps 1600 kPa

	DN	Rp	mm			80 °C		100 °C		120 °C		100 °C		120 °C											
			L	H	M	L1	X	Y	X	Y	X	Y	X	Y	X	Y									
	R2015..S1	15	1/2"	67	44	36	13	150	75	185	75	195	75	230	80	230	80	190	80	200	90	220	90	220	90
	R2020..S2	20	3/4"	78	46	46	14					200	75	235	80	235	80			205	90	225	90	225	90
	R2025..S2	25	1"	87	46	45	16					200	75	235	80	235	80			205	90	225	90	225	90
	R2032..S3	32	1 1/4"	105	50.5	55.5	19							240	80	240	80					230	90	230	90
	R2040..S3	40	1 1/2"	111	50.5	56	19						240	80	240	80					230	90	230	90	
	R3040-25-S4	40	1 1/2"	122	62	66.5	19							250	80	250	80					240	90	240	90
	R2050..S4	50	2"	125	56	68	22							245	80	245	80					235	90	235	90
	R3050-40-S4	50	2"	142	68	79	22							262	80	262	80					252	90	252	90

		A → AB 100%	A → AB 0%
		B → AB 0%	B → AB 100%

K_v $\Delta p_{vmax} < 350 \text{ kPa}$ 	 A → AB 100% B → AB 0%	 A → AB 100% B → AB 0%
	 A → AB 100% B → AB 0%	 A → AB 0% B → AB 100%
K_v $\Delta p_{vmax} < 1000 \text{ kPa}$ 	 A → AB 100% B → AB 0%	 A → AB 0% B → AB 100%
	 A → AB 100% B → AB 0%	 A → AB 0% B → AB 100%

