

# HK INSTRUMENTS Ltd

Kohäste 7  
FIN-40950 MUURAME  
FINLAND  
Tel: +358 14 337 2000  
Fax: +358 14 337 2020  
Email: info@hkstruments.fi

www.hkstruments.fi  
Bank: Leona 800019-01847365  
Vat Reg: FI 08730729  
Reg no: 404.989

## DIFFERENTIAL PRESSURE GAUGE



### Model summary

| Model   | Pressure range (Pa) |
|---------|---------------------|
| DPG60   | 0-60 Pa             |
| DPG100  | 0-100 Pa            |
| DPG120  | 0-120 Pa            |
| DPG200  | 0-200 Pa            |
| DPG250  | 0-250 Pa            |
| DPG300  | 0-300 Pa            |
| DPG400  | 0-400 Pa            |
| DPG500  | 0-500 Pa            |
| DPG600  | 0-600 Pa            |
| DPG800  | 0-800 Pa            |
| DPG1k   | 0-1 kPa             |
| DPG1,5k | 0-1,5 kPa           |
| DPG2k   | 0-2 kPa             |
| DPG3k   | 0-3 kPa             |
| DPG5k   | 0-5 kPa             |

### Accessories

Standard accessories\*:

- 2 fixing screws
- 2 plastic duct connectors
- 2 m tube  $\varnothing$  4 / 7 mm
- surface mounting plate

Optional accessories\*\*:

- metallic duct connectors
- flush mounting kit

\*included in the sales package

\*\* available separately

## Technical data

|                           |                                                                                                                 |                            |
|---------------------------|-----------------------------------------------------------------------------------------------------------------|----------------------------|
| <b>Materials</b>          | Housing                                                                                                         | ABS                        |
|                           | Cover                                                                                                           | PC                         |
|                           | Membrane                                                                                                        | silicone                   |
|                           | Machinery                                                                                                       | Aluminium and steel spring |
| <b>Accuracy</b>           | <math>\pm 2\% \text{ F.S (20}^\circ\text{C)}</math>, (DPG60 <math>\pm 4\%</math> ; DPG100 <math>\pm 3\%</math>) |                            |
| <b>Dial hole size</b>     | $\varnothing 110 \text{ mm}$                                                                                    |                            |
| <b>Weight</b>             | 234 grams                                                                                                       |                            |
| <b>Ambient conditions</b> | Operation                                                                                                       | -5... +60°C                |
|                           | Storage                                                                                                         | -40...+85°C                |

---

**Mounting position** Vertical

---

## Dimensions

