



EVAC Commercial Recovery Unit



Blazing Recovery Rates to Service Chillers & Other Large Cooling Systems

- Recovers R22 at 325-lb/min liquid & 6-lb/min vapor!
- Rugged open drive compressor provides years of reliable service, even on refrigerants heavily contaminated with oil, air, moisture, & acids. Equipped with in-line oil separator.
- Services R12, R22, R134a, R502, R410a & other high-pressure refrigerants.

Easy Operations

- Purging lines and switching from liquid to vapor recovery modes simply involves turning three 3way hand valves and rerouting one hose.

Specifications

Push/Pull Rates (R22)	325-lbs/min
Vapor Rates (R22)	6.0-lbs/min
Dimensions (l x w x h in inches)	32" x 29" x 45" Shipping (48" x 40" x 51") 406 lbs (471 lbs dual voltage)
Float Connection	3-pin BH
Connections	3/4" flare
Low Pressure Switch	15" Hg
Certifications standards	Certified by ETL to UL-1963
	Rated in accordance with ARI Standard 740-1998

Included with purchase

One 48-cubic inch drier core	50-ft power cord for controls
12-ft tank float cable	50-ft power cord for recovery unit
(2) 3/4"-5/8" & 5/8-1/2" fittings	Two 3/4" x 10ft & One 3/4" x 20ft recovery hoses w/ ball valves

Order number	Power options	Controls / Cooling option	Weight (lbs)
CRH-A-230-3-E	220-240V, 50/60Hz, 3Ph, 3Hp, 15A	Electromechanical Controls, Air Cooled	260
CRH-A-240-1-E	220-240V, 50/60Hz, 1Ph, 3Hp, 20A	Electromechanical Controls, Air Cooled	260
CRH-A-460-3-E	360-575V, 50/60Hz, 3Ph, 3Hp, 15A	Electromechanical Controls, Air Cooled	260
CRH-A-D24-1-E	240/460V 50/60Hz, 1PH, 5Hp, 30	Electromechanical Controls, Air Cooled	325
CRH-W-230-3-E	220-240V, 50/60Hz, 3Ph, 3Hp, 15A	Electromechanical Controls, Air/Water Cooled	265
CRH-W-240-1-E	220-240V, 50/60Hz, 1Ph, 3Hp, 20A	Electromechanical Controls, Air/Water Cooled	265
CRH-W-460-3-E	360-480V, 50/60Hz, 3Ph, 3Hp, 15A	Electromechanical Controls, Air/Water Cooled	265
CRH-W-D24-1-E	240/460V, 50/60Hz, 1Ph, 5Hp, 30	Electromechanical Controls, Air/Water Cooled	330

RefTec International, Inc.
10530 Portal Crossing West
Suite 104
Bradenton, FL 34211
U.S.A.

Toll Free Tel: 800-214-4883
Factory Tel: 941-750-6622
Sales Fax: 941-750-0222
Main Fax: 941-750-6633
www.reftec.com