





Convenient, mobile, versatile: the HD 5/12 C cold water high-pressure cleaner for vertical and horizontal operation. With accessory storage, brass cylinder head and automatic pressure relief.



### 1 Mobility

- The integrated carrying handle on the front of the device enables easy loading and convenient transport.
- Push handle can be retracted at the push of a button.



### 2 Flexibility

- Vertical and horizontal operation possible.
- The wheels are not on in horizontal operation. In this way, the device offers maximum stability.



### 3 Accessory storage

- Screw connections (M 18 x 1.5) for storing surface cleaner directly on the device.
- Practical nozzle compartments for triple nozzle and rotary nozzle.



### 4 Quality

- The automatic pressure relief protects the components and extends the service life.
- High-quality brass cylinder head.



## HD 5/12 C

- Automatic pressure relief
- For vertical and horizontal operation
- Easy Press spray gun and rotatable stainless steel spray lance

### Technical data

<b>Order No.</b>	1.520-120.0	
<b>EAN code</b>	4039784607446	
<b>Current type</b>	<b>Ph / V / Hz</b>	1 / 230 / 50
<b>Flow rate</b>	<b>l/h</b>	500
<b>Working pressure</b>	<b>bar / MPa</b>	120 / 12
<b>Max. pressure</b>	<b>bar / MPa</b>	175 / 17.5
<b>Max. feed temperature</b>	<b>°C</b>	60
<b>Connection output</b>	<b>kW</b>	2.5
<b>Weight</b>	<b>kg</b>	23.7
<b>Dimensions (L x W x H)</b>	<b>mm</b>	380 × 360 × 930

### Equipment

<b>Spray gun</b>	Easy-press trigger gun	
<b>Spray gun with soft grip</b>	■	
<b>High-pressure hose</b>	<b>m</b>	10 / ID 6, 250 bar
<b>Spray lance</b>	<b>mm</b>	850
<b>Triple nozzle (0°/25°/40°)</b>	manual	
<b>Anti-twist system</b>	■	
<b>Pressure cut-off</b>	■	

■ Included in delivery.

# Accessories for HD 5/12 C 1.520-120.0



	Order No.	ID	Max. working pressure	Length	Price	Description	
<b>Standard with unions on both sides</b>							
High-pressure hose, 15 m, ID 8, 315 bar, including rotary coupling	1	6.390-010.0	ID 8	315 bar	15 m		▲
High-pressure hose, 20 m, ID 8, 315 bar, extension piece	2	6.390-031.0	ID 8	315 bar	20 m		▲
High-pressure hose, 10 m, ID 8, 315 bar, extension piece	3	6.391-342.0	NW 8	315 bar	10 m		▲
High-pressure hose, 30 m, ID 8, including rotary coupling	4	6.390-293.0	ID 8	315 bar	30 m		▲
<b>Food industry version with unions on both sides</b>							
High-pressure hose, 10 m, DN 8, suitable for the food industry, extension piece	5	6.389-479.0	ID 8	250 bar	10 m	10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 x 1.5 with anti-kink sleeve.	▲
High-pressure hose, 20 m, ID 8, suitable for food industry, extension piece	6	6.389-581.0	ID 8	250 bar	20 m	20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 x 1.5, with kink protection. NW 8/155°C/250 bar.	▲
<b>Longlife 400 with unions on both sides</b>							
High pressure hose ID 6, 10 m, including rotary coupling	7	6.391-883.0	ID 6	400 bar	10 m	With rotary coupling, 2 x M 22 x 1,5	▲
Longlife 400 high-pressure hose, 10 m, DN 8, extension piece	8	6.391-354.0	ID 8	400 bar	10 m		▲
High-pressure hose Longlife 400, 15 m, ID 8, including rotary coupling	9	6.389-709.0	ID 8	400 bar	15 m	With rotary coupling, 2 x M 22 x 1,5	▲
High-pressure hose Longlife 400, 30 m, ID 8, including rotary coupling	10	6.390-294.0	ID 8	400 bar	30 m		▲
High-pressure hose 1.5 m, ID 8, including connectors	11	6.390-178.0	ID 8	400 bar	1.5 m	1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5).	□
<b>Longlife food design with screw connections at both ends</b>							
High pressure hose food ID 8, 10 m	12	6.391-864.0	ID 8	400 bar	10 m	Longlife HP hose for use in the food industry. Außendecke##	▲
High-pressure hose food industry 400 bar, 20 m, ID 8, including rotary coupling	13	6.391-887.0	ID 8	400 bar	20 m	animal-grease-resistant, non-colour-bleeding material. With rotary coupling, 2 x M 22 x 1,5	▲
<b>Standard</b>							
High-pressure hose, 10 m, ID 6, AVS trigger gun connector	14	6.391-238.0	ID 6	250 bar	10 m	10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.	■
High-pressure hose, 15 m, ID 6, AVS gun connection	15	6.391-394.0	ID 6	250 bar	15 m		□
High-pressure hose, 10 m, ID 8, AVS trigger gun connector	16	6.390-025.0	ID 8	315 bar	10 m	10 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	□
High-pressure hose, 15 m, ID 8, AVS trigger gun connector	17	6.390-185.0	ID 8	315 bar	15 m	15 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	□
High-pressure hose, 20 m, ID 8, AVS trigger gun connector	18	6.390-171.0	ID 8	315 bar	20 m	20 m high-pressure hose (M 22 x 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	□
High-pressure hose, 10 m, ID 6, 300 bar, AVS trigger gun connection	19	6.391-875.0	ID 6	300 bar	10 m	With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 x 1.5 with anti-kink protection. NW 6/155°C/300 bar	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



	Order No.	ID	Max. working pressure	Length	Price	Description	
<b>Longlife 400</b>							
High-pressure hose Longlife 400, 20 m, DN 8, AVS trigger gun connector	20	6.390-208.0	ID 8	400 bar	20 m	20 m high-pressure hose Longlife 400 (DN 8) with patented (rotating) AVS trigger gun connector and manual coupling. Two layer high-strength steel wire reinforced.	<input type="checkbox"/>
Longlife 400 high-pressure hose, 10 m, DN 6, M 22 x 1.5	21	6.391-882.0	ID 6	400 bar	10 m	With patented AVS connection in the trigger gun (pivot-mounted).	<input type="checkbox"/>
Longlife 400 high-pressure hose, 10 m, DN 8,	22	6.391-351.0	NW 8	400 bar	10 m		<input type="checkbox"/>
<b>Food industry version</b>							
High-pressure hose, 10 m, DN 8, AVS trigger gun connection, food, grey	23	6.390-704.0	ID 8	250 bar	10 m	Food industry version, AVS connection in the trigger gun. grey NW 8/155 °C/250 bar	<input type="checkbox"/>
High-pressure hose, 20 m, ID 8, AVS trigger gun connector, suitable for food industry, grey	24	6.390-705.0	ID 8	250 bar	20 m	20 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. NW 8/155°C/250 bar.	<input type="checkbox"/>
<b>Longlife food design</b>							
High-pressure hose Longlife 400, 10 m, ID 8, AVS trigger gun connection	25	6.391-885.0	ID 8	400 bar	10 m	Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)	<input type="checkbox"/>
High-pressure hose Longlife 400, 20 m, ID 8, AVS trigger gun connection	26	6.391-886.0	ID 8	400 bar	20 m		<input type="checkbox"/>
<b>Special hoses</b>							
High-pressure hose 1.5 m, ID 8, including connectors, outlet bend	27	6.388-886.0	ID 8	400 bar	1.5 m		<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



		Order No.	Flow rate					Price	Description	
<b>Easy Press high-pressure trigger gun with holding force reduction (Kärcher patent)</b>										
Easy Press HP trigger gun with soft grip	1	4.775-463.0							Easy press high-pressure trigger gun with softgrip. For high-pressure hoses DN 6 and DN 8 with 11 mm swivel diameter.	■
<b>Trigger guns</b>										
High-end HP trigger gun	2	4.775-823.0								□
<b>Inaktiv</b>										
High-end HP trigger gun	3	4.775-804.0								□
<b>Quick connect</b>										
Quick coupling	4	6.401-458.0							For quick change of different spray lances and accessories. Optimum adaption to Kärcher accessories, especially for connection between trigger gun and spray lance. With M22 x 1,5 female.	□
Male coupling	5	6.401-459.0							Hardened stainless steel nipple for quick coupling 6.401-458. With M22 x 1,5 male.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.


# Accessories for HD 5/12 C 1.520-120.0



		Order No.	Max. working pressure	Nozzle size		Price	Description	
<b>Triple nozzles</b>								
Triple nozzle 035	1	4.767-212.0	300 bar	35			Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application. Connector M 18x1.5.	■
<b>Dirt Blaster, small</b>								
Dirt blaster	2	4.767-022.0	180 bar	35			Small rotary nozzle for dirt blaster. The rotating point jet achieves 10 times the cleaning performance. Outstanding working time thanks to ceramic nozzle and bearing ring. Max. 180 bar/18 MPa, 60°C.	□
<b>Dirt blaster, large</b>								
Dirt blaster – without changeover function	3	4.763-931.0	300 bar	35			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.


# Accessories for HD 5/12 C 1.520-120.0



		Order No.	Max. working pressure	Length		Price	Description	
<b>Rotating spray lances</b>								
850 mm spray pipe, rotatable	1	4.760-663.0	300 bar	850 mm			850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	■
600 mm spray pipe, rotatable	2	4.760-664.0	300 bar	600 mm			600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
1050 mm spray pipe, rotatable	3	4.760-660.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
1550 mm spray pipe, rotatable	4	4.760-661.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
2050 mm spray pipe, rotatable	5	4.760-662.0	300 bar	2050 mm			2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	□
<b>Spray lances</b>								
Vibrasoft lance	6	6.415-951.0	250 bar	950 mm			The spring-loaded 360° loop handle significantly reduces the vibrations on the spray lance, reducing the physical burden on the user, e.g. when working with the dirt blaster.	□
<b>Angular spray lance</b>								
Spray lance for toilets and rain gutters	7	4.760-073.0					Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	□
<b>Undercarriage spray lance</b>								
Underbody lance	8	4.760-245.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	□
<b>Spray lance</b>								
250 mm lance, non-rotatable	9	4.760-667.0		250 mm			250 mm stainless steel lance. With manual coupling. Non-rotatable.	□
<b>Double lance</b>								
Double lance 960 mm	10	6.394-665.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	□
<b>Gutter cleaner</b>								
Gutter cleaning lance	11	2.642-305.0					The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	□

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



		Order No.	Flow rate	Nozzle size	Diameter	Price	Description	
<b>Hard surface cleaner FRV 30</b>								
FRV 30 surface cleaner	1	2.642-999.0						<input type="checkbox"/>
<b>Hard surface cleaner FR 30</b>								
Hard surface cleaner FR 30	2	2.642-997.0			300 mm			<input type="checkbox"/>
<b>FR 30 Me surface cleaner</b>								
Hard surface cleaner FR 30 Me	3	2.640-355.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	<input type="checkbox"/>
<b>Device-specific nozzle kits for FR</b>								
Nozzle kit for surface cleaners	4	2.640-401.0	500-650 l/h				Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (500 to 650 l/h).	<input type="checkbox"/>
<b>FRV 30 Me surface cleaner</b>								
FRV 30 Me	5	2.642-911.0						<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.



# Accessories for HD 5/12 C 1.520-120.0



2

		Order No.	Nozzle size				Price	Description	
<b>Power nozzle spray angle 15°</b>									
Power nozzle spray angle 15°	1	2.885-225.0	36						<input type="checkbox"/>
<b>Power nozzle spray angle 25°</b>									
Power nozzle spray angle 25°	2	2.885-255.0	35						<input type="checkbox"/>
25° power nozzle for applying cleaning agent	3	2.884-521.0	250						<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



		Order No.					Price	Description	
<b>Coupling</b>									
Connector	1	4.403-002.0						Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 x 1.5 m.	<input type="checkbox"/>
<b>Connector</b>									
Nozzle screws / screw socket	2	4.402-022.0						Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 x 1.5 and 1x M 18 x 1.5.	<input type="checkbox"/>
<b>Adapters</b>									
Adapter M 22 – Swivel	3	4.424-004.0						M22 x 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



		Order No.	Nozzle size				Price	Description	
<b>Wet blasting attachment (without nozzle)</b>									
Wet blasting attachment with flow control (without nozzles)	1	4.762-010.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	<input type="checkbox"/>
Wet blasting attachment without flow control (nozzles not included)	2	4.762-022.0						Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	<input type="checkbox"/>
<b>Nozzle kits for wet jet unit</b>									
Nozzle kit for wet jet unit 035	3	2.638-526.0	35					Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.762-010/-022.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



		Order No.	Max. working pressure	Nozzle size	Diameter	Price	Description	
<b>Pipe cleaning hose, ID 6</b>								
Pipe cleaning hose, NW 6, 20 m	1	6.390-028.0	120 bar				The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	<input type="checkbox"/>
Pipe cleaning hose, ID 6, 30 m	2	6.390-029.0	120 bar				30 m flexible high-pressure hose (DN 6) for cleaning pipes (threaded connection for R 1/8 nozzle).	<input type="checkbox"/>
Pipe cleaning hose, NW 6, 20 m, 250 bar	3	6.390-030.0	250 bar				The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	<input type="checkbox"/>
<b>Pipe cleaning nozzle</b>								
Pipe cleaning nozzle	4	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	<input type="checkbox"/>
	5	5.763-017.0		50	30 mm		Pipe cleaning nozzle with inner thread. Different spray directions. The hose moves freely through the pipe. (R 1/8" connection, 3 x 30° backwards, diameter 30 mm.)	<input type="checkbox"/>
Rotating pipe cleaning nozzle	6	6.415-428.0		50	16 mm		Pipe cleaning nozzle with four rotating jets and inner thread. Different spray directions. The hose moves freely through the pipe. With R 1/8" connection.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.


# Accessories for HD 5/12 C 1.520-120.0



		Order No.	Flow rate				Price	Description	
<b>Inno Foam Kit</b>									
Inno Foam Set with detergent injector	1	2.640-151.0						High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	<input type="checkbox"/>
<b>Easy Foam Set</b>									
Easy Foam Set with RM injector	2	2.640-691.0						HP foam system for use with HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	<input type="checkbox"/>
<b>Nozzle kits for Inno/Easy Foam Set</b>									
Nozzle kit 055 for Inno / Easy Set 500-600 l/h	3	2.640-870.0	500-600 l/h					Optimal adaptation to different machine outputs for economic use.	<input type="checkbox"/>
<b>Foam nozzle mounting kit</b>									
Foam nozzle attachment kit	4	2.637-926.0						Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.


# Accessories for HD 5/12 C 1.520-120.0



		Order No.	Length				Price	Description	
<b>Automatic, self-winding hose reels</b>									
Automatic hose reel, coated	1	2.639-919.0	20 m					Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	<input type="checkbox"/>
Powder-coated swivel holder	2	2.639-931.0						Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	<input type="checkbox"/>
Automatic hose reel, stainless steel, includes swivel holder	3	6.391-421.0	20 m					Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	<input type="checkbox"/>
Automatic hose reel, powder-coated steel / plastic	4	6.392-975.0	20 m					Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	<input type="checkbox"/>
Automatic stainless steel / synthetic material hose drum	5	6.392-965.0	20 m					Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



		Order No.	Length	Diameter		Price	Description	
<b>Starting current limiter</b>								
Starting current limiter	1	2.637-495.0					Reduces starting current in single-phase supply and protects line fuse.	<input type="checkbox"/>
<b>Geka coupling</b>								
Geka connector with hose barb, R 3/4"	2	6.388-455.0					with hose liner	<input type="checkbox"/>
Geka connector with inner thread, R 3/4"	3	6.388-473.0					with female thread	<input type="checkbox"/>
<b>Suction filter</b>								
Suction filter with check valve	4	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	<input type="checkbox"/>
<b>Water fine filter</b>								
Water fine filter, with adapter	5	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	<input type="checkbox"/>
<b>Water supply hose</b>								
Water supply hose	6	4.440-038.0	7.5 m				NW 13 R1" / R 3/4", up to 30 °C	<input type="checkbox"/>
<b>Backflow check valve</b>								
Backflow preventer	7	2.641-374.0					To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.

# Accessories for HD 5/12 C 1.520-120.0



		Order No.	Flow rate				Price	Description	
<b>Rotating washing brush</b>									
Rotating wash brush for < 800 l/h devices, natural hair bristles	1	4.762-560.0	500-800 l/h						<input type="checkbox"/>
Rotating wash brush for < 800 l/h devices, nylon bristles	2	4.762-561.0	500-800 l/h					The rotating wash brush gently removes fine dust and grime from all surfaces. Heat-resistant up to 80°C. (M 18 x 1.5, replaceable brush insert).	<input type="checkbox"/>
<b>Push-on washing brush</b>									
Push-on wash brush	3	4.762-497.0						The wash brush is fitted directly onto the devices' new dual and triple nozzles using clamping.	<input type="checkbox"/>

■ Included in delivery. □ Available accessories. ▲ Extension hose.