

**TM-1012**  
**TM-1014**  
**TM-1015**  
**TM-1016**



**TM-12E**  
**TM-13E**  
**TM-16E**



TM-12E	TM13E	TM-16E	TM-1012	TM-1014	TM-1015	TM-1016	Function
●	●			●	●	●	3 <sup>3</sup> / <sub>4</sub> Digits 4000 Counts
		●	●				3 <sup>1</sup> / <sub>2</sub> Digits 2000 Counts
●	●		●	●	●	●	AC Current 400A
		●					AC Current 600A
	●				●		DC Current 400A
						●	AC Current 0.1uA - 4000uA
						●	DC Current 0.1uA - 4000uA
●	●	●	●	●	●	●	AC Voltage
●	●	●	●	●	●	●	DC Voltage
●	●	●	●	●	●	●	Resistance
●				●			Frequency
●	●	●	●	●	●	●	Continuity Buzzer
						●	Temperature
						●	Capacitance
			●	●			Diode Test
●	●	●	●	●	●	●	Range Hold
				●	●	●	Back Lighting
●	●	●	●	●	●	●	Data Hold
				●	●		Storage of MAX/MIN value
●	●			●	●		Bargraph
●	●	●	●	●	●	●	Auto Range
●	●	●	●	●	●	●	Auto Power Off
30	30	30	30	30	30	30	Jaws Opening Diameter (mm)

**PATENTS PENDING**