

DG1004



4CH HD CCTV DVR

FEATURES

Cloud Service - EaZy Networking*

- ❖ EaZy Networking, the cloud service provided by AVTECH, available to connect this device to Internet automatically in three steps with our free mobile app, EagleEyes.
- ❖ The “Buddy” feature to share the device access permission to other people.

Push Status -

Active Event Notification with EagleEyes App

- ❖ Sends instant notifications for system events, such as video loss or HDD data removal.



HD Video Recording

- ❖ HD real-time recording brings users clear images while video recording and playback
- ❖ 1920*1080 Full HD video output service, giving the best image quality on LCD / LED monitors

Remote Surveillance

- ❖ Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system
- ❖ Video Viewer for 16 devices central management
- ❖ Applicable also to Apple’s media player, QuickTime.

Independent Channel Control

- ❖ Definable “Resolution” / “Quality” / “IPS” by channels at your preferences to increase the recording efficiency, and avoid any important scenes to be missed.

Remote Independent Operation

- ❖ Channel switching is independent from the local site, allowing users to have private image monitoring remotely.

Backup Function

- ❖ Supports USB flash drive and network backup.

* EaZy Networking is a service to connect your device to Internet automatically by plug and play, but it’s not free. AVTECH will initially provide 2GB data allowance (approx. 2185 minutes) for free. When 2GB is up, the network transmission is down to 1 FPS. To restore the fluency of live view, users need to subscribe a data plan from AVTECH, or configure the network settings by themselves.

➤ SPECIFICATIONS

▼ Video

Video System	NTSC / PAL (auto detection)	
Video Compression Format	H.264	
Video Input	4 channels (Composite video signal 1 Vp-p 75Ω BNC)	
Video Output	BNC	YES
	VGA	YES
	HDMI	YES

▼ Record & Backup

Maximum Recording Rate	1080P	1920 x 1080 pixels with 60 IPS
	720P	1080 x 720 pixels with 120 IPS
	QHD	960x540 pixels with 120 IPS
	Frame	704x480 pixels with 120 IPS <NTSC> / 704x576 pixels with 100 IPS <PAL>
	Field	704x240 pixels with 120 IPS <NTSC> / 704x288 pixels with 100 IPS <PAL>
	CIF	352x240 pixels with 120 IPS <NTSC> / 352x288 pixels with 100 IPS <PAL>
Recording Mode	Manual / Timer / Motion / Remote	
Pre-alarm Recording	YES	
Playback Channel	4CH	
Quick Search	Time / Motion search mode	
Backup Device	USB 2.0 flash drive / Network	

▼ Audio

Audio Input	1 audio input
Audio Output	1 audio output (Mono)

▼ General

Hard Disk Storage**	Up to 2 SATA HDDs
SATA Interface	YES
Image Quality Setting	SUPER BEST / BEST / HIGH / NORMAL
USB Mouse Control	YES
Motion Detection Area	16 × 12 grids per channel
Motion Detection Sensitivity	3 adjustable parameters for accurate detection
Event Notification	Push Status / FTP / E-Mail
Picture Zoom	2X digital zoom
PTZ Control	YES
IR Remote Control	YES (IR receiver built-in)
Key Lock (Password Protection)	YES
User Level	4 user levels for different access privilege
Video Loss Detection	YES
Camera Title	Supports up to 12 letters
Video Adjustable	Hue / Saturation / Contrast / Brightness
Date Display Format	YY/MM/DD, DD/MM/YY & MM/DD/YY
Daylight Saving	YES
Power Source (±10%)	DC12V / 3A
Operating Temperature	10°C ~ 40°C (50°F ~ 104°F)
Dimensions (mm)***	375(W) × 61(H) × 281(D)

▼ Network

Ethernet	10/100 Base-T. Supports remote control and live view via Ethernet
Network Protocol	TCP/IP, PPPOE, DHCP and DDNS

➤ SPECIFICATIONS

▼ Remote Surveillance from PC		
Compatible Operating System	Windows & MAC	
Compatible Program	Web Browser:	Internet Explorer, Mozilla Firefox, Google Chrome & Safari
	Video Viewer:	16CH central management software for Windows and MAC operating systems
	QuickTime:	For both Windows and MAC operating systems
Max. online users	10	
Web Transmitting Compression Format	H.264	
Network Live Audio	YES	
Remote Independent Operation	YES	
Remote Event Download & Playback	YES	
▼ Mobile Surveillance		
App	EagleEyes	
Compatible Devices	iOS & Android devices	
Push Status	YES	
▼ Others		
EaZy Networking	YES	
DCCS Support	YES	
AVTECH Free DDNS service	YES	
Multiplex Operation	Live display / record / playback / backup / network operations	
System Recovery	System auto recovery after power failure	
Optional Peripherals	HDMI Matrix (HDM02)	

* The specifications are subject to change without notice.

** 1 HDD capacity up to 4TB

*** Dimensional tolerance: ±5mm

➤ REAR PANEL

