

HDVR-2104

Compatible with:



HDVR-2116



HYBRID MULTIFUNCTIONAL STANDALONE DVR

STAREX IPVS

Features

- **H.264 High Profile** Video Compression
- Multi Functions Mode (**DVR/HVR/NVR**)
- **4/8/16CH D1 Real Time** (DVR Mode)
- **Graphic User Interface (GUI)**
- Support Super **Cloud Service** (www.dvrcenter.net)
- Support **Multi-Browser** (IE, Chrome, Firefox, Safari)
- Support **All Kind Of Mobile** Monitor
- Support **Multi Kinds Of PTZ Protocol** (RS485)
- **04/08CH** Support **1 Sata HDD Slot** (Max 2TB Each)
16CH 2 Sata HDD Slot (Max 2TB Each)
- **Multiplex Operation**
(Preview, Recording, Playback, Backup, Network Live, Mobile View)

Ideal for Home Surveillance, Child Care, Small Office, Retail Store ...etc.





Model	HDVR2104		HDVR2116
System			
Main Processor	HIS Chipset Hi3520A		HIS Chipset Hi3521
Display			
Display Screen	1/4	1/4/8/9	1/4/8/9/16
Video			
Monitor Quality	Monitor: D1 ; VGA:1080P ; HDMI:1080P		
Playback Quality	Max Support 1080P Under HVR and NVR Mode; Max Support D1 Under DVR Mode		
Encode Capability	4CH D1 Real Time (DVR Mode)	8CH D1 Real Time (DVR Mode)	16CH D1 Real Time (DVR Mode)
Decode Capability	4CH D1 Real Time (DVR Mode)	8CH HD1/1CH D1 Real Time (DVR Mode)	16CH D1 Real Time (DVR Mode)
Multi-mode Video input	DVR mode:4*D1 HVR mode:2 *D1+(1*1080P+1*720P) NVR mode:8*960H/4*720P/2*1080P /1*720P+7*D1/ /1*1080P+1*720P+2*D1	DVR mode:8*D1 HVR mode:2 *D1+(1*1080P+1*720P) NVR mode:8*960H/4*720P/2*1080P /1*720P+7*D1/ /1*1080P+1*720P+2*D1	DVR mode:16*D1 HVR mode:8*D1+16*D1/8*D1+8*720P 8*D1+(2*1080P+2*720P)/ 4*D1+20*D1/4*D1+(2*1080P+10*D1)/4*D1+(1*1080P+7*720P)/ 4*D1+(1*1080P+1*720P+10* 960H) NVR mode:24*D1/20*960H/4*1080P/1*1080P+8*720P/2*1080P+4*720P+4*960H
Motion Detection	Each Channel Can Set 192 (16*12) Detection Area; Can Set Multi-Level Of Flexibility (For Local Analog Channel Only)		
Record And Playback			
Record Mode	Manual , Alarm , Motion Detection , Timing		
Local Playback	1-9CH Playback Synchronously;Under The Mode Of DVR, Max Support 4CH D1 Real Time Playback Synchronously	1-9CH Playback Synchronously;Max Support 4CH Playback Synchronously Under 8CH D1 Recording (DVR Mode)	Max Support 16CH D1 Real Time Playback Synchronously (DVR Mode)
Storage And Back Up			
Video Storage	Local HDD , Network		
Space Occupation	Video: CIF 4~5G/Day*Channel, D1 16~20G/Day*Channel; Audio: 691.2M/Day*Channel		
Interface			
Video Input	4CH BNC	8CH BNC	16CH BNC
Video Output	1CH BNC, 1CH VGA, 1CH HDMI		
Audio Input	4CH RCA	8CH RCA	16CH RCA
Audio Output	1CH RCA		
PTZ Control	1 RS485; Support Multi Kinds Of PTZ Protocol		
HDD Port	1 SATA (Each Max Support 2048G)		2 SATA (Each Max Support 2048G)
Audio Input	4CH RCA	8CH RCA	16CH RCA

All Rights Reserved. Note: All Specification May Change Without Prior Notice.