



INTRODUCTION

The GV-NVR (Network Video Recorder) records video and audio data over TCP/IP networks. With up to 32 channels of pure IP surveillance, the GV-NVR offers the same functions as GV-Series Surveillance System. From monitoring features to video analytics as well as integration with LPR, POS/ATM and Access Control systems, it stands as one of the most comprehensive IP surveillance software in the security market.

Combined with GeoVision IP camera, the GV-NVR takes advantage of a better image quality thanks to the progressive scan technology and allows advanced video features such as Picture-In-Picture and Picture-And-Picture. Compatibility with a wide range of third party IP cameras makes the GV-NVR the ultimate solution for pure IP surveillance environments.

VERSION 8.3 KEY FEATURES

Built upon comprehensive and easy-to-integrate hardware and supporting technologies, the GV-Surveillance and Video Management Platform is the core system platform that provides performance-optimized video monitoring and various advanced video analytics/control features to support many of enterprise's management functions. It is a scalable, extensible platform that can be customized and seamlessly integrated with other security system applications, such as:

1. POS/ ATM/ EAS for loss prevention
2. Access Control for building automation
3. License Plate Recognition system for law enforcement, entrance control and revenue collection
4. Megapixel IP devices for critical area and mobile object monitoring
5. Central Monitoring stations for high profile security areas in commercial, industrial and residential markets

In addition the remote management WebCam and versatile storage system framework offer high scalability and extensibility for future integration with other functions or systems at remote sites.



- Support for 32 channels in GV-System and CMS applications
- Support for two GV Video Capture Cards in GV-System
- New features to Main System:
 - Digital Matrix
 - Automatic adjustment for DST (Daylight Saving Time)
 - Lost signal alarm
 - Talkback support when IP cameras provide 2-way audio
 - Windows-based direct POS integration (POS Text Sender)
 - Crowd Detection
 - Advanced Scene Change Detection
 - Advanced Unattended Object Detection
 - Advanced Missing Object Detection
 - Single Camera Tracking
 - Iris button added to the PTZ control panel
 - Colorful Mode to enhance video color
- Support for new 3rd-party IP cameras:
 - Arecont AV-3130, AV-8360
209FD, 209FD-R, 209MFD, 209MFD-R, 211M, 211W, 215, 216MFD, 216MFD-V, 241Q, 241S, P3301, Q7401
 - Axis
 - Cannon VB-C50i, VB-C300
 - IQEye IQEye 703, IQEye 705, IQEye 752, IQEye 753, IQEye 755
 - JVC VN-V25U, VN-V26U, VN-V686U
 - Mobotix M12D Web, M12D IT-DNIGHT, M12D Sec
 - Panasonic WV-NS202A, WV-NW484, WV-NW964
 - Pelco IP110, IP3701
SNC-CM120, SNC-CS20, SNC-DM110, SNC-DM160,
 - SONY SNC-DS10, SNC-DS60, SNC-RX530N, SNC-RX530P, SNC-RX570N, SNC-RX570P

- New features to ViewLog
 - Support for Daylight Saving Time (DST)
 - Playback of GPS tracks from GV-Compact DVR and GV-Video Server
 - Colorful Mode to enhance video color for playback

- New features to Webcam
 - Multicast
 - Audio Broadcast
 - POS/Wiegand Live View option added to Single View
 - New GUI for Remote Playback (RPB)
 - Support for BlackBerry phones

- New features to SMS Server
 - Unlimited log retention time
 - Support for new alert events, including Crowd Detection, Advanced Scene Change Detection, Advanced Unattended Detection and Advanced Missing Object Detection
 - Support for Wavecom GPRS Modem

- New features to Center V2:
 - Remote control of I/O devices from GV IP devices
 - Unlimited log retention time
 - Colorful Mode to enhance video color
 - Assigning a DVR client to another Center V2

- New features to VSM:
 - Remote control of I/O devices from GV IP devices
 - Unlimited log retention time
 - Automatic insertion of ID and Name to SMS messages
 - Support for new alert events, including Crowd Detection, Advanced Scene Change Detection, Advanced Unattended Detection and Advanced Missing Object Detection

- New features to Dispatch Server:
 - Unlimited log retention time
 - Colorful Mode to enhance video color

- New features to Control Center:
 - Support for new event settings in VMD, including Crowd Detection, Advanced Scene Change Detection, Advanced Unattended Detection and Advanced Missing Object Detection
 - Colorful Mode to enhance video color
 - GV-Keyboard support in Matrix
 - QView in Matrix for channel display on another monitor
 - Remote control of I/O devices from GV IP devices
 - Pop-up live view upon input triggers in I/O Central Panel

- New applications:
 - GV-GIS (Geographic Information System)
 - Multicast
 - Audio Broadcast

- New devices:
 - GV-I/O Box 4 Ports
 - GV-I/O Box 8 Ports
 - GV-I/O Box 16 Ports

FULL FEATURE LIST

▶ Monitoring

- Support for 32 channels in GV-System and CMS applications
- Digital Matrix, support maximum 8 monitors display
- Higher Screen Resolutions (1920 x 1200, 1680 x 1050, 1600 x 1200, 1280 x 800, 1440 x 900 and 1920 x 1080)
- Noise Tolerance for Motion Detection
- Report Generator
- Support for Cardholder data from GV-Video Server
- Touch Screen Support
- Full screen view
- Dual display operation for live monitoring and ViewLog playback on two monitors
- Screen pop-ups on motion or alarm activation
- Object counting
- Unattended and missing object detection
- Alarm on objects passing between predefined regions
- Digital watermark
- Video lost detection
- On screen video loss message
- Video de-interlace filter
- E-map
- Windows lockup
- Image size indicator
- Synchronized video and audio
- Backlight compensation
- Video scaling filter
- AVI repair utility
- System log
- Support 1,000 accounts for logins and passwords
- Multi level passwords protection
- Use Microsoft Remote Desktop to control another GV-System
- Twin DVR
- Embedded I/O devices control
- Embedded PTZ control panel
- Support dynamic IP address
- Password Expiration Management
- System Idle Protection
- Spot Monitor Controller
- POS Live Viewer
- Photo-ID Integration (GV-WT)
- Authentication Server
- Colorful Mode to enhance video color

▶ Intelligent Recording & Playback

- Recording trigger by round-the-clock, motion detection, alarm and schedule
- Adjustable recording quality and frame rate for each camera
- Pre-motion and post-motion recording
- Supports Windows XP / Server 2003 burning software
- Instant Playback
- Time Merge From Different Clips
- Splitting Files for Backup onto Multiple Discs
- Extracting Frames from a Video Clip During Playback
- Support for Daylight Saving Time (DST)
- Playback of GPS tracks from GV-Compact DVR and GV-Video Server

▶ Audio

- 32 channels of live audio streaming and recording

▶ Video Analytics

- Advanced Motion Detection
- Face Detection
- Advanced Scene Change Detection
- Advanced Unattended Object Detection
- Advanced Missing Object Detection
- Privacy Mask
- Enhanced Object Counting
- Intrusion Alarm
- People Counting
- Panorama View
- Video Stabilization
- Defog Function
- Crowd Detection

▶ Smart Search & Ease Playback

- Timeline Search
- Face Detection for Object Index
- Object search
- Index search
- Object Index
- Thumbnail browse for ease of search for specific frames within video footage
- Export a video footage within a specified time range
- Synchronized audio and video for both live and playback modes
- Continues playback of set frames A to B
- EXE format export, playable with any third-party players
- AVI format export in multiple screens mode
- DVD format export for Hybrid Card format files
- Option for recycling the input-triggered events (Never recycle function)
- Backup, save AVI and BMP functions accessible in LAN ViewLog
- Automatic refresh of the video event list in LAN ViewLog

▶ **Notification**

- E-mail notification with attached video images on motion and alarm activation
- E-mail or telephone notification on video lost or I/O error
- Directs PTZ dome to a preset location on motion and alarm activation
- SMS alerts available in Main System, Center V2 and Vital Sign Monitor
- Alarms on objects that pass between predefined regions

▶ **WebCam - Remote Surveillance**

- POS Live View via IE Browser
- 3G Mobile Phone Support (3GPP)
- SSL Encrypt Connection Support
- UPnP™ Support
- Control Panel on Single View to Provide Instant Information and Operation
- Support PIP, PAP, Defogging Live Videos, and Video Stabilizer in Single View
- Restricting Power User and User to Access WebCam Server at Specified Time Length
- Event List Query
- Download Center
- Drag-and-Drop Support for Camera, PTZ and I/O Icons on the 2 Windows of MPEG4 Encoder Viewer
- Remote E-Map
- Pop-up Live Images upon Input Trigger in Remote E-Map
- Multicast
- Audio Broadcast

▶ **Advanced I/O Control**

- Visual Automation
- Virtual I/O Control
- One-Click I/O Status Control
- Multiple I/O Types Selection
- Latch Trigger Feature

▶ **Mobile Phone Application**

- Support 4, 9, and 16 screen divisions
- PTZ control via directional buttons
- Channel switch via middle button
- Support for Nokia S60 3rd Edition

▶ **Profile Management**

- Selectable GUI Skin
- Custom Start-Up Splash Screen, Non-Active Video & Video Lost Screen
- Customizing System Features
- Easy Configuration Backup & Restore
- Custom DVR Setting's Template

▶ **Remote Monitoring Software**

- Remote View
- IP Multicast
- WebCam
- Remote Playback System
- G-View for WinCE PDA
- I-Mode
- BlackBerry phones

▶ **IT Technology**

- RSA Network Security
- Authentication Server: central control of password settings in local GV-DVRs

▶ **Central Monitoring Station (CMS)**

- Center V2
- Vital Sign Monitor
- Dispatch Server
- Control Center
- GV-GIS (Geographic Information System)

▶ **Integration Solution**

- Point-Of-Sale
- EAS Integration
- Access Control
- Megapixel Integration
- Licence Plate Recognition
- Central Monitoring Station

VERSION 8.3 GV-NVR Specifications

NVR			
Model	GV-NVR (GV)	GV-NVR	
Video Input	4, 8, 12, 16, 20, 24, 28, 32	1, 2, 4, 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32	
Audio Input	4, 8, 12, 16, 20, 24, 28, 32	1, 2, 4, 6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32	
Video Compression	MJPEG, MPEG4, H.264		
Video Resolution	From CIF to 5 Mega pixel		
IP Camera	GeoVision GV-IPCAM 1.3M, GV-Video Server, GV-Compact DVR	Arecont Vision	AV1300, AV2100, AV3100, AV3130, AV5100, AV5105, AV8360
		AXIS	AXIS 206, AXIS 207, AXIS 207W, AXIS 207MW, AXIS 209FD, AXIS 209FDR, AXIS 209MFD, AXIS 209MFD-R, AXIS 210, AXIS 210A, AXIS 211, AXIS 211A, AXIS 211M, AXIS 211W, *AXIS 212 PTZ, *AXIS 213 PTZ, *AXIS 214 PTZ, AXIS 215, AXIS 216FD, AXIS 216FD-V, AXIS 216MFD, AXIS 216MFD-V, AXIS 221, AXIS 223M, AXIS 225FD, AXIS 231D, AXIS 232D, AXIS 233D, AXIS 241Q, AXIS 241S, AXIS P3301, AXIS Q7401
		Canon	*VB-C300, *VB-C50i
		GeoVision	GV-IPCAM 1.3M, GV-Video Server, GV-Compact DVR
		IQinvision	IQeye301, IQeye302, *IQeye510, *IQeye511, IQeye701, IQeye702, IQeye703, IQeye705, IQeye752, IQeye753, IQeye755
		JVC	VN-C20U, VN-C205U, VN-C215U, *VN-C625U, *VN-C655U, NV-25, VN-V26, *VN-V686
		Mobotix	M12D_Sec_DNIGHT, M12D_Web, M12D_IT_DNIGHT, M12D_Sec, M12D_Sec_R8
		Panasonic	BB-HCM110, *BB-HCM311, *BB-HCM331, BB-HCM371, *BB-HCM381, *BB-HCM403, *BB-HCE481A, BL-C10, BL-C30, *WV-NS202A, WV-NW484, *WV-NW964
		Pelco	IP110, IP3701
		SONY	SNC-CS10, SNC-CS11, SNC-CS20, SNC-CS50N, SNC-CS50P, SNC-CM120, SNC-DF40N, SNC-DF40P, SNC-DF50N, SNC-DF50P, SNC-DF70N, SNC-DF70P, SNC-DF80N, SNC-DF80P, SNC-DM110, SNC-DM160, SNC-DS10, SNC-DS60, SNC-P1, *SNC-P5, *SNC-RX530N, *SNC-RX530P, *SNC-RX550N, *SNC-RX550P, *SNC-RX570N, *SNC-RX570P, *SNC-RZ25N, *SNC-RZ25P, *SNC-RZ50N, *SNC-RZ50P
		* IP Cam with PTZ control	
Networking	TCP / IP, LAN, WAN, Internet, Modem Dial-up, Modem-to-Modem, ISDN		
Backup Device	HDD, NAS, CD-R / R-W, DVD+R / +RW, DVD+R (DL), ZIP, JAZ, Blu-ray		
Operating System	Windows 2000, Windows XP, Windows Server 2003, Windows Vista		
Language	Czech / Danish / English / French / German / Hebrew / Hungarian / Italian / Japanese / Polish / Portuguese / Russian / Serbian / Simplified Chinese / Spanish / Traditional Chinese		

Telefeeling Communication Sdn Bhd
Tel : 03-9131 3030
Fax : 03-9133 2030
info@telefeeling.com
www.telefeeling.com