

www.telefeeling.com

Honeywell *Black*

A One Stop Solution
For small to medium scale application

VISTA Series
Video Surveillance Security System
2011 Product Catalogue

ANALOGUE CAMERAS



VCC-600P



High Resolution WDR Camera

- 1/3" Sony Super HAD CCD
- Resolution: 540TV lines Min illumination of 0.001 (DSS on)
- WDR, Day Night, BMB™, DNR
- Privacy zone masking, Motion detection, digital zoom

CABC-560P **NEW**



High Resolution Mini Box Camera

- 1/3" Sony Super HAD CCD
- Resolution: 560 TV lines
- Mini illumination: 0.05 Lux (F1.2, 30IRE)
- AGC, ATW, BLC, Flickerless
- OSD menu, DNR, Privacy zone, Motion detection
- 12 VDC Input Voltage

CA2C-250PT **NEW**



High Resolution 25x Zoom Camera

- 1/3" Sony Super HAD CCD
- 1/3" CCD, Color,
- 580TV Lines
- 25X optical zoom lens, 10X digital zoom
- 0.5Lux(color), 0.1lux(B/W), 0.0005Lux(DSS 128X),
- TDN, DNR, Privacy Zone, Motion Detection
- PAL

CA2C-270PT **NEW**



High Resolution 27x Zoom Camera

- 1/3" Sony Super HAD CCD
- 1/3" CCD, Color,
- 580TV Lines
- 27X optical zoom lens, 10X digital zoom
- 0.5Lux(color), 0.1lux(B/W), 0.0005Lux(DSS 128X),
- TDN, DNR, Privacy Zone, Motion Detection
- PAL

CA2C-350PT **NEW**



High Resolution 27x Zoom Camera

- 1/3" Sony Super HAD CCD
- 1/3" CCD, Color,
- 580TV Lines
- 27X optical zoom lens, 10X digital zoom
- 0.5Lux(color), 0.1lux(B/W), 0.0005Lux(DSS 128X),
- WDR, TDN, DNR, Privacy Zone, Motion Detection
- PAL

VBC-800PI50-WC **NEW**



High Resolution Mini Box Camera

- 25 – 30m IR visible range
- Anti-flare double glass
- Intelligent IR compensation
- 4 – 9mm vari-focal lens
- 12 VDC input voltage
- IP66
- Wall mount and ceiling mount support

VBC-800PI30-WC **NEW**



High Resolution Mini Box Camera

- 40 – 50m IR visible range
- Anti-flare double glass
- Intelligent IR compensation
- 9 – 22mm vari-focal lens
- 12 VDC input voltage
- IP66
- Wall mount and ceiling mount support



VBC-800PI



High Resolution Mini Box Camera

- 1/3" Sony Super HAD CCD
- Resolution: 540TV lines
- 25m IR Visible Range
- Anti-flare Double Glass
- Intelligent IR Compensation
- IP66, 12VDC Input Voltage

CADC-600PWW



High Resolution WDR Varifocal Dome Camera

- 1/3" Sony Super HAD CCD
- 600TV Lines
- Day & Night
- WDR
- Varifocal lens 3.8 ~ 9.5mm
- 0.1 Lux (Color) 0.05Lux(B/W) / 0.0002 Lux (DSS On, B/W)
- Dual Power, PAL

ANALOGUE CAMERAS

VDC-600P



High Resolution WDR Fixed Dome Camera

- 1/3" Sony Super HAD CCD
- More than 540TV Lines Horizontal Resolution
- Day & Night
- BMB™, WDR, DNR
- Privacy Zone Masking, Motion Detection, Digital Zoom
- Lens (Fixed : 3.6mm / 6.0mm)
- 12 VDC input voltage

CADC-600PV **NEW**



High Resolution Varifocal Dome Camera

- 1/3" Sony Super HAD CCD
- 600TV Lines
- Day & Night
- Varifocal lens 3.8 ~ 9.5mm
- 0.1 Lux (Color) 0.05Lux(B/W) / 0.0002 Lux (DSS On, B/W)
- Dual Power, PAL

CADC-560P **NEW**



High Resolution Mini Dome Camera

- 1/3" SONY Super HAD CCD
- 560 TV lines
- Optional 2.5mm, 3.8 mm, 6mm fixed lens
- 0.05 Lux (F1.2, 30IRE)
- AGC, ATW, BLC
- 12 VDC input voltage

VDC-400P



Color Dome Camera

- 1/3" Sony Super HAD CCD
- 480 TV line High Horizontal Resolution
- Built-in fixed lens (f=3.8mm)
- Automatic white balance
- Dome size: 68mm
- Min illumination: 0.3 Lux
- Surveillance angle: 3-axis adjusting mechanism

CADC-350PIV-V **NEW**



Hig Resolution Vandal-Proof IR Varifocal Dome Camera

- 1/3" SONY Super HAD CCD, 540 TV lines
- 4 – 9mm vari-focal lens
- 10 – 15m IR visible range
- 0 Lux (IR LED ON)
- Anti-flare double glass
- Intelligent IR compensation
- 12 VDC input voltage

CADC-350PI-V **NEW**



Hig Resolution Vandal-Proof IR Fixed Dome Camera

- 1/3" SONY Super HAD CCD, 540 TV lines
- 3.6 / 6 / 8 mm fixed lens
- 10 – 15m IR visible range
- 0.1 Lux (IR LED OFF) / 0 Lux (IR LED ON)
- Anti-flare double glass
- Intelligent IR compensation
- 12 VDC input voltage

👍 VDC-350PI



IR Indoor Fix Dome

- 1/3" SONY Super HAD CCD, 540 TV lines
- 3.6mm Fixed Lens
- 15m IR Visible Range
- 0.1Lux/F1.2 (IR LED OFF), 0Lux (IR LED ON)
- Anti-flare Double Glass
- Intelligent IR Compensation
- 12 VDC Input Voltage

👍 HSPT-120P



Weather-Proof Mini Pan/Tilt Speed Dome

- 90mm diameter dome
- High performance 530TVL resolution, day&night, DNR
- Full directional pan and tilt: Pan 360° endless rotation up to 30°/s, tilt 0°~90° up to 30°/s
- Ultra-low noise; No picture shake, 32 preset, 6 groups of programmable tours

VSD-100/101P



Hi-Res 10x PTZ Dome Camera

- 1/4" Sony Super HAD CCD
- 10x Optical zoom, 16 Digital zoom
- More than 540TV lines
- Illumination of 0.001 lux
- TDN(ICR), WDR, BMB™, DNR
- 240 preset, 8 pattern, 8 tour, 8 scan, 32 privacy zone
- present speed: max. 400°/sec
- self calibration
- Vandal-proof roof and IP 67 (VSD-101P)

PTZ DOME CAMERAS

VSD-181P



Weather Proof High Res 18x PTZ Dome Camera

- 1/4" Sony EXview CCD
- 18x Optical Zoom, 12x Digital Zoom
- More than 480TV Lines
- Minimum Illumination of 0.01lx
- True Day & Night (ICR)
- 128 preset, 3 pattern, 6 Scan
- 360° continuous rotation
- IP66

VSD-261P



Weather Proof High Res 26x PTZ Dome Camera

- 1/4" IT CCD SONY, 480TVL (Color Mode), 520TVL(B/W Mode)
- ICR True Day/Night,
- IP66 Standard Lighting & surge protector. High strength metal housing, Heater and Fan
- High Speed
- 128 Preset positions, 24 Privacy Mask Zone
- Hot plugging technology , Digital turn over function, Built-in multi protocol.

VSD-361P



Weather Proof High Res 36x PTZ Dome Camera

- 1/4" IT CCD SONY, 480TVL (Color Mode), 520TVL(B/W Mode)
- ICR True Day/Night,
- IP66 Standard Lighting & surge protector. High strength metal housing, Heater and Fan
- High Speed
- 128 Preset positions, , 24 Privacy Mask Zones
- Hot plugging technology , Digital turn over function, Built-in multi protocol.

DIGITAL VIDEO RECORDER

HD-DVR-1004

NEW



4 Channel mobile enable DVR, HDMI output

- Support TV, VGA and HDMI output simultaneously
- 4 channels, 100/100 CIF
- All 4 channels support CIF resolution recording, first channel supports D1 resolution recording
- Support cross network video image live view, configuration, searching and PTZ control
- Mobile surveillance software available for remote access easily anywhere
- support max 1 HDD slots, 2 USB slots
- Alarm activation supports triggered recording, short message
- Web access ease-of-use operation
- Smart video detection: motion detection, camera blank, video loss

HD-DVR-1016

NEW



16 Channel mobile enable DVR, HDMI output

- Support TV, VGA and HDMI output simultaneously
- 16 channels, 400/400 CIF
- All 16 channels support CIF resolution recording, 1st & 9th channel supports D1 resolution recording
- Support cross network video image live view, configuration, searching and PTZ control
- Mobile surveillance software available for remote access easily anywhere
- support max 1 HDD slots, 2 USB slots
- Alarm activation supports triggered recording, short message
- Web access ease-of-use operation
- Smart video detection: motion detection, camera blank, video loss

ENTERPRISE DVR

HD-16DVR-C

NEW



16 Channel mobile enable DVR, HDMI output

- Support TV, VGA and HDMI output simultaneously
- 4/16 channels video recording continuously for one month
- All 4 channels support CIF resolution recording, first channel supports D1 resolution recording
- Support cross network video image live view, configuration, searching and PTZ control
- Mobile surveillance software available for remote access easily anywhere
- support max. 4 HDD slots, 2 USB slots
- Alarm activation supports triggered recording, short message
- Web access ease-of-use operation
- Smart video detection: motion detection, camera blank, video loss

CONTROLLER

HD-JC-010



Keyboard controller, Joystick

- Support Honeywell DVR: HSVR-04 / 16, HD-DVR-1004 / 1016, HD-16DVR-C
- Network connection
- Joystick control for pan, tilt and zoom of PTZ cameras
- Preset Position, Auto Pan, Auto Tour & Pattern Control
- Multi-screen operation for DVR
- LCD screen for menu and operation display

LENS







CALA3580F14/28120F16 **NEW**
/50500F14









1/3" CS-Mount Auto Iris Lens

- 3.5~8mm lens (CALA3580F14), F1.4
- 2.8~12mm lens (CALA28120F16), F1.6
- 5.0~50mm lens (CALA50500F14), F1.4







CAMERA SELECTION

	Dome Camera					
	HDC-895PV	CADC580PWV	CADC580PTWV	CADC600P	CADC600PV	CADC600PTV
Images						
Indoor / Outdoor	Indoor	Indoor	Indoor	Indoor	Indoor	Indoor
Image Sensor	1/3" Interline Transfer CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD
Lens	2.8 - 10mm	3.8 - 9.5mm	2.8 - 10.5mm	2.5 / 3.8 / 6mm	3.8 - 9.5mm	2.8 - 10.5mm
TV Line	580TVL	Color: 580TVL B/W: 650TVL	Color: 580TVL B/W: 650TVL	Color: 600TVL B/W: 650TVL	Color: 600TVL B/W: 650TVL	Color: 600TVL B/W: 650TVL
Effective Pixel	752 (H) x 582 (V)	752 (H) x 582 (V)	752 (H) x 582 (V)	752 (H) x 582 (V)	752 (H) x 582 (V)	752 (H) x 582 (V)
Min. Illumination	1.0 Lux (50IRE), 0.01 Lux (DSS), 0.001 Lux (TDN, DSS)	0.05 Lux (Color), 0.03 Lux (B/W), 0.0002 Lux (B/W, DSS On), F1.2, 30IRE	0.05 Lux (Color), 0.02 Lux (B/W), 0.0002 Lux (B/W, DSS On), F1.2, 30IRE	0.05 Lux, F1.2, 30IRE	0.05 Lux, F1.2, 30IRE	0.05 Lux (Color), 0.01Lux (B/W), F1.2, 30IRE
Day / Night	SDN	SDN	TDN	SDN	SDN	TDN
Optical Zoom						
Digital Zoom		6x	6x			
PTZ						
WDR	0 - 20 adjustable	Low / Middle / High	Low / Middle / High			
BLC	Off / Low / Middle / High	Off / Low / Middle / High	Off / Low / Middle / High	Off / Low / Middle / High	Off / Low / Middle / High	Off / Low / Middle / High
White Balance	ATW / AWC / One-push Lock / Indoor / Outdoor / Manual	ATW / Manual / Push	ATW / Manual / Push	ATW / Manual / Push	ATW / Manual / Push	ATW / Manual / Push
Privacy Zone	8 zones	On / Off (8 programmable zones)	On / Off (8 programmable zones)	On / Off (4 programmable zones)	On / Off (4 programmable zones)	On / Off (4 programmable zones)
Motion Detection	Yes	On / Off (4 programmable zones)	On / Off (4 programmable zones)	On / Off (4 programmable zones)	On / Off (4 programmable zones)	On / Off (4 programmable zones)
IR						
Stablizer		On / Off	On / Off			
Vandal						
OSD	English / Japanese / Korean / Chinese	English / French / Spanish / Korean / Russian / Chinese /	English / French / Spanish / Korean / Russian / Chinese	English, Chinese	English, Chinese	English, Chinese
Housing						
Input Voltage	12VDC / 24VAC	12VDC / 24VAC	12VDC / 24VAC	12VDC / 24VAC	12VDC / 24VAC	12VDC / 24VAC
Mounting						

CAMERA SELECTION

	IR Camera					
	VDC-350PI	VDC-350PI-V	VDC-350PIV-V	VBC-800PI	VBC-800PI30-WC	VBC-800PI50-WC
Images						
Indoor / Outdoor	Indoor	Indoor	Indoor	Outdoor	Outdoor	Outdoor
Image Sensor	1/3" Sony CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD	1/3" Sony Super HAD CCD
Lens	3.6mm	3.6 / 6 / 8mm	4 - 9mm	4 - 9mm	4 - 9mm	9 - 22mm
TV Line	540TVL	Color: 540TVL, B/W: 600TVL	Color: 540TVL, B/W: 600TVL	Color: 540TVL B/W: 600TVL	Color: 540TVL B/W: 600TVL	Color: 540TVL B/W: 600TVL
Effective Pixel	752 (H) x 582 (V)	752 (H) x 582 (V)	752 (H) x 582 (V)	752 (H) x 582 (V)	752 (H) x 582 (V)	752 (H) x 582 (V)
Min. Illumination	0.1 Lux/F1.2 (IR Led Off), 0 Lux (IR Led On)	0 Lux (IR Led On) / 0.1Lux (IR Led Off)	0 Lux (IR Led On) / 0.1Lux (IR Led Off)	0.3 Lux/F1.2 (IR Led Off), 0 Lux (IR Led On)	0 Lux (IR Led On) / 0.1Lux (IR Led Off)	0 Lux (IR Led On) / 0.1 Lux (IR Led Off)
Day / Night	SDN	SDN	SDN	SDN	SDN	SDN
Optical Zoom						
Digital Zoom						
PTZ						
WDR						
BLC	Auto	Auto	Auto	Auto	Auto	Auto
White Balance	Auto	Auto	Auto	Auto	Auto	Auto
Privacy Zone						
Motion Detection						
IR	10 - 15m	10 - 15m	10 - 15m	25 - 30m	25 - 30m	40 - 50m
Stablizer						
Vandal		Vandal Proof	Vandal Proof			
OSD						
Housing		IP66	IP66	IP66	IP66	IP66
Input Voltage	12VDC	12VDC	12VDC	12VDC	12VDC	12VDC
Mounting				Wall	Wall / Ceiling	Wall / Ceiling

CAMERA SELECTION

	Speed Dome					
	HSPT-120	VSD-181P	VSD-261P	VSD-361P	CASD270PT-I	CASD270PT-O
images						
Indoor / Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Indoor	Outdoor
Image Sensor	1/4" Sony Super HAD CCD	1/4" ExView HAD CCD	1/4" ExView HAD CCD, Sony	1/4" IT HAD CCD, Sony	1/4" Sony Super HAD CCD	1/4" Sony Super HAD CCD
Lens	6mm	3.1 - 73.8mm	3.5 - 91mm	3.6 - 129.6mm	3.6 - 97.2mm	3.6 - 97.2mm
TV Line	530TVL	>480TVL	Color: 480TVL B/W: 520TVL	Color: 480TVL B/W: 520TVL	Color: 580TVL B/W: 600TVL	Color: 580TVL B/W: 600TVL
Effective Pixel	752(H) x 582(V)	752(H) x 582(V)	752(H) x 582(V)	752(H) x 582(V)	752(H) x 582(V)	752(H) x 582(V)
Min. Illumination	1 Lux (50IRE)	0.01 Lux (50IRE, TDN off, DSS)	1 Lux / 1/50sec (ICR-OFF) 0.07 Lux / 1/3sec (ICR-OFF) 0.15 Lux / 1/60sec (ICR-ON) 0.01 Lux / 1/3sec (ICR-ON)	1 Lux (30IRE, IR Cut Filter On) 0.1Lux (30IRE IR Cut Filter Off) 0.001 Lux (DSS x 256-ON) 0.0001 Lux (30IRE, Night ON+DSS)	0.5 Lux (Color 30IRE) / 0.1 Lux (B/W 30IRE) / 0.0005 Lux (DSS on, 30IRE)	0.5 Lux (Color 30IRE) / 0.1 Lux (B/W 30IRE) / 0.0005 Lux (DSS on, 30IRE)
Day / Night	SDN	TDN	TDN	TDN	TDN	TDN
Optical Zoom		18x	26x	36x	27x	27x
Digital Zoom		12x	12x	12x	10x	10x
PTZ	PT	PTZ	PTZ	PTZ	PTZ	PTZ
WDR						
BLC			On / Off	On / Off	Normal / C,L,U,D,R High / Low (5 Area Selectable)	Normal / C,L,U,D,R High / Low (5 Area Selectable)
White Balance		Manual / ATC / ATW	Auto / Manual / Indoor / Outdoor / ATW	Auto / Manual / Indoor / Outdoor / ATW	Auto / Manual	Auto / Manual
Privacy Zone					8 zones	8 zones
Motion Detection						
IR						
Stablizer						
Vandal						
OSD					On / Off	On / Off
Housing	IP66	IP66	IP66	IP66		IP66
Input Voltage	24VAC	24VAC	24VAC	24VAC	24VAC	24VAC
Mounting		Wall / Ceiling / Pole	Wall / Ceiling / Pole	Wall / Ceiling / Pole	Wall / Pendant / Flush / Ceiling	Wall / Pendant

Honeywell *Black*

www.telefeeling.com

A One Stop Solution

For small to medium scale application

Distributed by:

TELEFEELING COMMUNICATION SDN BHD

Tel : 03-9131 303

Fax : 03-9133 2030

Info@telefeeling.com

www.telefeeling.com