


KOCOM Products

Home Network Home Automation Videophone Interphone & Doorphone CCTV System LED Lighting System

























Head Office

KOCOM Bldg., 260-7 Yumchang-Dong, Kangseo-Gu,


Seoul 157-040, Korea

TEL +82-2-6675-2211 +82-2-6675-2000 Homepage http://www.kocom.com export@kocom.co.kr

* This catalogue is based on the date as shown in the right and specifications are subject to change without notice for quality improvement. 2009.05



Since1976
MANAGER





2009 / 2010's

Home Network Type I **High-end Home Network Solution** Chiefly composed of main display (KHN-880 / 870 / 671 Wall-pad) and the home gateway comprehending inside and outside homenetwork, KOCOM high-end Home Network Solution wholly provides major services indispensable for realizing highly elegant intelligent home. C Digital Doorlock METRO Back Bone AV Settop Box Display Unit

The system configuration can be changed according to the house and its place.

* The periaherals and accessories are optional.

Wall-Pad



KHN-970

- 7" TFT LCD Touch Screen (GUI)
 Remote Control of Entrances (Access Control)
 Security and Accident Detection System
 Control of Household Appliances & Living Equipment
 Home Entertainment: Wired and Wireless Network Unmanned Security & Parking Control
- Mutual Calling & Conversation Between Residents
 Life Information / Telephone





KHN-880

- 10" TFT LCD Touch Screen (GUI)
 Remote Control of Entrances (Access Control)
 Security and Accident Detection System
 Control of Household Appliances & Living Equipment
 Home Entertainment: Wired and Wireless Network
 Unmanned Security & Parking Control
- Mutual Calling & Conversation Between Res
 Life Information / Telephone



KHN-671

- 7" TFT LCD Touch Screen (GUI)
 Remote Control of Entrances (Access Control)
 Security and Accident Detection System
 Control of Household Appliances & Living Equipment
 Home Entertainment: Wired and Wireless Network
- Unmanned Security & Parking Control
- Mutual Calling & Conversation Between Resident





KHN-870

- T"TFT LCD Touch Screen (GUI)
 Remote Control of Entrances (Access Control)
 Security and Accident Detection System
 Control of Household Appliances & Living Equipment
 Home Entertainment: Wired and Wireless Network
- Unmanned Security & Parking Control
- Mutual Calling & Conversation Between Residents

Gateway








KHG-108 / 112 / 116

- Home Control Lights, Heater, Gas, Curtain and Electrical Appliance (Option)
 Network Switching Hub (10/100 Mbps), NAT/IP Masquerading, DHCP Server & Client, Web Server
- BS485, PLC (Z-256 / Lonworks, LnCP).

KHG-1000

- Home Control Lights, Heater, Gas, Curtain and Electrical Appliance (Option)
 Network Switching Hub (10/100 Mbps), NAT/IP Masquerading, DHCP Server & Client, Web Server BS485, PLC (Z-256 / Lonworks, LnCP)

- KHU-305
- Access & communication main device between apartment, guard master and integrated access device
 Upto 960 apartments and 80 Lobby phones (Entry Access Panel) connection



Controller & Switch



KAR-4000

- Operating Speed: 250mm/sec (8Ms base : about 12sec.)
 Length : 8Ms (Single Motor), 20M (Tandem Motor)
 Communication Interface: RS-485
- Power: DC 24V
 Power Consumption : 38W (in operation)
 Control speed: 10-Step









KP-IR100 / RH29

- KP-IR100

 Dome Housing Type Surface Mount
 IR Emission : Omni-Direction RH29
- RH29

 Communication: IrDA Function

 Home Appliance Control: Air Conditioner, TV

 Audio / Video Channel & Volume Control

 Lighting, Curtain, Gas Valve Control









KSR-4200 / 4301 / 4300

Tilting function: You can control blinds tilting only by pushing button.
Buzzer Sound / Mute: You can check the opened and closed status of up to 8 curtains in real time through the LCD screen.
No Need Wring: You can Easily attach it to the desired location without the need of connecting cables.





KV-3011 / 3012

- Power : AC 90V~240V. 50/ 60Hz

- KV-5014 / KV-5021 / 5022
- Power: AC 90V-240V, 50 / 60Hz KVR-5014 On / Off 1 Circuit, 4 Lamp Lighting Control KVR-5021 Dimming 1 Circuit, 1 Lamp Dimming Control KVR-5022 Dimming 2 Circuit, 2 Lamp Dimming Control

- KV-0404
- Power: AC 90V-240V, 50 / 60Hz
 Control Circuit: Dimming & On / Off 4 Circuit,
 Dimming Circuit 2000W (Max. 1000W each circuit)
 Turn on / off Circuit 2000W (Max. 500W each circuit)
- Incandescent Lamp, Magnetic low voltage Halogen Lamp Fluorescent Lamp (with Dimming Ballast)









KL-0400 / 0800

- Power: AC 90V~240V, 50 / 60Hz
- KL-0400 : Dimming & On / Off 4 Circuit KL-0800 : Dimming & On / Off 8 Circuit

Controller

- Remote control-Working type: Infrared-ray communication
- Operating distance: 6m
 Power supply: 3V, Lithium (CR-2025)

KSR-800

- 4.3" TFT LCD
- CPU-Samsung ARM9 400MHz
 NAND Flash memory: 128MB / SDRAM: 64MB
 OS: Windows CE 5.0 Professional





- Communication with Guardroom Master Phone (KAM-305)
 Communication between Mutual Interphone (KIP-305)
 Operation: Telephone Type (10key button), Handsets Type













Security Sensor & Gas Controller

- Gas leakage sensor

 Motion sensor

 Burglar sensor

 Fire sensor

- **Dead Bolt Lock**
 - Automatically Opening Common Gate in Emergency Alarm
 Automatically Canceled the Locking of Common Gate in Fire Alarm

Home Automation

Hands Free Type Home Autor



KHV-478

- Color 7" TFT LCD
 Function to identify visitor and prevent crime (fire, gas, security sensor)
 Function to open common gate


- Function to open common gate as well as household door Available communication with guard Available identifying absent households at guard room Emergency call / Telephone function





KHV-458 / KCV-358

- Color 5" TFT LCD
- Function to identify visitor and prevent crime (fire, gas, security sensor : KHV-458)
 Function to open common gate
- as well as household door
- Available communication with guard Available identifying absent
- households at quard room



Lobby Phone & Guard Master



one (Entry Access Panel) **KLP-305**

- Call & communication wtih resident & guard
- LCD display (apartment no. & communication status)
 Gate open by password & RF card (Option)
 Lobby phone based in SIP (Option)



Bathroom Phone Home Aut



KAM-305

- Call & communication with resident & visitor

- LDD display (apartment no. & event details display in the call & event)
 Gate open in communication with visitor
 Parking management system interlocking (Option, RS485)

KBP-105

- Private door camera/Lobby phone communication
- Emergency call
 Receiving the general phone
 Water proof cover
 Door open

Sub Phone & Kitchen TV Phone



KSP-230

- 4" TFT LCD Handsfree Communication 4" 1F1 LCD Handstree Communication
 Visitor Identification & Communication through
 Front Door & Common Gate Camera
 (Lobby phone) and Door Open
 Mutual Call and Communication with Guard
 Emergency Call Function



KSP-270

- 7" clor TFT LCD

- /* rior IFT LCU
 Handsfree Communication
 Adjustable Monitor Screen Angle (Left 90 */ Right 90 *)
 Message Recording & Radio / Auto Scanning for TV
 Interlocking with Home Network & Automation System
 Call & Communication with Visitor (door open) & Guard
 Telephone Function



KTD-510/512

- KTD-510 : 7" Color TFT LCD / KTD-512 : 10" Color TFT LCD

KTD-510: "Color TFT LCD / KTD-512: 10" Color TFT Handsfree Telephone Function Auto Scanning for TV & Radio Message Recording Time, Channel & Condition Display Interlocking with Home Network & Automation System Call & communication with Visitor (door open) & Guard

Door Lock





KDL-T1

- I-Button touch key & Access code

- Anti-prank feature
 Panic (One touch open)
 Dual & compulsory locking mode
 Manual unlocking mode



Finger Print Type KDL-F1

- RF card & Access code
 Anti-prank feature
 Panic (One touch open)
 Dual & compulsory locking mode
 Manual unlocking mode
- Finger print & Access code
 Anti-prank feature
 Panic (One touch open)
 Dual & compulsory locking mode
 Manual unlocking mode

Handset Type Security Phone Home Videophone



KCV-802R / D802R

- 7 7inch Color LCD (NTSC / PAL Auto Switching)
 For Single House, Multi Apartment Condominium & Villa System(upto 450 units)


- viiii 3ysietrii (pito 450 Uniis) Upto 4 Indoor Uniis Including Audio Sub Phones with 2 Door Cameras & 10 Common Gate Cameras Connection Internal Call & Conversation between Extended Indoor Units Door Open & Monitoring Function(Door Camera
- & Common Gate Camera)
 Telephone Function(PABX)
- Call & Conversation with Guard Master Phone (KIP-120)
- 18 Melody Selection (24 Poly Melody) Extra Speical Function Key Button Built-in 128 Cut Images Memory
- OSD (On Screen Disply) Menu Control KCV-802R : AC Type / KCV-D802R : DC Type



Videophone

Bus Type Multi-Entry System Home Videophone





KVM-520 / D520


- 4" CRT B/W VDP For single house & multi apartment Internal call & conversation function between extended indoor units in a house
- Door open (common gate) function KVM-520 : AC Type / KVM-D520 : DC Type





- 5" TFT LCD Color Handsfree VDP

- 5" TFT LCD Color Handsfree VDP For single house & multi apartment Internal call & conversation function between extended indoor units in a house Door open (front door & common gate) function KIV-212: AC type / KIV-D212: DC type 2 Camera connection (front door camera)





KIV-102 / D102

- 4" CRT B/W Handsfree VDP

- 4" CRT BW Handstree VDP For single house & multi apartment Internal call & conversation function between extended indoor units in a house Door open (front door & common gate) function KIV-102 : AC type / KIV-D102 : DC type

- 2 Camera connection (front door camera)

Bus Type Multi-Entry System Home Videophone




Common gate camera




Common gate camera

(a) KLP-P100(B/W) (b) KLP-P104(B/W) (c) KLP-P108(B/W) (d) KLP-P112(B/W)



Handset Type





KCV-801R / D801R / 801 / D801

- 7 inch Color LCD
 LED Indication in Conditions
 4 Melody Selection
 OSD Menu Control
 PIR Sensor Camera & CCTV Camera Connection
 CCTV Monitoring Mode
 Built 128 Cut Images Memory (KCV-801R, KCV-D801R)
 Auto Record in Absence Mode (KCV-801R, KCV-D801R)
 Upto 2 Monitor & 2 Audio Sub Phone with 2 Cameras Connection
 Internal Call & Conversation between Extended Indoor Units

- Internal Call & Conversation betwee AC Type: KCV-801R, KCV-801 DC Type: KCV-D801R, KCV-D801



KVM-301 / D301

KCV-W354 / DW354

- Compact & Stylish Design
 Digital Color LCD
 Digital Color LCD
 Sub in Operating Condition
 Ultra Luw Power Consumption (0.7W on Standby)
 Long Distance Connection upto 100m (UTP, CAT5)
 Either Monitor or Camera Door Lock Connection Availability
 Internal Call & Conversation between Extended Indoor Unit
 Little & Ledoc Leit with & Camera Connection

 Camera Connection Control Control

 Connection Connection Control

 Little & Ledoc Leit with & Camera Connection

 Connection Connection

 Connection Connection

 Connection Connection

 Connection Connection

 Connection Connection

 Connection Connection

 Connection

 Connection Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection

 Connection
- Upto 4 Indoor Unit with 2 Camera Connection 5 Melody Selection CCTV Monitoring Mode

Memory & B/W Type Home Videophone



- 4 inch CRT B/W Videophone
 External 64 Cut Memory Equipment Connection
 Internal Call & Conversation between extended Indoor Units
 Audio & video Conversation with Visitor
 Door open & Monitoring Function
 5 Melody Selection, Security Sensor Connection

- 5 Melody Selection, Security Sensor Connection
 PIRI Sensor Camera, CCTV Camera Connection
 CCTV Monitoring Mode, Camera Selection
 Doorlock Connection Eighter Monitor or Camera
 Upto 2 Monitors & 2 Audio Sub Phones with 2 Cameras Connection
 AC Type: KVM-301 / DC Type: KVM-D301

External Memory Equipment (32M DRAM) Upto 64 Cut frame Record Play & Record (Manual & Automatic) Function Date Setting (Year / Month / Day) Connection with KVM-301 / KVM-D301 Monitor

KVR-300

Ø 🔵 ā 📵

æ 📵 ē 🔵

- **KDP-602G** Extension Sub Doorphone Audio Conversation with Door Camera Internal Call & Converstation
- Door Open


Multi-Entry Panel



Easy Access of Gate using "I"

KVL-C302i / C303i / C304i / TC306i / KVL-TC308i / KEL-312 / T324

- Modern & Stylish Design
 Call, Communication & Door Open with Monitor
 Door Open by I-Button Key (Dallas Chip)
 Max. 1,300 Numbers of I-Button Key Registration.
- White LED On in Low Illumination. Name Plate LED On in Operation
- Camera Angle Adjustable (Up, Down, Right & Left).
 Receiving & Calling Audio Volume Adjustable.
 Door Lock Connection



B/W Handset Type Home Videophone



KVM-524RG

- 4" CRT B/W VDP
 64 cut memory VDP
 Internal call & converse
- on function between extended indoor units in a house
- Door open function KVM-524RG : AC type
- 2 Camera connection

2 Wire Color Hands Free Type Home Videophone



- 2 wires (Non-polanty)

 Digital Color LCD

 OSD in Operating condition

 Ultra Low Power Consumption
 (0.7W on standby)

 Long Distance Connection upto 100m (UTP, CAT5)

 Either Monitor or Camera Door Look Connection Automatic Wiring & Installation Check with Sounds







2 Wire Multi-Entry Panel Home Videophone

KVL-C202i / C203i / C204i / KEL-212

KVM-604

4" CRT R/W VDP

- Modern & Stylish Design
 Easy & Simple Installation with 2 Wires
 Call, Communication & Door Open with Monitor
 Door Open by I-Button Key (Dallas Chip)
 Max. 1,300 numbers of I-Button Key registration.
 White LED On in Low Illumination.
- Name Plate LED On in operation Camera Angle Adjustable (Up. Down, Right & Left).
- Receiving & Calling Audio Volume Adjus
- Long Distance Connection

Easy Access of Gate using "I" Buttor Touch Key

KVI -SV30

@ KEL-212

| Door Camera

■ Color Door Camera









KC-MC22 (2Wire) KC-MC32 (2Wire) KC-MC24 (4Wire) KC-MC30 (4Wire)



KC-MC20 (4Wire)



KC-MC31 (4Wire)

■ B/W Door Camera



KC-C63 (4Wire) **KC-B61** (4Wire)



KC-D20 (4Wire)





KC-MB30 (4Wire) KC-MB20 (4Wire) KC-D33 (4Wire)



Doorphone Interphone

Multiple & Single Doorphone



KIP-603/KDP-100/104/108/112

- For multi apartment, condominium &

- For multi apartment, condominium & villa system, upto 450 houses are available. Up to 3 indoor extension in a house Internal call & conversation function between extended indoor units in a house Audio conversation with visitor.
- Door open (common gate) function
- Call & conversation function with guard master : KIP-120
- Communication with door panel DS2D & Common gate panel : KDP-603

000 000 (b) KLP-1000 a KDP-205

KDP-205/KLP-1000

KDP-205 • For multi apartment, condominium & villa system, upto 585 houses are available • Audio conversation with visitor

Door open (common gate) function
Call & conversation function with guard (KLP-1000)

KLP-1000

Door open function by access code
Firm metal body case with new modern design

Up to 2pcs of common gate panel connection in a building

...

MSD-3B



KIP-222/KDP-602A/D

 Duplex interphone & doorphone
 Audio conversation with visitor
 Door open function
 Internal call & conversation with extended units Gentle electronic sound (seperate call sound) Easy installation (mount on the wall or desk)

KDP-602A / D • Triplex interphone & doorphone Upto 2 audio handset with 1 outdoor panel connection Same function with KIP-222

Doorphone **Outdoor Panel Series**



DP-203HA / KDP-501A / KDP-601A

- Audio conversation with visitor
 Door open function
 Upto 3 audio handset with outdoor panel connection
- 4 melody selection (DP-906H)

- Gentle electronic sound

- Easy installation (mount on the wall or desk)
 DC 12V Type available: DP-203HD (DC 12V)

MSD-1B/2B



Aluminum outdoor panel
1 house (MSD-1B) Upto 2 house (MSD-2B) Upto 3 house (MSD-3B) Upto 4 house (MSD-4B)



KC-MD12/14

- Rain proof, metal anti vandal proof
 Flush & surface mounting
 Upto 2 house (KC-MD12)
 Upto 4 house (KC-MD14)

· KC-MD14 KC-MD12







KIP-612MI

| · ·

MSD4B







© KC-MD20

KIP-605PG

DS-4M

Interphone

Multiple Interphone



IP-201P / KIP-501P / KIP-601P

- Duplex interphone
- Gentle electronic sound Easy wiring & installation (mount on the wall or desk)



KIP-612ML/IP-200PC

- 12Ch Multiple interphone Master & sub phone syster Master : KIP-612MBL
- Master : NIP-012/IDL
 Sub : IP-200PC
 Gentle electronic sound
 Easy wiring & installation (mount on the wall or desk)



KIP-611PG / 605PG

- 5 Ch multiple interphone : KIP-605PG
- 11 Ch multiple interphone : KIP-611PG
- Single or multiple connection
 All master intercom system
 Paging function
 Gentle electronic sound
- Easy wiring & installation(mount on the wall or desk)
 Outdoor panel, DS-4M connection

CCTV System

Zoom Camera CCTV



KZC-SPT271IN/ SPT2710UT

 1/4" Sonv Super HAD CCD (540TVL) · 30x Optical Zoom, 8x Digital Zoom



KZC-VISPT10/ VOSPT10

 1/4" Interline Transfer CCD, 500TVL(Min.) 10x Optical Zoom, 10x Digital Zoom



KZC-281

High Sensitive 1/4" Sony Hyper CCD
 410K Pixels (480 TV Lines)
 35x Optical Zoom, 12x Digital Zoom





KZC-221

1/4" Sony CCD
410K Pixels (480 TV Lines)
22x Optical Zoom, 10x Digital Zoom

IR Day & Night CCTV



KCC-IRV550

1/3" Super HAD IT CCD (SONY)540TVLOSD Menu

DC Auto iris lens (5~50mm)



KCC-IRV99

• 1/3" Sony Super HAD (480TVL) • IR LED 75 EA, Varifocal Lens (f:4~9mm)



KCC-IRD99

Dual (Color, B/W) mode camera
1/3" Sony Super HAD (480TVL)
IR LED 75EA



Varifocal(4~9 mm) IR Day & Night Camera

KCC-IRV24

C & CS Mount

1/3" Sony Super HAD (480TVL)
IR LED 24 EA, Varifocal Lens (f:4~9mm)



KCC-VP400

• 1/3" Sony Super HAD (480TVL) • Poly carbonate dome cover

Dome

KOCOM



KCC-D500HO

 1/3" Sony Super HAD CCD
 3-Axis Dome Camera
 High resolution 540 TV lines Varifocal lens (f: 4~9mm)



KCC-D400 /D300/KCB-D300

• 1/3" Sony Super HAD • KCC-D400 (480TVL), KCC-D300 (380TVL)

Color & B/W Dome camera

• KCB-D300 (B/W, 380TVL)

KCC-IRVP400V/300V

1/3" Sony Super HAD
 IR LED 24EA, Varifocal lens (f: 4~9mm)
 KCC-IRVP400V (480TVL)
 KCC-IRVP300V (380TVL)



KCC-VP400 ARIR

• 1/3" Sony Super HAD (480TVL)

Poly carbonate dome cover
 IR LED 21EA

KCC-IRVP400F/300F

1/3" Sony Super HAD
 IR LED 24EA
 KCC-IRVP400F (480TVL), KCC-IRVP300F (380TVL)



IR Day & Night Camera

KCC-3000

• 1/3" Sony Super HAD (480TVL) • IR LED 49 EA



KCC-IR49H / 49N



KCC-IB49H (480TVL) / KCC-IB49N (380TVL)



KCC-IR10 / IR10S

• 1/3" Sony Super HAD (380TVL) • IR LED 10EA



KCC-D61

• 1/3" Double Speed (WDR) CCD (SONY) · High Sensitivity, 550TVL(410K Pixels)





KCD-F850 / F750

 1/3" Interline Super HAD CCD (SONY)
 KCD-F850 (550TVL) KCD-F750 (380TVL)



KCD-F772IR

• 1/3" Interline Super HAD CCD (SONY)

IR LED 30EA



KCD-V850

1/3" Interline Super HAD CCD (SONY)
 550TVL

DC Auto iris lens (4~9mm)

C & CS Mount CCTV



KCC-D51

• 1/3" Sony Super HAD CCD (540TVL) SDNR (Super Digital Noise Reduction)



KCC-D41 / D27 / 41 / 27

True Day & Night camera (KCC-D41 / D27)
Normal camera (KCC-41 / 27)
1/3" Sony Super HAD

• KCC-D41 / 41 (480TVL), KCC-D27 / 27 (380TVL)



KCC-340 / KCB-340

 True Day & Night camera 1/3" Sony Super HAD KCC-340 : Color (480TVL) KCB-340 : B/W (600TVL)



KCC-S41 / S27

 Color ultra small C & CS Mount camera
 1/3" Sony Super HAD
 KCC-S41 (480TVL) KCC-S27 (380TVL)



KCD-V772IR

KCC-IBSD400 (480TVL)

• 1/3" Interline Super HAD CCD (SONY)

 DC Auto iris lens (4~9mm) • IR LED 24EA



KCV-F850

• 1/3" Interline Super HAD CCD (SONY)



KCV-V850

• 1/3" Interline Super HAD CCD (SONY)

· DC Auto iris lens (4~9mm)



KCV-V772IR

1/3" Interline Super HAD CCD (SONY)550TVL

 DC Auto iris lens (4~9mm) IR LED 24EA

CCTV System

Bullet Camera



KCC-DB41/B41/B27

- 1/3" Sony Super HAD
- KCC-DB41 (Day & Night, 480TVL)
 KCC-B41 (480TVL), KCC-B27 (380TVL)



KCC-VB41

- 1/3" Sony Super HAD (480TVL) Varifocal lens (f: 4~9mm)
- 1/3" Sharp CCD (480TVL) 50m Deep Under Water • IR LED 7EA

KCC-1000W

Mini Camera

KCS-B250



KCC-21CH

1/3" Sharp CCD (480TVL)



KCL-F190WX / P190

KCC-F190WX : Board Lens, Water Proof KCC-P190 : Cone Pinhole Lens

1/3" Super HAD CCD (Sony)



KCB-1000W KCB-100W

KCB-100P

KCB-1000W

- B/W 1/3" Sonv CCD (380TVL) KCB-1000W : water proof, IR LED 8EA
 KCB-100W : weather proof

KCS-B250 / P250 KCS-B250 : Board Lens KCS-P250 : Cone Pinhole Lens • 1/3" Super HAD CCD(SONY) • 550TVL



KCC-421 / P421(Color) KCB-421 / P421(B/W)

 1/3" (Color & B/W) Sony Super HAD (380TVL)

KCC-401 / P401 • 1/4" Sony Super HAD (380TVL)

Monitor



KMC-19B / 17B

- High resolution (1280 x 1024) Pixel pitch (0.294x 0.294mm)
- · Video IN / OUT (BNC) S-video IN / OUT

- VGA IN / Audio IN/OUT (L&R)
 Brighness 250cd / m2
 Contrast 700 : 1 (Typical)
 KMC-19B (19 "LCD), KMC-17B (17 "LCD)






KCS-P250

- GUI (Graphic Users Interface)
 Easy operation by mouse & remote controller
 Modified MPEG4
- Pentaplex
- Network (web browser view) function USB Backup

DVR System CCTV





KRS-HR09





KRS-HR16 Triplex (Live Display, Recording, Network)

- Triplex (Live Display, Recording, Network)
 H.264 Hardware Compression (High Quality Video)
 Embedded Linux Operating System
 Simultaneous Monitoring via Composite, VGA
 Backup and Firmware Update by USB drive
 Multiple Screen Division
 Easy to Use and Convinient GUI
 Fast Operation by Mouse and Remote Controller
 Network: DHCP & Static IP Supported
 Event Recording Midting Detection and Sensor.

Event Recording: Motion Detection and Sensor
 Network (Web Browser View) Function
 KRS-HR04 (4CH) / KRS-HR09 (9CH) /
KRS-HR16 (16CH)



KRS-SD2209/ **KRS-SD4416**

- MPEG4 Compression Technology
 Real-time Recording: 480FPS /16Ch [NTSC],
 400FPS / 16Ch [PAL], 270FPS / 9Ch(NTSC),
 225FPS / 9Ch(PAL)
 Graphic User Interface (GUI)
 Mouse Control
 Dut is Mexic (ACM).
- Built-in Matrix (4CH)
- KRS-SD2209 (9CH) / KRS-SD4416 (16CH)



KMAX-7160 / 7320

- External Alarm Device Available
 Direct Connection with System Contro
 DVR, VDA, etc.
- Easy Extension using RJ-45 Cable
 RS-485/422 PTZ Connection
- Equal Video Strength for All Outputs
- KMAX-7160 (16CH) / KMAX-7320 (32CH)

KVDA-7160

- Multi Type Input/Output Groups
 Equal Video Strength for All Outputs
 Unused Outputs are Self-terminating
 Color and B&W Compatible
 NTSC and PAL Compatible
 101 Beat Size

19" Rack Size
LED Indicator for Power & Video Input

DVR System

DVR (IP Camera) CCTV



KCD-800

- Distribute RS-485 Data Signal
- 1 Input x 8 Outputs
 Each Output Port drives up to 32 Devices LED Indicator for Power, Output and Error Detection

KCC-IP250

Vandal-Proof Dome Camera

1/3" Super HAD Color CCD With 410K Pixels
High Resoulution of 540TV Line



KCC-MIP20

- H.264/MJPEG compression
 2.0 Magapixel1/2.5" CMOS Image sensor
 Max full HD (1920x1080 30p) video
- with progressive scan

High Quality of H.264 compression Algorithm
 1/3" Super HAD Color CCD (540TVL)
 10x Optical Zoom, 10x Digital Zoom

DVR Borad



- KCC-MIP13
- H.264/MJPEG compression
 1.3" 1.3M Sony Progressive CCD
 WDR (Wide Dynamic Range) support



KCC-IP230

- 1/3" Super HAD Color CCD With 410K Pixels High Resoulution of 540TV Line





KZC-IPSPT10 (X10) KZC-IPSPT36 (X36)

- High Quality of H 264 compression Algorithm
- 1/3" Super HAD Color CCD (540TVL)
 36x Optical Zoom, 12x Digital Zoom



KDB-240240S

- **KVS-100**
- High quality H.264 AlgorithmFull-duplex audio/video transmis30fps/25fps @ full D1 resolution





- MPEG-4 Compression
- KRS-Series · KRS-P2432 (32CH, 240 / 240 µs) · KRS-P4116 (16CH, 480 / 120 fps) · KRS-P4216 (16CH, 480 / 240 fps)



KDB-480060S



KDB-060060S



Accessorv



KDB-120120S







KDB-120120S





Internal Sensor Board

KDB-240240S

Minicam



MINICAM-K700

- Car Black Box / Mini DVR / UCC Cam / MP4 Player





KH-5120S / 5120



KBR-1000



KBR-101

KBR-102 KBR-103

C-mount Lens



















KV-3580M KV-3580AD KV-3580AV KVL-3580AD KVL-0550AD KVL-2812AD





KJC-4000J

- Simple and Easy Installation Camera / DVR / Monitor Control 3-Axis Jov Stick
- S-As-485/422 Communicaton [Max. 1.2km]
 Multi-Protocol Support [Cyber Scan I, Cyber Scan II, P-D, P-P, etc]
 Easy Extension up to 6 Slave Controller





KCL-006 KCI -004

KCL-008

KCL-012 KCL-016



