

# SPECIFICATION

## LED LAMPS



### LED A70 Bulb-A70-54S0F


PLUTO

#### Features:

- High Brightness SMD LED's.
- Lamp housing – use efficient heat dissipation thermoplastic.
- Reduces energy and maintenance costs when compared to conventional light sources.
- Reduces energy consumption up to 80%.
- No warm up time, instant-on with full light output and consistency color temperature
- Contains no hazardous materials.
- 25,000 hours life at 70% lumen maintenance.
- Suitable for indoor use.
- Mercury, UV and IR free .
- CE, RoHS Compliance.

#### Applications:

Suitable for lighting in stations, clubs, stores, hotels, restaurants, office building, factories, residential, especially in the recessed down lighting and etc.



#### Specifications :

MODEL	A70-54S0F	A70-54S0F	A70-54S0F	A70-54S0F
Power Consumption	10W	10W	10W	10W
LED Quantity	54pcs SMD	54pcs SMD	54pcs SMD	54 pcs SMD
Color Temperature	2700K	3000K	4000K	6000K
Operating Voltage	220-240 Vac	220-240 Vac	220-240 Vac	220-240 Vac
Operating Current	110 mA	110 mA	110 mA	110 mA
Line Frequency	50Hz	50Hz	50Hz	50Hz
Power Factor	0.4	0.4	0.4	0.4
CRI	Ra80 / Ra90	Ra80 / Ra90	Ra80 / Ra90	Ra70 / Ra90
Initial Lumen	680lm/600lm	830lm/730lm	810lm/710lm	940lm/830lm
Dimmable	No	No	No	No
Bulb Finishing	Opal	Opal	Opal	Opal
Base	E27	E27	E27	E27
Average Lifetime	25,000h	25,000h	25,000h	25,000h
Operating Temperature	-20°C~45°C	-20°C~45°C	-20°C~45°C	-20°C~45°C
Dimension DxH	φ70x122mm	φ70x122mm	φ70x122mm	φ70x122mm
Net Weight	177g	177g	177g	177g
Replacement of GLS	60W	60W	60W	60W