

SPECIFICATION

LED LAMPS



LED A60 Bulb-A60-45S0P


PLUTO

Features:

- High Brightness SMD LED's.
- Lamp housing – use efficient heat dissipation thermoplastic.
- Reduces energy and maintenance costs when compared to conventional light sources.
- Reduces energy consumption up to 88%.
- No warm up time, instant-on with full light output and consistency color temperature.
- Contains no hazardous materials.
- 25,000 hours life at 70% lumen maintenance.
- Suitable for indoor use.
- Mercury, UV and IR free .
- CE, RoHS Compliance.

Applications:

Suitable for lighting in stations, clubs, stores, hotels, restaurants, office building, factories, residential, especially in the recessed down lighting and etc.



Specifications :

MODEL	A60-45S0P	A60-45S0P	A60-45S0P
Power Consumption	9W	9W	9W
Color Temperature	3000 K	4000 K	6000 K
Operating Voltage	220-240 Vac	220-240 Vac	220-240 Vac
Line Frequency	50Hz	50Hz	50Hz
Input current	85 mA	85 mA	85 mA
Power Factor	0.5	0.5	0.5
CRI	80	80	70
Initial Lumen	850 lm	880 lm	950 lm
Colour Code	830/5A	840/5A	760/5A
Lumen Maintenance	L70	L70	L70
Dimmable	No	No	No
PC Cover Finishing	Opal	Opal	Opal
Base	E27	E27	E27
Average Lifetime	25,000 h	25,000 h	25,000 h
Operating Temperature	-20°C~45°C	-20°C~45°C	-20°C~45°C
Dimension DxH	φ60x114 mm	φ60x114 mm	φ60x114 mm
Net weight	113g	113g	113g
Replacement Of GLS	75 W	75 W	75 W