SPECIFICATION

LED LAMPS




LED A60 Bulb-A60-35S0P

PLUTO

Features:

- High Brightness SMD LED's.
- Lamp housing use efficient heat dissipation thermoplastic.
- Reduces energy and maintenance costs when compared to conventional light sources.
- Reduces energy consumption up to 88%.
- No warm up time, instant-on with full light output and consistency color temperature.
- Contains no hazardous materials.
- 25,000 hours life at 70% lumen maintenance.
- Suitable for indoor use.
- Mercury, UV and IR free .
- CE, RoHS Compliance.





Suitable for lighting in stations, clubs, stores, hotels, restaurants, office building, factories, residential, especially in the recessed down lighting and etc.





Specifications:

| MODEL | A60-35S0P | A60-35S0P | A60-35S0P |
|-----------------------|-------------|-------------|-------------|
| Power Consumption | 7W | 7W | 7W |
| Color Temperature | 3000 K | 4000 K | 6000 K |
| Operating Voltage | 220-240 Vac | 220-240 Vac | 220-240 Vac |
| Line Frequency | 50Hz | 50Hz | 50Hz |
| Input current | 70 mA | 70 mA | 70 mA |
| Power Factor | 0.5 | 0.5 | 0.5 |
| CRI | 80 | 80 | 70 |
| Initial Lumen | 680 lm | 700 lm | 750 lm |
| Colour Code | 830/5A | 840/5A | 760/5A |
| Lumen Maintenance | L70 | L70 | L70 |
| Dimmable | No | No | No |
| PC Cover Finishing | Opal | Opal | Opal |
| Base | E27 | E27 | E27 |
| Average Lifetime | 25,000 h | 25,000 h | 25,000 h |
| Operating Temperature | -20°C~45°C | -20°C~45°C | -20°C~45°C |
| Dimension DxH | φ60x114 mm | φ60x114 mm | φ60x114 mm |
| Net weight | 113g | 113g | 113g |
| Replacement Of GLS | 60 W | 60 W | 60 W |

http://www.wiselite.com