



模位类别 Tool model	标记 Symbol	26工位 26 dies		36工位 36 dies		40工位 40 dies		38工位 38 dies		尺寸范围 Dimension range
		NO	AI	NO	AI	NO	AI	NO	AI	
A	●	10		20		18		17		φ3.0~φ12.7mm
B	●	10	2	10	2	16		15		φ12.7~φ31.75mm
C	●	2		2		2		2		φ31.75~φ50.8mm
D	●	2		2		2	2	1	2	φ50.8~φ88.9mm
E	●							1		φ88.9~φ114.3mm

HPQ系列数控转塔冲床参数  
Parameters of HPQ CNC turret punch press

参数	Parameter	单位Unit	HPQ-3044	HPQ-3047	HPQ-3048	HPQ-3057	HPQ-3058
公称力	Nominal pressure	kN	300	300	300	300	300
最大加工板材尺寸 (含一次再定位)	Max. sheet dimension (including first positioning)	mm	1250×2500	1250×4000	1250×5000	1500×4000	1500×5000
最大加工板材厚度	碳钢板 Carbon steel sheet	mm	6.35	6.35	6.35	6.35	6.35
Max. sheet thickness	不锈钢板 Stainless steel sheet	mm	4	4	4	4	4
一次冲孔最大直径	Max. one-time punching diameter	mm	φ88.9	φ88.9	φ88.9	φ88.9	φ88.9
标配模位数	Dies		40	40	40	40	40
冲孔精度	Punching accuracy	mm	±0.1	±0.1	±0.1	±0.1	±0.1
冲头冲压频次	Punching times per minute	cpm	1750	1750	1750	1750	1750
最高冲孔频率 (1mm步距 6mm冲程)	Max. punching frequency (1mm step 6mm punching stroke)	cpm	690	690	690	690	690
最高冲孔频率 (25.4mm步距 6mm冲程)	Max. punching frequency (25.4mm step 6mm punching stroke)	cpm	330	330	330	330	330
板材最大移动速度	Max. sheet speed	m/min	102	102	102	102	102
转盘转速	Turret speed	rpm	30	30	30	30	30
控制轴数	Axes of control		5(X, Y, Z, T, C)	5(X, Y, Z, T, C)	5(X, Y, Z, T, C)	5(X, Y, Z, T, C)	5(X, Y, Z, T, C)
总功率	Main power	kW	21	23	24	23	24
气源	Air pressure	Mpa	0.6	0.6	0.6	0.6	0.6
外形尺寸 Overall dimensions	长 Length	mm	5800	5800	5800	6300	6300
	宽 Width	mm	2300	4000	5000	4000	5000
	高 Height	mm	2200	2200	2200	2200	2200
重量	Weight	kg	14500	15500	16500	18500	19500

HPI系列数控转塔冲床参数  
Parameters of HPI CNC turret punch press

参数	Parameter	单位Unit	HPI-3044	HPI-3047	HPI-3048	HPI-3057	HPI-3058
公称力	Nominal pressure	kN	300	300	300	300	300
最大加工板材尺寸 (含一次再定位)	Max. sheet dimension (including first positioning)	mm	1250×2500	1250×4000	1250×5000	1500×4000	1500×5000
最大加工板材厚度	碳钢板 Carbon steel sheet	mm	6.35	6.35	6.35	6.35	6.35
Max. sheet thickness	不锈钢板 Stainless steel sheet	mm	4	4	4	4	4
一次冲孔最大直径	Max. one-time punching diameter	mm	φ88.9	φ88.9	φ88.9	φ88.9	φ88.9
标配模位数	Dies		36	36	36	36	36
冲孔精度	Punching accuracy	mm	±0.1	±0.1	±0.1	±0.1	±0.1
冲头冲压频次	Punching times per minute	cpm	1000	1000	1000	1000	1000
最高冲孔频率 (1mm步距 6mm冲程)	Max. punching frequency (1mm step 6mm punching stroke)	cpm	530	530	530	530	530
最高冲孔频率 (25.4mm步距 6mm冲程)	Max. punching frequency (25.4mm step 6mm punching stroke)	cpm	295	295	295	295	295
板材最大移动速度	Max. sheet speed	m/min	102	102	102	102	102
转盘转速	Turret speed	rpm	30	30	30	30	30
控制轴数	Axes of control		5(X, Y, Z, T, C)	5(X, Y, Z, T, C)	5(X, Y, Z, T, C)	5(X, Y, Z, T, C)	5(X, Y, Z, T, C)
总功率	Main power	kW	21	23	24	23	24
气源	Air pressure	Mpa	0.6	0.6	0.6	0.6	0.6
外形尺寸 Overall dimensions	长 Length	mm	5600	5600	5600	6100	6100
	宽 Width	mm	2300	4000	5000	4000	5000
	高 Height	mm	2200	2200	2200	2200	2200
重量	Weight	kg	14000	15000	16000	18000	19000

HPH系列数控转塔冲床参数  
Parameters of HPH CNC turret punch press

参数	Parameter	单位Unit	HPH-3044/5044	HPH-3047/5047	HPH-3048/5048	HPH-3057/5057	HPH-3058/5058
公称力	Nominal pressure	kN	300/500	300/500	300/500	300/500	300/500
最大加工板材尺寸 (含一次再定位)	Max. sheet dimension (including first positioning)	mm	1250×2500	1250×4000	1250×5000	1500×4000	1500×5000
最大加工板材厚度	碳钢板 Carbon steel sheet	mm	6.35/8	6.35/8	6.35/8	6.35/8	6.35/8
Max. sheet thickness	不锈钢板 Stainless steel sheet	mm	4/6	4/6	4/6	4/6	4/6
一次冲孔最大直径	Max. one-time punching diameter	mm	φ88.9	φ88.9	φ88.9	φ88.9	φ88.9
标配模位数	Dies		26	26	26	26	26
冲孔精度	Punching accuracy	mm	±0.1	±0.1	±0.1	±0.1	±0.1
冲头冲压频次	Punching times per minute	cpm	600/800	600/800	600/800	600/800	600/800
最高冲孔频率 (1mm步距 6mm冲程)	Max. punching frequency (1mm step 6mm punching stroke)	cpm	320/340	320/340	320/340	320/340	320/340
最高冲孔频率 (25.4mm步距 6mm冲程)	Max. punching frequency (25.4mm step 6mm punching stroke)	cpm	230/240	230/240	230/240	230/240	230/240
板材最大移动速度	Max. sheet speed	m/min	102	102	102	102	102
转盘转速	Turret speed	rpm	30	30	30	30	30
控制轴数	Axes of control		4(X, Y, T, C)	4(X, Y, T, C)	4(X, Y, T, C)	4(X, Y, T, C)	4(X, Y, T, C)
总功率	Main power	kW	21	23	24	23	24
气源	Air pressure	Mpa	0.6	0.6	0.6	0.6	0.6
外形尺寸 Overall dimensions	长 Length	mm	5600/5800	5600/5800	5600/5800	6100/6300	6100/6300
	宽 Width	mm	2300	4000	5000	4000	5000
	高 Height	mm	2200/2300	2200/2300	2200/2300	2200/2300	2200/2300
重量	Weight	kg	14000/21000	15000/22000	16000/22500	18000/24500	19000/25500