

WEH Series Hydraulic Sheet Metal Pressbrakes

- ▼ 坚固的刚性扭轴设计，确保滑块运动同步
- ▼ 内置式机械挡块，确保滑块精确定位
- ▼ 德国Bosch-Rexroth阀堆，确保液压系统稳定可靠
- ▼ E10系统精确显示滑块、后挡料位置
- ▼ Stable Torque bar design with rigidity assuring the synchronized movement of ram
- ▼ Build-in block assuring the precise positioning of ram
- ▼ Bosch-Rexroth valve block from Germany, assuring hydraulic system stable and reliable
- ▼ Ram and back gauge position can be displayed accurately by E10 system



E10数显系统
E-10 digital readout system

WEH系列液压板料折弯机参数
Parameter of WEH(K) series hydraulic sheet metal pressbrake

规格参数	Specifications	单位 Unit	40/2000	63/2500	80/3200	110/3100	110/4100	160/3100	160/4100	220/3100	220/4100	250/3100	250/4100	300/3100	300/4100
公称压力	Nominal pressure	kN	400	630	800	1100	1100	1600	1600	2200	2200	2500	2500	3000	3000
工作台长度	Length of table	mm	2000	2500	3200	3100	4100	3100	4100	3100	4100	3100	4100	3100	4100
立柱间距	Distance between uprights	mm	1590	1970	2600	2600	3600	2600	3600	2600	3600	2600	3600	2600	3600
喉口深度	Throat depth	mm	250	250	320	350	350	350	350	410	410	410	410	410	410
开启高度	Open height	mm	380	390	420	420	420	450	450	450	450	560	560	560	560
快下速度	Open height	mm/s	90	90	90	100	100	100	100	90	90	100	100	90	90
工作速度	Pressing speed	mm/s	≥12	≥8	≥7	≥10	≥10	≥8.5	≥8.5	≥7	≥7	≥9.5	≥9.5	≥9	≥9
返程速度	Return speed	mm/s	>100	54	50	85	85	95	95	85	85	125	125	120	120
滑块行程	Stroke of ram	mm	100	100	150	150	150	160	160	160	160	250	250	250	250
油箱容积	Capacity of oil tank	L	145	200	300	400	550	400	550	400	550	620	850	620	850
主电机功率	Main motor	kW	4	4	7.5	7.5	7.5	11	11	15	15	18.5	18.5	22	22
机器总长	Length of machine tool	mm	2220	2680	3360	3360	4360	3360	4360	3380	4360	3380	4220	3390	4230
机器宽度	Width of machine tool	mm	1350	1420	1520	1630	1630	1840	1840	1970	1970	1925	1925	2190	2190
机器高度	Height of machine tool	mm	2100	2200	2350	2580	2580	2670	2670	2760	2860	3160	3160	3210	3210
机器重量(约)	Weight of machine tool	kg	2900	3980	6250	7500	8700	10100	11800	12000	14500	15040	17740	18100	21000