







Product image	Description	Frok finish	Wheel diameter (mm)	Wheel width (mm)	Top plate /stem size (mm)	Hole spacing (mm)	Overall height (mm)	Fork thickness (mm)	Top plate thickness (mm)	Load capacity (kg)	New price (RM)
	Shock absorbing caster, PU on cast iron wheel, double ball bearings, fixed.	Galvanized	150	50	140*110	115*86-97*7 1	226	5.0	5.0	80~350	63.00
	Shock absorbing caster, PU on cast iron wheel, double ball bearings, swivel.	Galvanized	150	50	140*110	115*86-97*7 1	226	5.0	5.0	80~350	69.75
	Shock absorbing caster, PU on cast iron wheel, double ball bearings, swivel with brake	Galvanized	150	50	140*110	115*86-97*7 1	226	5.0	5.0	80~350	81.00
	Shock absorbing caster, PU on cast iron wheel, double ball bearings, fixed.	Blue powder coating	150	50	140*110	115*86-97*7 1	226	5.0	5.0	80~350	66.00
	Shock absorbing caster, PU on cast iron wheel, double ball bearings, swivel.	Blue powder coating	150	50	140*110	115*86-97*7 1	226	5.0	5.0	80~350	72.00
	Shock absorbing caster, PU on cast iron wheel, double ball bearings, swivel with brake	Blue powder coating	150	50	140*110	115*86-97*7 1	226	5.0	5.0	80~350	83.00

WOO KYUNG P&J LOGISTIC (M) SDN BHD