

型号 Model	气缸容积 Displacement	冷却方式 Cooling	电机类型 Motor Type	制冷量 Cooling Capacity			COP			认证 Certification	最大高度“A” Max. Height "A"
				ASHRAE		CECOMAF	ASHRAE		CECOMAF		
				-23.3°C		-25°C	-23.3°C		-25°C		
				W	Btu	W	W/W	EER	W/W		

LBP

220-240V 50HZ R134a

T系列 T Series

ATA72X	7.2	ST/OC	RSIR	205	699	155.3	1.35	4.6	1.05	CCC/CB/VDE	185/188
ATA80X	8.1	ST/OC	RSIR	230	785	174.2	1.35	4.6	1.05	CCC/CB	185/188
ATK72X	7.2	ST/OC	RSCR	205	699	154.0	1.40	4.8	1.09	CCC/CB/VDE/CE	185/188
ATK80X	8.1	ST/OC	RSCR	230	785	174.0	1.40	4.8	1.09	CCC/CB	185/188
▲ATD50V	5.0	ST	RSIR	140	478	105.2	1.25	4.3	0.98	CCC/CB	182
ATD66X	6.6	ST/OC	RSIR	190	648	142.8	1.25	4.3	0.98	CCC/CB	182
△ATA50K	5.0	ST	RSIR	144	491	108.9	1.35	4.6	1.05	CCC/CB	182/185
△ATA66K	6.6	ST	RSIR	190	648	142.8	1.25	4.3	0.98	CCC/CB	182
ATA66K(OC)	6.6	OC	RSIR	190	648	143.7	1.35	4.6	1.05	CCC/CB	188
ATA72K(OC)	7.2	OC	RSIR	205	699	154.0	1.35	4.6	1.05	CCC/CB	188
ATK55	5.5	ST	RSCR	160	546	121.0	1.35	4.6	1.05	CCC/CB	185
ATK60	6.0	ST	RSCR	180	614	135.0	1.51	5.2	1.18	CCC/CB/CE	185
ATK66	6.6	ST	RSCR	192	655	144.0	1.55	5.3	1.21	CCC/CB/CE	185
ATK72	7.2	ST	RSCR	205	699	154.0	1.51	5.2	1.18	CCC/CB	185
ATK80	8.1	ST	RSCR	230	785	174.0	1.51	5.2	1.18	CCC/CB	185
ATZ55	5.5	ST	RSCR	170	580	128.3	1.62	5.5	1.26	CB	185

S系列 S Series

ASF43X	4.3	ST	RSCR	117	399	87.7	1.35	4.6	1.05	CCC/CB	162.5
ASF51X	5.1	ST	RSCR	144	491	108.0	1.35	4.6	1.05	CCC/CB	162.5
△ASD43K	4.3	ST	RSIR	117	399	87.8	1.15	3.9	0.88	CCC/CB/VDE	167
△ASD53K	5.1	ST	RSIR	144	491	108.1	1.20	4.1	0.94	CCC/CB/VDE	171
△ASF43K	4.3	ST	RSCR	117	399	87.4	1.40	4.8	1.10	CB	162.5
△ASF53K	5.1	ST	RSCR	144	491	107.8	1.41	4.8	1.10	CB	171
△ASF65K	6.5	ST	RSCR	176	601	132.0	1.41	4.8	1.10	CB	171

Y系列 Y Series

AYA25X	2.5	ST	RSIR	66	225	49.4	1.10	3.8	0.87	CCC/CB	141
AYA30X	3.0	ST	RSIR	80	273	59.9	1.10	3.8	0.87	VDE	141

N系列 N Series

ANA80	8.0	ST/OC	RSIR	235	802	176.0	1.35	4.6	1.06	CCC/VDE	193
ANA90	8.8	ST/OC	RSIR	250	853	187.3	1.35	4.6	1.06	CCC/VDE	193
ANZ80	8.0	ST	RSCR	235	802	176.0	1.62	5.5	1.28	CCC	196
ANZ90	8.8	ST	RSCR	250	853	187.3	1.62	5.5	1.28	CCC	196
△ANA90K	8.8	F/OC	CSIR	250	853	187.3	1.30	4.4	1.02	CB	196

注：带“△”的型号适用起动电压范围“160~260V”。

带“▲”的型号适用起动电压范围“150~230V”。

Note: The models with "△" are available for start voltage "160V~260V".

The models with "▲" are available for start voltage "150V~230V".