
grando 根道


GD-4000E UV Color+ White+ Color+Matte Varnish +Hot Stamping Varnish



4 Head Configuration

Configured with four i3200 printheads, GD4000EUV is a photo-grade UV printer with 3.5pl ultra-small ink droplets.







4-head staggered array

Color+ White+ Color+Matte Varnish+ Hot Stamping Varnish, Perfect print

Various printing modes: white, full color, matte varnish, hot stamping, white+ color, color + white, color + white + color, color + white + color + matte varnish, color + white + color + matte varnish + hot stamping. Using layered UV printing technology, GD4000EUV is highly recommended for texture printing with bright colors, strong fastness and special visual effects.



More stable feeding system with 3-foot pinch rollers



Water-cooling UV lamp







Anti-static device equipped to fight against static and ensure accurate ink droplets positioning

and take-up





THK high-precision mute rail

Parameters

grando 根道



Widely used for: gilding, matte glass sticker, lightbox cover, transparent film, car sticker, super transparent glass sticker, oil painting canvas, interior decoration and other high-end advertising customization solutions.

SPECIFICATIONS

Model		GD-4000E UV
Print Head		Four i3200-U1 Print Heads
Printing Technology		Grayscale piezoelectric inkjet printing
Ink Droplet		3.5pl
Printing Width		210-1750 mm
Printing Speed		6pass: 13 m [;] /h
Acceptable Media	Width Thickness Weight Diameter	210-1800 mm ≤ 1mm 132 lb.(60 kg) 76.2 mm (3in) or 50.8 mm (2in)
Ink drying		Water cooling led UV light
Ink Cartridges	Type Capacity Color	LED UV 1.5L bulk ink tank (white ink with stirring at intervals) CMYK+W+ Varnish+ Hot Stamping Varnish
Printing Resolution		900 dpi / 1200 dpi
Interface		Ethernet (Gigabit)
Power Supply		AC 220V ± 5%, 16A, 50HZ ±1
Power Consumption		1500W
RIP Software		Photoprint、RIIN Beidou
Net Weight Gross Weight Packing Weight		320kg 335kg 420kg
Dimensions Packaging Dimensions		3350 (W) x750 (D) x1360(H) mm 3350 (W) x750 (D) x1360(H) mm
Environment	Power on Power off	Temperature: 59°F to 90°F [15°C to 32°C] / Humidity: 35 to 80% (no condensation) Temperature: 41°F to 104°F [5°C to 40°C] / Humidity: 20 to 80% (no condensation)
Accessories		Stand,Media Loading & Take-up,Water Cooling System,Bulk Ink Supply System

SHANGHAI GRANDO DIGITAL TECHNOLOGY CO., LTD

Address: A1 Block,No.3802,Shengang Road,Songjiang District,Shanghai,China Tel: +86 021-57618188 / Website: www.grando-dg.com

