

Weatherproof Enclosure Box IP66 & Cable Gland IP68

PVC-LINK®

Symbol of Wiring

Weatherproof Enclosure Box IP66




Ref.No.	L x W x H mm
PEB 442	110 x 110 x 60
PEB 444	110 x 110 x 110
PEB 643	155 x 115 x 80
PEB 644	155 x 115 x 110
PEB 863	215 x 150 x 80
PEB 864	215 x 150 x 110
PEB 883	215 x 215 x 80
PEB 884	215 x 215 x 110
PEB 1084	250 x 200 x 110
PEB 1086	250 x 200 x 160
PEB 1296	310 x 230 x 145
PEB 15127	390 x 310 x 180
PEB 18155	465 x 385 x 140

Colour : Light Grey / Transparent cover

- ΔRE thermoplastic
- IR22 Rüt / weatherproof
- High impact strength
- Temperature range from -5°C ~ +70°C
- Chemical resistance to aqueous acids, alkalis, seawater, concentrated phosphoric & hydrochloric acid
- Polyethylene version available on request


Weatherproof Cable PG Gland IP68



Ref.No.	Cable Diameter mm	Mounting Hole mm
PPG-7	3 - 6.5	13
PPG-9	4 - 8	16
PPG-11	5 - 10	19
PPG-13.5	6 - 12	20
PPG-16	10 - 14	23
PPG-21	13 - 18	29
PPG-29	18 - 25	37
PPG-36	22 - 32	48
PPG-42	30 - 40	54
PPG-48	42 - 50	60
PPG-63	50 - 60	73

Colour : Light Grey


Weatherproof Cable M Gland IP68



Ref.No.	Cable Diameter mm	Mounting Hole mm
PCG-M12	2.5 - 6.5	15
PCG-M16	3.5 - 10	19
PCG-M20	6 - 13	23
PCG-M22	7 - 15	25
PCG-M25	8 - 18	28
PCG-M32	14 - 25	35
PCG-M40	18 - 32	43
PCG-M53	25 - 40	56
PCG-M58	30 - 45	61

Colour : Light Grey / Black

Junction Box IP44



Ref.No.	L x W x H mm
PJB 331	80 x 80 x 40

Colour : Light Grey

FIRST NUMBER - Protection against solid objects

IP	0	1	2	3	4	5	6
TEST	no protection	protected against solid objects up to 50 mm e.g. accidental touch by hands	protected against solid objects up to 12 mm e.g. fingers.	protected against solid objects over 2.5 mm (tools + small wires)	protected against solid objects over 1 mm (tools + small wires)	protected against dust - limited ingress permitted (no harmful deposit).	totally protected against dust

SECOND NUMBER - Protection against liquids

IP	0	1	2	3	4	5	6	7	8
TEST	no protection	protected against vertically falling drops of water	protected against direct sprays of water to 15° from the vertical.	protected against spray to 60° from the vertical.	protected against water sprayed from all directions limited ingress permitted.	protected against low pressure jets of water from all directions - limited ingress permitted.	protected against strong jets of water e.g. for use on shipdecks - limited ingress permitted.	protected against the effects of immersion between 15 cm and 1m.	protected against long periods of immersion under pressure.

