

RG6 A112 COAXIAL CABLE

APPLICATION


- ❖ High quality RG Type Coaxial cable,75 Ohm suitable for many applications, particularly broadcast and CATV installations.

PRODUCT FACTS

- ❖ INDOOR USE , Accepts 900m longer
- ❖ Suitable for shop-lot, home, factory

PRODUCT CODE

❖ **A112**



TECHNICAL DATA

ITEM		UNIT	SPEC. VALUE
Inner Conductor	Material	---	Bare Copper
	Dia.(approx)	mm	1.00 ± 0.15
Insulation	Material	---	Foam Polyethylene
	Nom. Thickness	mm	1.56 ± 0.18
	Dia.(approx)	mm	4.80 ± 0.18
	Colour	---	Natural
Outer Conductor	Type	---	Braid
	Material	---	Aluminum LC
	Coverage	%	95 ± 3
	Dia.(approx)	mm	0.12 x 128
Jacket	Material	---	PVC
	Nom. Thickness	mm	0.80 ± 0.2
	Colour	---	Black
	Dia.(approx)	mm	7.00 ± 0.20
CHARACTERISTICS			
DC Conductor Resistance at 20°C			< 26.1Ω/100m
Insulation Resistance at 20°C			> 200 MΩ.m
Nominal Velocity of Propagation			66.6 ± 3%
Capacitance			67 ± 5 pF/m
Characteristic Impedance at 20°C,200MHz			75 ± 5Ω
PACKING			WEIGHT
Wooden drum - 370x370x265(mm)	500m/drum		22.kg