



Part No	lumiDL1500C4	lumiDL1500N4	lumiDL1500W4
Correlated Color Temp $\pm$ 5%	Cool White 5700K	Natural White 4000K	Warm White 3000K
CRI	Ra > 80 / R9 > 0		
Luminance $\pm$ 5%	1420 lumens		1300 lumens
Rated Wattage	12W		
Lumens per Watt	118		108
Input Power (DC)	180-265V 50/60Hz		
	240V @ 50mA		
Power Factor	> 0.9 @240VAC		
Working Temp	Ambient Temperature Max 50°C		
Projection Angle	60°		
Dimension / Size	4" @ 105mm ( $\phi$ ) x 55mm (H) Round Face 4" @ 105mm (W) x 105mm (L) x 55mm (H) Square Face		
Opening Hole	4" @ 95mm		
Weight $\pm$ 5%	300g		
Warranty	2 Years		
Optional	TRIAC Dimming & Zigbee Wireless Dimming option available		



Square Face Plate



Round Face Plate

lumiDL (6" diameter)



lumiDL (8" diameter)



Part No	lumiDL 1000 C6 / C8	lumiDL 1000 N6 / N8	lumiDL 1000 W6 / W8	lumiDL 1500 C6 / C8	lumiDL 1500 N6 / N8	lumiDL 1500 W6 / W8	lumiDL 2000 C8	lumiDL 2000 N8	lumiDL 2000 W8	lumiDL 3000 C8	lumiDL 3000 N8	lumiDL 3000 W8
Correlated Color Temp ± 5%	Cool W 6000K	Natural W 4000K	Warm W 3000K	Cool W 6000K	Natural W 4000K	Warm W 3000k	Cool W 6000K	Natural W 4000K	Warm W 3000k	Cool W 6000K	Natural W 4000K	Warm W 3000k
CRI	Ra > 80 / R9 > 0											
Luminance ± 5%	1120 lm		1000 lm	1500 lm		1350 lm	2250 lm		2020 lm	3360 lm		3030 lm
Rated Wattage	9W			12W			18W			28W		
Lumens per Watt	125		112	125		112	125		112	120		112
Input Power (DC)	180-265V 50/60Hz											
	240V @ 40mA			240V @50mA			240V @.75mA			240V @ 120mA		
Power Factor	> 0.85 @240VAC			> 0.9 @240VAC								
Working Temp	Ambient Temperature Max 50°C											
Projection Angle	120°											
Dimension / Size	6" @190mm (Ø) x 55mm (H)						8" @235mm (Ø) x 55mm (H)					
Opening Hole	6" @165mm						8" @ 210mm					
Weight ± 5%	6" @ 110g						8" @140g					
Warranty	2 Years											
Optional	TRIAC Dimming & Zigbee Wireless Dimming option available											

lumiDN (8" diameter)



lumiDN (10" diameter)



Part No	lumiDN3800 C8 / C10	lumiDN3800 N8 / N10	lumiDN3800 W8 / W10	lumiDN7000 C8 / C10	lumiDN7000 N8 / N10	lumiDN7000 W8 / W10
Correlated Color Temp ± 5%	Cool White 5000 - 5700K	Natural White 4000K	Warm White 3000K	Cool White 5000 -5700K	Natural White 4000K	Warm White 3000k
CRI	Ra > 80 / R9 > 0					
Luminance ± 5%	3800 lumens		3500 lumens	7000 lumens		6500 lumens
Rated Wattage	30W			60W		
Lumens per Watt	126		116	116		108
Input Power (DC)	180-265V 50/60Hz					
	240V @ 130mA			240V @250mA		
Power Factor	> 0.9 @240VAC			> 0.9 @240VAC		
Working Temp	Ambient Temperature Max 50°C					
Projection Angle	60°					
Dimension / Size	8" @230mm (Ø) x 155mm (H)			10" @280mm (Ø) x 180mm (H)		
Opening Hole	8" @200mm			10" @ 250mm		
Weight ± 5%	8" @ 150g			10" @180g		
Warranty	2 Years					
Optional	TRIAC Dimming & Zigbee Wireless Dimming option available					