

Individual Swivelling Mechanism for greater flexibility and customisation



Single Round Unit




Rectangle Housing




Part No	lumiBA1500C	lumiBA1500N	lumiBA1500W
Correlated Color Temp ± 5%	Cool White 5700K	Natural White 4000K	Warm White 3000K
CRI	Ra > 80 / R9 > 0		
Luminance ± 5%	1500 lumens		1350 lumens
Rated Wattage	12W		
Lumens per Watt	125		112
Input Power (DC)	180-265V 50/60Hz 240V @ 50mA		
Power Factor	> 0.9 @240VAC		
Working Temp	Ambient Temperature Max 50°C		
Projection Angle	36°		
Warranty	1 Year		
Optional	TRIAC Dimming & Zigbee Wireless Dimming option available		

Note: * ± 10% Lux accuracy * Test environment @ 25°C *Specifications subject to change without prior notice.
* Product images are for illustration purposes only.


Adjustable Fitting Configuration




Single Round Fitting
Part No: HAR111S
Size: 170mm (Ø)
Opening: 155mm (Ø)
Weight: 500g



Single Square Fitting
Part No: HAR111SQ
Size: 175mm x 175mm
Opening: 155mm x 155mm
Weight: 500g



Double Fitting
Part No: HAR111D
Size: 325mm x 175mm
Opening: 305mm x 155mm
Weight: 1000g



Triple Fitting
Part No: HAR111T
Size: 475mm x 175mm
Opening: 455mm x 155mm
Weight: 1500g