
# 316 STAINLESS STEEL HEATERS

## Superior Corrosion and Contamination Resistance When You Need It



- Corrosion resistance all wetted surfaces are made of 316 stainless steel.
- Contamination prevention all wetted surfaces are passivated to remove free iron from the heater surface.

## **Fast Deliveries**

More than 150 assembly stock designs are available for shipment in five days or less. Heaters same as stock, except for voltage and/or wattage, are available for shipment in 10 days or less.

Call us. We offer the widest range of **STOCK** 316 stainless steel heaters in the business.

## **Common Applications**

- Ultrasonic cleaning for:
  Circuit boards
  Electronic components
  Disk drive components
  Plastic parts
  Laboratory test tubes
  Glassware
  Medical instruments
  Metal stampings
  Optical lenses
  Glass and ceramic parts
  Jewelry
  Precious stones
  Watches and coins
- In-line process heating
- Hot runner molds
- Aqueous and semi-aqueous cleaning
- Spot-free rinse at car washes



## **Features and Benefits**

#### **Corrosion resistant**

Long heater life

## Sheath temperatures to 1200°F (649°C)

· Suitable for demanding applications

#### Oxide-free elements

Prevents contamination of your process

### All wetted parts passivated

· Prevents contamination of your process

#### 316 stainless steel contains molybdenum

Eliminates pitting

## **UL®** and CSA recognition

Assured safety and agency approved




HAN-316-1008

Watlow® is a registered trademark of Watlow Electric Manufacturing Company.

## **WATROD Tubular Heaters**

- Fully annealed for forming into virtually any shape and size to fit your application requirements.
- 36 standard bend formations: spirals, compound bends and multi-axis or multiplane configurations.
- A variety of termination and mounting options: threaded stud terminals or lead wires and bulkheads for liquid tight mounting.
- Specially sealed to prevent moisture contamination from entering the heater sheath.



WATROD Tubular Heater

## **Circulation Heaters**

- Complete assemblies with heating elements, vessels, insulation, terminal enclosure, mounting brackets, and inlet and outlet connections.
- NPT connections and mounting blocks allow for easy installation. Optional flanged connections available.
- All wetted parts are passivated 316 stainless steel to minimize contamination of the process.
- Specifically designed for in line processes requiring the heating of flowing gases or liquids.
- Optional thermostats, process or high limit thermocouples and electrical enclosures available.



Circulation Heater

## Screw Plug and Flanged Immersion Heaters

- Stock voltages include 120V 1-phase, 240 and 480V 1- or 3-phase. Stock wattages from 3 to 150kW.
- All wetted parts are passivated 316 L stainless steel to minimize contamination of the process.
- Standard NEMA 1 electrical enclosures. Moisture and explosion resistant enclosures available.
- Special voltages, wattages, materials and sizes available upon request. Consult your local authorized sales agent or distributor.
- 21/2 inch NPT screw plug heater, and 4 and 6 inch ANSI flange heater stock configurations. Other sizes available.



Screw Plug Heater

## Corrosion

Corrosion occurs when the heater's outer sheath deteriorates due to chemical attacks from the material being heated. This allows contaminants to enter the heater. Watlow's 316 stainless steel sheath which contains molybdenum minimizes corrosion in various environments, especially in deionized or demineralized water applications.

Molybdenum eliminates pitting caused by chlorides, increases corrosion resistance to chemicals and solvents, and increases strength and ductility.

## **Contamination Prevention**

Watlow's 316 stainless steel heaters are passivated to reduce the possibility of contamination of your process from free iron and other contaminants.

316 stainless steel offers optimum resistance against these corrodants and more:

- Acid solutions
- Aluminum acetate
- Barium hydroxide
- Bisulfate
- Butyl acetate
- Calcium bisulfate
- Deionized water
- Magnesium sulfate
- Electroplating baths
- Potassium shlorate
- Potassium chloride
- Process water

Consult factory for proper watt densities for these various solutions.

To be automatically connected to the nearest North American Technical Sales Office:

## 1-800-WATLOW2 • www.watlow.com • info@watlow.com